



Product Comparison

Are you comparing
Apples



to Apples?

| Cres Cor RO-151-FWUA-18D | Winston CAT522 | Cres Cor Advantage |
|--|---|--|
| CAPACITY: (18) 18" x 26" or (36) 12" x 20" pans, 18 sets universal angles on 1-1/2" centers. | CAPACITY: (14) 18" x 26" or (28) 12" x 20" pans, 14 sets universal angles on 3-1/2" centers. | Cres Cor's heavy duty solid stainless steel angles won't rust or break. Easily adjustable to hold a variety of pan sizes. |
| BODY CONSTRUCTION: 22 ga. stainless steel body with stainless steel internal frame. Automatic water fill hook-up at rear. Interior coved corners 1-1/2" fiberglass in doors top and base, 2" in sidewalls. | BODY CONSTRUCTION: Stainless steel throughout. Connect to water supply through saddle valve and tubing kit at rear (supplied). No coved corners. Insulation on top, sides, and doors. | Cres Cor has a strong internal frame for structure and securing hardware. Thick insulation throughout has better heat retention. Coved corners are easier to clean and sanitize. |
| WATER PAN: 4 gal. water reservoir with drain. | WATER PAN: 2 gal. water reservoir with tube. | Holds more water and easier to drain |
| DOOR: 22 ga. stainless steel dutch doors. Field reversible. Embossed pan stop. Anti-microbial ceramic magnetic pull latch. Self-closing, lift-off hinges of heavy duty steel. Silicone door gaskets | DOOR: Stainless steel dutch doors. Field reversible. Magnetic door latch. Lift-off hinges. | Anti-microbial latches protect against spreading germs. Silicone door gaskets prevent temperature loss with proper seal. |
| CASTERS: 5" dia. swivel modulus, two with brakes. | CASTERS: 5" dia., two with brakes. | High modulus wheel for quiet rolling and shock absorption on uneven or rough surfaces. |
| CONTROLS: Digital LED solid state controls top mounted. (18) programmable menu buttons. Lighted on/off push button. 1-1/2" probe included. | CONTROLS: Computerized processor controls top mounted. (8) programmable menu buttons. Lighted on/off rocker switch. Food probe undertermined. | Easy to read LED display with more reliable push button power button. Standard with food probe cooking. |
| ELECTRICAL: 12,000 Watts, 208 Volt, 3 Phase, 50 Amp. 12,000 Watts, 240 Volt, 3 Phase, 50 Amp. 10' 12/3 ga. NEMA 15-50 cord and plug NSF, CSA-US, CSA-C listed | ELECTRICAL: 11,215 Watts, 208 Volt, 3 Phase, 50 Amp. 11,215 Watts, 240 Volt, 3 Phase, 50 Amp. 7' NEMA 15-50 cord and plug NSF, UL, UL-C listed | Quick to reheat after door opening, and longer cord gives more room for access while cabinet is plugged in. |
| EXTERIOR DIMENSIONS: 37-3/4"W x 28-3/4"D x 73-11/16"H | EXTERIOR DIMENSIONS: 34-1/2"W x 27-3/5"D x 76-1/10"H | |
| SHIP WEIGHT: 392 lbs. | SHIP WEIGHT: 410 lbs. | |
| WARRANTY: 3-Year Parts, 1-Year Labor 5-Year parts for K-12 schools | WARRANTY: 1-Year Limited | Warranty is 3x longer on parts coverage and 5x better for K-12 schools! |
| | | Cres Cor is built stronger to last longer! |



Product Comparison

Are you comparing
Apples



to Apples?

| Cres Cor RO-151-FWUA-18D | FWE RH18HO | Cres Cor Advantage |
|--|---|---|
| CAPACITY: (18) 18" x 26" or (36) 12" x 20" pans, 18 sets of stainless steel wire universal angles on 1-1/2" centers. Cabinet will hold 34 sets of angles. | CAPACITY: (18) 18" x 26" pans, 18 welded rod-style tray slides, nickel chrome plated on 1-1/2" spacing. | Cres Cor's heavy duty solid stainless steel angles won't rust or break. |
| BODY CONSTRUCTION: 22 ga. stainless steel body with 18 ga. stainless steel internal frame. Automatic water fill hook-up at rear. Interior coved corners. 1-1/2" fiberglass in doors top and base, 2" in sidewalls. | BODY CONSTRUCTION: 18 ga. stainless steel throughout. Welded tubular base. Connect to water supply through saddle valve and tubing kit at rear (supplied). Interior coved corners. Fiberglass minimum 2" max 4" throughout. | Cres Cor has a strong internal frame for structure and securing hardware. Thick insulation throughout has better heat retention. Coved corners are easier to clean and sanitize. |
| WATER PAN: 4 gal. water reservoir with drain. | WATER PAN: unknown | Holds water and easier to drain |
| DOOR: 22 ga. stainless steel dutch doors. Field reversible. Embossed pan stop. Anti-microbial ceramic magnetic pull latch. Self-closing, lift-off hinges of heavy duty steel. Silicone door gaskets | DOOR: 18 ga. stainless steel dutch doors. Not field reversible. Magnetic door latch. Lift-off hinges. Gasketless doors. | Anti-microbial latches protect against spreading germs. Silicone door gaskets prevent temperature loss with proper seal. |
| CASTERS: 5" dia. swivel modulus, two with brakes. | CASTERS: 5" dia., polyurethane, two with brakes. | High modulus wheel for quiet rolling and shock absorption on uneven or rough surfaces. |
| CONTROLS: Digital LED solid state controls top mounted. (18) programmable menu buttons. Lighted on/off push button. 1-1/2" probe included. | CONTROLS: LED thermometer, analog controls. (12) programmable menu buttons. On/off switch. Food probe ready, probe not included. | Easy to read LED display with more reliable push button power button. Standard with food probe cooking. |
| ELECTRICAL: 12,000 Watts, 208 Volt, 3 Phase, 50 Amp. 12,000 Watts, 240 Volt, 3 Phase, 50 Amp. 10' 12/3 ga. NEMA 15-50 cord and plug NSF, CSA-US, CSA-C listed | ELECTRICAL: 11,170 Watts, 208 Volt, 3 Phase, 50 Amp. 14,720 Watts, 240 Volt, 3 Phase, 50 Amp. NEMA 15-50 cord and plug unknown length. NSF, CSA-US, CSA-C listed | Quick to reheat after door opening, and longer cord gives more room for access while cabinet is plugged in. |
| EXTERIOR DIMENSIONS: 37-3/4"W x 28-3/4"D x 73-11/16"H | EXTERIOR DIMENSIONS: 34-1/2"W x 27-3/5"D x 76-1/10"H | |
| SHIP WEIGHT: 392 lbs. | SHIP WEIGHT: 600 lbs. | |
| WARRANTY: 3-Year Parts, 1-Year Labor 5-Year parts for K-12 schools | WARRANTY: 2-Year Parts, 1-Year Labor | Warranty is longer on parts coverage and better for K-12 schools! |
| | | Cres Cor is built stronger to last longer! |