

3M™ Sky Blue Hi-Performance Burnish Pad 3050



Optimization & Performance for Softer Floor Finishes

Industry Standard for Floor Care

In 1958, 3M revolutionized floor maintenance with the introduction of the first floor pad made of synthetic fibers, abrasives and adhesives. 3M synthetic floor pads quickly became the industry standard. 3M's line of burnishing floor pads offers exceptional performance for a variety of mark removal and high-gloss renewal operations. Designed for use with all ultra high speed electric, battery and propane machines (1500–3000 RPM).

Introducing the NEW 3M™ Sky Blue Hi-Performance Burnish Pad 3050

Restores gloss to dull floors. Designed for frequent burnishing with less dust, point build-up and burning, this pad is an excellent addition to 3M's high-performing line of burnishing pads.

NEW!




Consistent Performance, Long Lasting Shine

NEW! 3M™ Sky Blue Hi-Performance Burnish Pad 3050

Burnishing floor pad optimized for use on softer floor finishes typically used in retail environments and burnished frequently.

- Better durability than competitive burnish pad designed for softer floor finishes
- Remarkable gloss improvement
- Designed to reduce burn marks, minimize dust, point build-up and swirl marks



Lab Testing

	Competitor A	3M™ Sky Blue Hi-Performance Burnish Pad 3050
Pad Life — Durability Evaluation (Pad Weight Loss After 70 Cycles)	42% of Wt. Lost	0.6% of Wt. Lost
High Spot Burn Test	Significant Abrasion/Burn	Minimal Abrasion/Burn
Donut Burn Test — Stationary Burnish	Significant Burn Marks	No/Minimal Burn Marks

Ordering Information

Product	UPC (500-48011-)	Size	Stock Number
	59826-5	17 in.	70-0715-9384-5
	59827-2	18 in.	70-0715-9385-2
3M™ Sky Blue Hi-Performance Burnish Pad 3050	59828-9	19 in.	70-0715-9386-0
	59825-8	20 in.	70-0715-9382-9
	59829-6	21 in.	70-0715-9387-8
	59830-2	24 in.	70-0715-9388-6
	59824-1	27 in.	70-0715-9381-1

3M™ Burnishing Floor Pads — Repair Finish and Improve Gloss and Image Clarity of Floor Surface

Recommended Steps for Burnishing:

1. Dust mop
2. Burnish only clean floors
3. Burnish to a high gloss using overlapping passes
4. Dust mop

Scuff and Mark Removal



3M™ Eraser Burnish Pad 3600
Removes black marks and returns gloss in fewer passes than other pads while producing less dust. Ideal for harder finishes and high traffic areas. Excellent durability and minimal finish removal.



3M™ Natural Blend Tan Pad 3500
Blend of natural and synthetic fibers. For use on harder finishes and high traffic conditions. Removes marks and scuffs while polishing.



3M™ Tan Burnish Pad 3400
Produces brilliant gloss while removing scuffs and marks. Exceptional durability and life. For use on harder finishes and high traffic conditions.

Gloss Improvement



3M™ TopLine Speed Burnish Pad 3200
Optimizes UHS burnishing on a wide variety of finishes. Combines black mark removal and gloss generation in one pad.



3M™ Natural Blend White Pad 3300
Blend of natural and synthetic fibers. Excellent results on a wide variety of finishes and traffic conditions. Provides consistent high gloss while minimizing swirl marks.

Soft Finish



3M™ Aqua Burnish Pad 3100
Produces brilliant gloss. Exceptional durability and life. The soft finish problem solver.



3M™ Sky Blue Hi-Performance Burnish Pad 3050
Provides greater durability and less dust, point build-up and burning while restoring gloss to dull floors. Ideal for softer floor finishes where frequent burnishing is required.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for user's particular purpose and suitable for user's method of application.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Warranty and Limited Remedy: 3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.



Building and Commercial Services Division
3M Center
St. Paul, MN 55144-1000
www.3M.com/building

3M is a trademark of 3M.
Used under license in Canada.
Please recycle. Printed in U.S.A.
© 3M 2012. All rights reserved.
78-8134-0520-2

How to Reach Us

For more information on 3M™ Floor Pads or to place an order, call your local 3M distributor. Or, for the name of your distributor, call **1-800-852-9722**. To speak to a technical support person, call **1-800-626-8578**. For general assistance, call **1-800-3M-HELPS**.