



Reach-Ins & Pass-Thrus

REFRIGERATORS & FREEZERS



Continental[®]
Refrigerator

INNOVATIVE DESIGNS FOR YOUR FOODSERVICE NEEDS

Reach-Ins & Pass-Thrus

Refrigerators & Freezers

Our Reach-In Refrigerators and Freezers are designed for performance and reliability that protects your long-term investment. We use the highest quality materials and components to provide the user with optimal product temperatures, exceptional food safety and the best value in today's foodservice market.

State-of-the-Art Designs

Continental Refrigerator has one of the most diversified commercial Reach-In product lines in the industry, with modern styling and standard features not found on other units.

Performance & Reliability

Performance-run tested for a minimum of 12 hours providing a highly sophisticated temperature analysis recording, exclusive to each cabinet.



FLEXIBILITY

Modifications Made Easy.

At Continental Refrigerator, we know the foodservice industry is an ever-changing environment. We are reminded of this every day through feedback from our customers, both directly and through our network of representatives. In fact, customer feedback has often lead to our custom engineering modifications becoming standard product features.

For this reason, we pride ourselves in delivering feature-rich refrigeration equipment solutions designed specifically for the commercial foodservice market. Whether it's kitchen ambient, food safety, limited space or storage challenges, our products are packed with flexible options that provide **real** operator benefits out of the box. This flexibility, a key differentiator of our products, enables our customers to modify base product features strategic to the way they operate their kitchen or bar environment.

Shown: 2RN

Standard Model



Half Doors



Laminated Doors



Half Doors (On Right Only),
Pan Slide Assemblies (On Right)

Glass Doors

6" Adjustable Legs

Consult factory for other modifications

Overview of Models & Standard Features

Standard Features

Stainless steel front, aluminum end panels and interior

Self-contained, performance-rated refrigeration system

Environmentally-safe R-290 refrigerant

(except 3-section Pass-Thru refrigerators & 2- and 3-section freezers)

Environmentally-safe R-134a refrigerant (3-section Pass-Thru refrigerators only)

R404A refrigerant (2- and 3-section freezers only)

3" Non-CFC polyurethane foam insulation

Smooth, polished, chrome door handles (solid doors)

Cam-action, lift-off hinges

Heavy-duty, epoxy-coated steel shelves

Automatic, electric condensate evaporator

Expansion valve system (some models)

Magnetic, snap-in door gaskets

Door locks

Snap-in door wiper (sliding glass doors)

5" high casters

Self-closing doors

LED interior lighting

Electronic controller w/ digital display & hi-low alarm

Automatic electric defrost (freezers/dual temp freezer section)

Triple-pane, tempered glass doors (hinged glass doors)


Double-pane, low-e, tempered glass doors (sliding glass doors)

High-efficiency PVC frame (sliding glass doors)


Widths




Slim Line
1 Section
17 3/4"




Slim Line
2 Section
36 1/4"




Standard
1 Section
26"




Standard
2 Section
52"




Standard
3 Section
78"




Extra-Wide (X)
1 Section
36 1/4"



Extra-Wide
1 Section
28 1/2"




Extra-Wide
2 Section
57"




Extra-Wide
3 Section
85 1/2"


Depths



Standard Depth
Reach-In
35 3/8"




Shallow Depth
Reach-In
29 1/4"




Standard Depth
Pass-Thru
38 3/4"


Door Styles



Hinged Solid
Full Door




Hinged Solid
Half Doors




Hinged Glass
Full Door



Hinged Glass
Half Doors




Sliding Glass
Full Doors




Sliding Glass
Half Doors


Optional Pan Slide Assemblies (not available for Shallow Depth models)




Stainless Steel Full & Half Section
for 18 x 26 or (2) 18 x 14 Pans
on 3" Center Bottom Supports
Holds (# pans/section): 16 (full), 8 (half)




Stainless Steel Full & Half Section
for 18 x 26 or (2) 18 x 14 Pans
on 3" Center Rim Supports
Holds (# pans/section): 16 (full), 8 (half)



Extra-Wide (E) Models Only
Universal Stainless Steel Full & Half Section
for (1) 18 x 26 or (2) 12 x 20 Pans
on 5" Center Bottom Supports
Holds (# pans/section): 10 (full), 5 (half)



Chrome-Plated Wire Full & Half Section
for 18 x 26 Pans on 2" Center Rim Supports
Holds (# pans/section): 21 (full),
9 top & 12 bottom (half)



Chrome-Plated Wire Full & Half Section
for 18 x 26 Pans on 2" Center Bottom Supports
Holds (# pans/section): 21 (full),
9 top & 12 bottom (half)

Optional Models:

-SA: Stainless steel exterior, aluminum interior
-SS: Stainless steel exterior & interior

Specifications - Standard & Slim Line Refrigerators

Standard Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1RN	1RNSA	1RNSS	26 x 35 3/8 x 82 1/4	1940	1/4+	310
	2RN	2RNSA	2RNSS	52 x 35 3/8 x 82 1/4	2560	1/3+	520
	3RN	3RNSA	3RNSS	78 x 35 3/8 x 82 1/4	4010	1/2	725
HALF DOORS	1RNHD	1RNSAHD	1RNSSH	26 x 35 3/8 x 82 1/4	1940	1/4+	310
	2RNHD	2RNSAHD	2RNSSH	52 x 35 3/8 x 82 1/4	2560	1/3+	520
	3RNHD	3RNSAHD	3RNSSH	78 x 35 3/8 x 82 1/4	4010	1/2	725
FULL DOORS SHALLOW DEPTH	1RSN	1RSNSA	1RSNSS	26 x 29 1/4 x 82 1/4	1940	1/4+	310
	2RSN	2RSNSA	2RSNSS	52 x 29 1/4 x 82 1/4	2560	1/3+	520
	3RSN	3RSNSA	3RSNSS	78 x 29 1/4 x 82 1/4	4010	1/2	725
HALF DOORS SHALLOW DEPTH	1RSNHD	1RSNSAHD	1RSNSSHD	26 x 29 1/4 x 82 1/4	1940	1/4+	310
	2RSNHD	2RSNSAHD	2RSNSSHD	52 x 29 1/4 x 82 1/4	2560	1/3+	520
	3RSNHD	3RSNSAHD	3RSNSSHD	78 x 29 1/4 x 82 1/4	4010	1/2	725

Standard Pass-Thru Models

FULL DOORS	1RNPT	1RNSAPT	1RNSSPT	26 x 39 x 82 1/4	1940	1/4+	340
	2RNPT	2RNSAPT	2RNSSPT	52 x 39 x 82 1/4	2560	1/3+	580
	3R-PT	3R-SA-PT	3R-SS-PT	78 x 39 x 82 1/4	4010	1/2	815
HALF DOORS	1RNPTH	1RNSAPTH	1RNSSPTH	26 x 39 x 82 1/4	1940	1/4+	340
	2RNPTH	2RNSAPTH	2RNSSPTH	52 x 39 x 82 1/4	2560	1/3+	580
	3R-PT-HD	3R-SA-PT-HD	3R-SS-PT-HD	78 x 39 x 82 1/4	4010	1/2	815

Slim Line Reach-In Models

FULL DOORS	1RSEN	1RSENSA	1RSENSS	17 3/4 x 35 3/8 x 82 1/4	1940	1/4+	310
	2RSEN	2RSENSA	2RSENSS	36 1/4 x 35 3/8 x 82 1/4	2190	1/3+	430
HALF DOORS	1RSENHD	1RSENSAHD	1RSENSSHD	17 3/4 x 35 3/8 x 82 1/4	1940	1/4+	310
	2RSENHD	2RSENSAHD	2RSENSSHD	36 1/4 x 35 3/8 x 82 1/4	2190	1/3+	430
FULL DOORS SHALLOW DEPTH	1RSESN	1RSENSA	1RSESNSS	17 3/4 x 29 1/4 x 82 1/4	1940	1/4+	310
	2RSESN	2RSENSA	2RSESNSS	36 1/4 x 29 1/4 x 82 1/4	2190	1/3+	430
HALF DOORS SHALLOW DEPTH	1RSESNHD	1RSENSAHD	1RSESNSSH	17 3/4 x 29 1/4 x 82 1/4	1940	1/4+	310
	2RSESNHD	2RSENSAHD	2RSESNSSH	36 1/4 x 29 1/4 x 82 1/4	2190	1/3+	430

*BTU/HR Rating @ +25°F, 90°F ambient. 10 ft. cord and plug attached

**Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

Specifications - Extra Wide Refrigerators

Extra-Wide Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1REN	1RENSA	1RENSS	28 1/2 x 35 3/8 x 82 1/4	1940	1/4+	330
	1RXN	1RXNSA	1RXNSS	36 1/4 x 35 3/8 x 82 1/4	2190	1/3+	430
	2REN	2RENSA	2RENSS	57 x 35 3/8 x 82 1/4	2560	1/3+	560
	3REN	3RENSA	3RENSS	85 1/2 x 35 3/8 x 82 1/4	4010	1/2	785
HALF DOORS	1RENHD	1RENSAHD	1RENSSHD	28 1/2 x 35 3/8 x 82 1/4	1940	1/4+	330
	1RXNHD	1RXNSAHD	1RXNSSHD	36 1/4 x 35 3/8 x 82 1/4	2190	1/3+	430
	2RENHD	2RENSAHD	2RENSSHD	57 x 35 3/8 x 82 1/4	2560	1/3+	560
	3RENHD	3RENSAHD	3RENSSHD	85 1/2 x 35 3/8 x 82 1/4	4010	1/2	785
FULL DOORS SHALLOW DEPTH	1RESN	1RESNSA	1RESNSS	28 1/2 x 29 1/4 x 82 1/4	1940	1/4+	310
	1RXSN	1RXSNSA	1RXSNSS	36 1/4 x 29 1/4 x 82 1/4	2190	1/3+	410
	2RESN	2RESNSA	2RESNSS	57 x 29 1/4 x 82 1/4	2560	1/3+	520
	3RESN	3RESNSA	3RESNSS	85 1/2 x 29 1/4 x 82 1/4	4010	1/2	725
HALF DOORS SHALLOW DEPTH	1RESNHD	1RESNSAHD	1RESNSSHD	28 1/2 x 29 1/4 x 82 1/4	1940	1/4+	310
	1RXSNHD	1RXSNSAHD	1RXSNSSHD	36 1/4 x 29 1/4 x 82 1/4	2190	1/3+	410
	2RESNHD	2RESNSAHD	2RESNSSHD	57 x 29 1/4 x 82 1/4	2560	1/3+	520
	3RESNHD	3RESNSAHD	3RESNSSHD	85 1/2 x 29 1/4 x 82 1/4	4010	1/2	725

Extra-Wide Pass-Thru Models

FULL DOORS	1RENPT	1RENSAPT	1RENSSPT	28 1/2 x 38 3/4 x 82 1/4	1940	1/4+	360
	1RXNPT	1RXNSAPT	1RXNSSPT	36 1/4 x 38 3/4 x 82 1/4	2190	1/3+	435
	2RENPT	2RENSAPT	2RENSSPT	57 x 38 3/4 x 82 1/4	2560	1/3+	620
	3RE-PT	3RE-SA-PT	3RE-SS-PT	85 1/2 x 38 3/4 x 82 1/4	4010	1/2	875
HALF DOORS	1RNPTH	1RENSAPTH	1RENSSPTH	28 1/2 x 38 3/4 x 82 1/4	1940	1/4+	360
	1RXNPTH	1RXNSAPTH	1RXNSSPTH	36 1/4 x 38 3/4 x 82 1/4	2190	1/3+	435
	2RENPTH	2RENSAPTH	2RENSSPTH	57 x 38 3/4 x 82 1/4	2560	1/3+	620
	3RE-PT-HD	3RE-SA-PT-HD	3RE-SS-PT-HD	85 1/2 x 38 3/4 x 82 1/4	4010	1/2	875

*BTU/HR Rating @ +25°F, 90°F ambient. 10 ft. cord and plug attached

**Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

Specifications - Standard & Slim Line Freezers (0°F)

Standard Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1FN	1FNSA	1FNSS	26 x 35 3/8 x 82 1/4	1590	1/2	325
	2F	2F-SA	2F-SS	52 x 35 3/8 x 82 1/4	2470	1/2	555
	3F	3F-SA	3F-SS	78 x 35 3/8 x 82 1/4	3575	3/4 [§]	790
HALF DOORS	1FNHD	1FNSAHD	1FNSSHHD	26 x 35 3/8 x 82 1/4	1590	1/2	325
	2F-HD	2F-SA-HD	2F-SS-HD	52 x 35 3/8 x 82 1/4	2470	1/2	555
	3F-HD	3F-SA-HD	3F-SS-HD	78 x 35 3/8 x 82 1/4	3575	3/4 [§]	790
FULL DOORS SHALLOW DEPTH	1FSN	1FSNSA	1FSNSS	26 x 29 1/4 x 82 1/4	1590	1/2	325
	2FS	2FS-SA	2FS-SS	52 x 29 1/4 x 82 1/4	2470	1/2	555
	3FS	3FS-SA	3FS-SS	78 x 29 1/4 x 82 1/4	3575	3/4 [§]	790
HALF DOORS SHALLOW DEPTH	1FSNHD	1FSNSAHD	1FSNSSHD	26 x 29 1/4 x 82 1/4	1590	1/2	325
	2FS-HD	2FS-SA-HD	2FS-SS-HD	52 x 29 1/4 x 82 1/4	2470	1/2	555
	3FS-HD	3FS-SA-HD	3FS-SS-HD	78 x 29 1/4 x 82 1/4	3575	3/4 [§]	790

Standard Pass-Thru Models

FULL DOORS	1F-PT	1F-SA-PT	1F-SS-PT	26 x 39 x 82 1/4	1590	1/3	355
	2F-PT	2F-SA-PT	2F-SS-PT	52 x 39 x 82 1/4	2470	3/4 [§]	665
	3F-PT	3F-SA-PT	3F-SS-PT	78 x 39 x 85 3/4	4325	1 [§]	885
HALF DOORS	1F-PT-HD	1F-SA-PT-HD	1F-SS-PT-HD	26 x 39 x 82 1/4	1590	1/3	355
	2F-PT-HD	2F-SA-PT-HD	2F-SS-PT-HD	52 x 39 x 82 1/4	2470	3/4 [§]	665
	3F-PT-HD	3F-SA-PT-HD	3F-SS-PT-HD	78 x 39 x 85 3/4	4325	1 [§]	885

Slim Line Reach-In Models

FULL DOORS	1FSEN	1FSENSA	1FSENSS	17 3/4 x 35 3/8 x 82 1/4	1590	1/2	305
	2FSE	2FSE-SA	2FSE-SS	36 1/4 x 35 3/8 x 82 1/4	1840	1/2	445
HALF DOORS	1FSENHD	1FSENSAHD	1FSENSSHD	17 3/4 x 35 3/8 x 82 1/4	1590	1/2	305
	2FSE-HD	2FSE-SA-HD	2FSE-SS-HD	36 1/4 x 35 3/8 x 82 1/4	1840	1/2	445
FULL DOORS SHALLOW DEPTH	2FSES	2FSES-SA	2FSES-SS	36 1/4 x 29 1/2 x 82 1/4	1840	1/2	445

BTU/HR Rating @ -15°F, 90°F ambient
10 ft. cord and plug attached (115-60-1 volts)

[§]No cord and plug attached (115/208-230-60-1 volts)

**Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

Specifications - Extra Wide Freezers (0°F)

Extra-Wide Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1FEN	1FENSA	1FENSS	28 1/2 x 35 3/8 x 82 1/4	1590	1/2	345
	1FX	1FX-SA	1FX-SS	36 1/4 x 35 3/8 x 82 1/4	1840	1/2	485
	2FE	2FE-SA	2FE-SS	57 x 35 3/8 x 82 1/4	2470	1/2	595
	3FE	3FE-SA	3FE-SS	85 1/2 x 35 3/8 x 82 1/4	3575	3/4 [§]	830
HALF DOORS	1FENHD	1FENSAHD	1FENSSHD	28 1/2 x 35 3/8 x 82 1/4	1590	1/2	345
	1FX-HD	1FX-SA-HD	1FX-SS-HD	36 1/4 x 35 3/8 x 82 1/4	1840	1/2	485
	2FE-HD	2FE-SA-HD	2FE-SS-HD	57 x 35 3/8 x 82 1/4	2470	1/2	595
	3FE-HD	3FE-SA-HD	3FE-SS-HD	85 1/2 x 35 3/8 x 82 1/4	3575	3/4 [§]	830
FULL DOORS SHALLOW DEPTH	1FESN	1FESNSA	1FESNSS	28 1/2 x 29 1/4 x 82 1/4	1590	1/2	345
	1FXS	1FXS-SA	1FXS-SS	36 1/4 x 29 1/4 x 82 1/4	1840	1/2	485
	2FES	2FES-SA	2FES-SS	57 x 29 1/4 x 82 1/4	2470	1/2	595
	3FES	3FES-SA	3FES-SS	85 1/2 x 29 1/4 x 82 1/4	3575	3/4 [§]	830
HALF DOORS SHALLOW DEPTH	1FESNHD	1FESNSAHD	1FESNSSHD	28 1/2 x 29 1/4 x 82 1/4	1590	1/2	345
	1FXS-HD	1FXS-SA-HD	1FXS-SS-HD	36 1/4 x 29 1/4 x 82 1/4	1840	1/2	485
	2FES-HD	2FES-SA-HD	2FES-SS-HD	57 x 29 1/4 x 82 1/4	2470	1/2	595
	3FES-HD	3FES-SA-HD	3FES-SS-HD	85 1/2 x 29 1/4 x 82 1/4	3575	3/4 [§]	830

Extra-Wide Pass-Thru Models

FULL DOORS	1FE-PT	1FE-SA-PT	1FE-SS-PT	28 1/2 x 38 3/8 x 82 1/4	1590	1/3	375
	1FX-PT	1FX-SA-PT	1FX-SS-PT	36 1/4 x 38 3/8 x 82 1/4	1840	1/2	450
	2FE-PT	2FE-SA-PT	2FE-SS-PT	57 x 38 3/8 x 82 1/4	3575	3/4 [§]	695
	3FE-PT	3FE-SA-PT	3FE-SS-PT	85 1/2 x 38 3/8 x 85 3/4	4325	1 [§]	945
HALF DOORS	1FE-PT-HD	1FE-SA-PT-HD	1FE-SS-PT-HD	28 1/2 x 38 3/8 x 82 1/4	1590	1/3	375
	1FX-PT-HD	1FX-SA-PT-HD	1FX-SS-PT-HD	36 1/4 x 38 3/8 x 82 1/4	1840	1/2	450
	2FE-PT-HD	2FE-SA-PT-HD	2FE-SS-PT-HD	57 x 38 3/8 x 82 1/4	3575	3/4 [§]	695
	3FE-PT-HD	3FE-SA-PT-HD	3FE-SS-PT-HD	85 1/2 x 38 3/8 x 85 3/4	4325	1 [§]	945

BTU/HR Rating @ -15°F, 90°F ambient

10 ft. cord and plug attached (115-60-1 volts)

§No cord and plug attached (115/208-230-60-1 volts)

**Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

Specifications - Low Temperature Freezers (-15°F) & Dual Temperature

Low Temp Freezers Standard Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1F-LT	1F-LT-SA	1F-LT-SS	26 x 35 3/8 x 82 1/4	2050	3/4	450
	2F-LT	2F-LT-SA	2F-LT-SS	52 x 35 3/8 x 85 3/4	2600	1	565
	3F-LT	3F-LT-SA	3F-LT-SS	78 x 35 3/8 x 85 3/4	6300	2	810
HALF DOORS	1F-LT-HD	1F-LT-SA-HD	1F-LT-SS-HD	26 x 35 3/8 x 82 1/4	2050	3/4	450
	2F-LT-HD	2F-LT-SA-HD	2F-LT-SS-HD	52 x 35 3/8 x 85 3/4	2600	1	565
	3F-LT-HD	3F-LT-SA-HD	3F-LT-SS-HD	78 x 35 3/8 x 85 3/4	6300	2	810

Low Temp Freezers Extra-Wide Reach-In Models

FULL DOORS	1FE-LT	1FE-LT-SA	1FE-LT-SS	28 1/2 x 35 3/8 x 82 1/4	2050	3/4	450
	1FX-LT	1FX-LT-SA	1FX-LT-SS	36 1/4 x 35 3/8 x 85 3/4	2600	1	480
	2FE-LT	2FE-LT-SA	2FE-LT-SS	57 x 35 3/8 x 85 3/4	3600	1	565
	3FE-LT	3FE-LT-SA	3FE-LT-SS	85 1/2 x 35 3/8 x 85 3/4	6300	2	810
HALF DOORS	1FE-LT-HD	1FE-LT-SA-HD	1FE-LT-SS-HD	28 1/2 x 35 3/8 x 82 1/4	2050	3/4	450
	1FX-LT-HD	1FX-LT-SA-HD	1FX-LT-SS-HD	36 1/4 x 35 3/8 x 85 3/4	2600	1	480
	2FE-LT-HD	2FE-LT-SA-HD	2FE-LT-SS-HD	57 x 35 3/8 x 85 3/4	3600	1	565
	3FE-LT-HD	3FE-LT-SA-HD	3FE-LT-SS-HD	85 1/2 x 35 3/8 x 85 3/4	6300	2	810

BTU/HR Rating @ -30°F, 90°F ambient
No cord and plug attached (115/208-230-60-1 volts)

Dual Temperature Standard Reach-In Models

FULL DOORS	2RFN	2RFNSA	2RFNSS	52 x 35 3/8 x 82 1/4	1940, 1590	1/4, 1/3	580
	3RRFN	3RRFNSA	3RRFNSS	78 x 35 3/8 x 82 1/4	2560, 1590	1/3, 1/3	835
	3RFF	3RFF-SA	3RFF-SS	78 x 35 3/8 x 82 1/4	1940, 2470	1/4, 1/2	835
HALF DOORS	1RFNH	1RFNSAHD	1RFNSSHD	26 x 35 3/8 x 82 1/4	1625, 1800	1/5, 1/3	420
	2RFNH	2RFNSAHD	2RFNSSHD	52 x 35 3/8 x 82 1/4	1940, 1590	1/4, 1/3	580
	3RRFNH	3RRFNSAHD	3RRFNSSH	78 x 35 3/8 x 82 1/4	2560, 1590	1/3, 1/3	835
	3RFF-HD	3RFF-SA-HD	3RFF-SS-HD	78 x 35 3/8 x 82 1/4	1940, 2470	1/4, 1/2	835

Dual Temperature Extra-Wide Reach-In Models

FULL DOORS	2RFEN	2RFENSA	2RFENSS	57 x 35 3/8 x 82 1/4	1940, 1590	1/4, 1/3	620
	3RRFEN	3RRFENSA	3RRFENSS	85 1/2 x 35 3/8 x 82 1/4	2560, 1590	1/3, 1/3	885
	3RFFE	3RFFE-SA	3RFFE-SS	85 1/2 x 35 3/8 x 82 1/4	1940, 2470	1/4, 1/2	885
HALF DOORS	1RFENH	1RFENSAHD	1RFENSSH	28 1/2 x 35 3/8 x 82 1/4	1625, 1800	1/5, 1/3	435
	1RFXNH	1RFXNSAHD	1RFXNSSHD	36 1/4 x 35 3/8 x 82 1/4	1940, 1590	1/4, 1/3	555
	2RFENH	2RFENSAHD	2RFENSSH	57 x 35 3/8 x 82 1/4	1940, 1590	1/4, 1/3	620
	3RRFENH	3RRFENSAHD	3RRFENSSH	85 1/2 x 35 3/8 x 82 1/4	2560, 1590	1/3, 1/3	885
	3RFFE-HD	3RFFE-SA-HD	3RFFE-SS-HD	85 1/2 x 35 3/8 x 82 1/4	1940, 2470	1/4, 1/2	885

Note: Consult factory for Pass-Thru and Shallow Depth models.

BTU/HR Rating @ +25°F, 90°F ambient (refrigerators)
BTU/HR Rating @ -15°F, 90°F ambient (freezers)
(2) 10 ft. cords and plugs attached (115-60-1 volts)

**Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

Specifications - Standard & Extra Wide Display Refrigerators w/ Hinged Glass Doors

Standard Reach-In Models w/ Hinged Glass Doors

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1RNGD	1RNSAGD	1RNSSGD	26 x 35 3/8 x 82 1/4	1940	1/4+	315
	2RNGD	2RNSAGD	2RNSSGD	52 x 35 3/8 x 82 1/4	2560	1/3+	530
	3RNGD	3RNSAGD	3RNSSGD	78 x 35 3/8 x 82 1/4	4010	1/2	740
HALF DOORS	1RNGDHD	1RNSAGDHD	1RNSSGDHD	26 x 35 3/8 x 82 1/4	1940	1/4+	315
	2RNGDHD	2RNSAGDHD	2RNSSGDHD	52 x 35 3/8 x 82 1/4	2560	1/3+	530
	3RNGDHD	3RNSAGDHD	3RNSSGDHD	78 x 35 3/8 x 82 1/4	4010	1/2	740
FULL DOORS SHALLOW DEPTH	1RSNGD	1RSNSAGD	1RSNSSGD	26 x 29 1/4 x 82 1/4	1940	1/4+	315
	2RSNGD	2RSNSAGD	2RSNSSGD	52 x 29 1/4 x 82 1/4	2560	1/3+	530
HALF DOORS SHALLOW DEPTH	1RSNGDHD	1RSNSAGDHD	1RSNSSGDHD	26 x 29 1/4 x 82 1/4	1940	1/4+	315
	2RSNGDHD	2RSNSAGDHD	2RSNSSGDHD	52 x 29 1/4 x 82 1/4	2560	1/3+	530

Extra-Wide Reach-In Models w/ Hinged Glass Doors

FULL DOORS	1RENGD	1RENSAGD	1RENSSGD	28 1/2 x 35 3/8 x 82 1/4	1940	1/4+	335
	1RXNGD	1RXNSAGD	1RXNSSGD	36 1/4 x 35 3/8 x 82 1/4	2560	1/3+	440
	2RENGD	2RENSAGD	2RENSSGD	57 x 35 3/8 x 82 1/4	2560	1/3+	575
	3RENGD	3RENSAGD	3RENSSGD	85 1/2 x 35 3/8 x 82 1/4	3400	1/2	800
HALF DOORS	1RENGDHD	1RENSAGDHD	1RENSSGDHD	28 1/2 x 35 3/8 x 82 1/4	1940	1/4+	335
	1RXNGDHD	1RXNSAGDHD	1RXNSSGDHD	36 1/4 x 35 3/8 x 82 1/4	2560	1/3+	440
	2RENGDHD	2RENSAGDHD	2RENSSGDHD	57 x 35 3/8 x 82 1/4	2560	1/3+	575
	3RENGDHD	3RENSAGDHD	3RENSSGDHD	85 1/2 x 35 3/8 x 82 1/4	3400	1/2	800
FULL DOORS SHALLOW DEPTH	1RESNGD	1RESNSAGD	1RESNSSGD	28 1/2 x 29 1/4 x 82 1/4	1940	1/4+	335
	1RXSNGD	1RXNSAGD	1RXSNSSGD	36 1/4 x 29 1/4 x 82 1/4	2560	1/3+	440
	2RESNGD	2RESNSAGD	2RESNSSGD	57 x 29 1/4 x 82 1/4	2560	1/3+	575
HALF DOORS SHALLOW DEPTH	1RESNGDHD	1RESNSAGDHD	1RESNSSGDHD	28 1/2 x 29 1/4 x 82 1/4	1940	1/4+	335
	1RXSNGDHD	1RXNSAGDHD	1RXSNSSGDHD	36 1/4 x 29 1/4 x 82 1/4	2560	1/3+	440
	2RESNGDHD	2RESNSAGDHD	2RESNSSGDHD	57 x 29 1/4 x 82 1/4	2560	1/3+	575

Note: Consult factory for Pass-Thru and Shallow Depth models.

BTU/HR Rating @ +25°F, 90°F ambient

10 ft. cord and plug attached (115-60-1 volts)

§No cord and plug attached (115/208-230-60-1 volts)

**Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

Specifications - Standard & Extra Wide Display Refrigerators w/ Sliding Glass Doors

Standard & Extra Wide Low Temperature Display Freezer (-15°F)

Standard Reach-In Display Refrigerators w/ Sliding Glass Doors

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	2RNSGD	2RNSASGD	2RNSSSGD	52 x 34 x 82 1/4	2560	1/3+	530
HALF DOORS	2RNSGDHD	2RNSASGDHD	2RNSSSGDHD	52 x 34 x 82 1/4	2560	1/3+	530
FULL DOORS SHALLOW DEPTH	2RSNSGD	2RSNSASGD	2RSNSSSGD	52 x 27 7/8 x 82 1/4	2560	1/3+	530
HALF DOORS SHALLOW DEPTH	2RSNSGDHD	2RSNSASGDHD	2RSNSSSGDHD	52 x 27 7/8 x 82 1/4	2560	1/3+	530

Extra-Wide Reach-In Refrigerators w/ Sliding Glass Doors

FULL DOORS	2RENSGD	2RENSASGD	2RENSSSGD	57 x 34 x 82 1/4	2560	1/3+	575
HALF DOORS	2RENSGDHD	2RENSASGDHD	2RENSSSGDHD	57 x 34 x 82 1/4	2560	1/3+	575
FULL DOORS SHALLOW DEPTH	2RESNSGD	2RESNSASGD	2RESNSSSGD	57 x 27 7/8 x 82 1/4	2560	1/3+	575
HALF DOORS SHALLOW DEPTH	2RESNSGDHD	2RESNSASGDHD	2RESNSSSGDHD	57 x 27 7/8 x 82 1/4	2560	1/3+	575

BTU/HR Rating @ +25°F, 90°F ambient

10 ft. cord and plug attached (115-60-1 volts)

§No cord and plug attached (115/208-230-60-1 volts)

**Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

Standard Reach-In Low Temp Freezers w/ Hinged Glass Doors

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1F-LT-GD	1F-LT-SA-GD	1F-LT-SS-GD	26 x 35 3/8 x 85 3/4	2600	1	425
	2F-LT-GD	2F-LT-SA-GD	2F-LT-SS-GD	52 x 35 3/8 x 85 3/4	4200	2	595
	3F-LT-GD	3F-LT-SA-GD	3F-LT-SS-GD	78 x 35 3/8 x 85 3/4	7100	2	840
HALF DOORS	1F-LT-GD-HD	1F-LT-SA-GD-HD	1F-LT-SS-GD-HD	26 x 35 3/8 x 85 3/4	2600	1	425
	2F-LT-GD-HD	2F-LT-SA-GD-HD	2F-LT-SS-GD-HD	52 x 35 3/8 x 85 3/4	4200	2	595
	3F-LT-GD-HD	3F-LT-SA-GD-HD	3F-LT-SS-GD-HD	78 x 35 3/8 x 85 3/4	7100	2	840

Extra-Wide Reach-In Low Temp Freezers w/ Hinged Glass Doors

FULL DOORS	1FE-LT-GD	1FE-LT-SA-GD	1FE-LT-SS-GD	28 1/2 x 35 3/8 x 85 3/4	2600	1	440
	1FX-LT-GD	1FX-LT-SA-GD	1FX-LT-SS-GD	36 1/4 x 35 3/8 x 85 3/4	3175	1	480
	2FE-LT-GD	2FE-LT-SA-GD	2FE-LT-SS-GD	57 x 35 3/8 x 85 3/4	4200	2	635
	3FE-LT-GD	3FE-LT-SA-GD	3FE-LT-SS-GD	85 1/2 x 35 3/8 x 85 3/4	7100	2	885
HALF DOORS	1FE-LT-GD-HD	1FE-LT-SA-GD-HD	1FE-LT-SS-GD-HD	28 1/2 x 35 3/8 x 85 3/4	2600	1	440
	1FX-LT-GD-HD	1FX-LT-SA-GD-HD	1FX-LT-SS-GD-HD	36 1/4 x 35 3/8 x 85 3/4	3175	1	480
	2FE-LT-GD-HD	2FE-LT-SA-GD-HD	2FE-LT-SS-GD-HD	57 x 35 3/8 x 85 3/4	4200	2	635
	3FE-LT-GD-HD	3FE-LT-SA-GD-HD	3FE-LT-SS-GD-HD	85 1/2 x 35 3/8 x 85 3/4	7100	2	885

BTU/HR Rating @ -30°F, 90°F ambient

No cord and plug attached (115/208-230-60-1 volts)

**Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

Specifications - Standard & Extra Wide Display Freezer (0°F) w/ Hinged Glass Doors

Standard Reach-In Models w/ Hinged Glass Doors

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1FNGD	1FNSAGD	1FNSSGD	26 x 35 3/8 x 82 1/4	2470	1/2	330
	2F-GD	2F-SA-GD	2F-SS-GD	52 x 35 3/8 x 85 3/4	4325	1 [§]	565
	3F-GD	3F-SA-GD	3F-SS-GD	78 x 35 3/8 x 85 3/4	6050	1 1/2 [§]	805
HALF DOORS	1FNGDHD	1FNSAGDHD	1FNSSGDHD	26 x 35 3/8 x 82 1/4	2470	1/2	330
	2F-GD-HD	2F-SA-GD-HD	2F-SS-GD-HD	52 x 35 3/8 x 85 3/4	4325	1 [§]	565
	3F-GD-HD	3F-SA-GD-HD	3F-SS-GD-HD	78 x 35 3/8 x 85 3/4	6050	1 1/2 [§]	805
FULL DOORS SHALLOW DEPTH	1FSNGD	1FNSAGD	1FNSSSGD	26 x 29 1/4 x 82 1/4	2470	1/2	330
	2FS-GD	2FS-SA-GD	2FS-SS-GD	52 x 29 1/4 x 85 3/4	4325	1 [§]	565
HALF DOORS SHALLOW DEPTH	1FSNGDHD	1FNSAGDHD	1FNSSSGDHD	26 x 29 1/4 x 82 1/4	2470	1/2	330
	2FS-GD-HD	2FS-SA-GD-HD	2FS-SS-GD-HD	52 x 29 1/4 x 85 3/4	4325	1 [§]	565

Note: Consult factory for Pass-Thru models.

Extra-Wide Reach-In Models w/ Hinged Glass Doors

FULL DOORS	1FENGD	1FENSAGD	1FENSSGD	28 1/2 x 35 3/8 x 82 1/4	2470	1/2	345
	1FX-GD	1FX-SA-GD	1FX-SS-GD	36 1/4 x 35 3/8 x 82 1/4	2720	3/4 [§]	455
	2FE-GD	2FE-SA-GD	2FE-SS-GD	57 x 35 3/8 x 85 3/4	4325	1 [§]	610
	3FE-GD	3FE-SA-GD	3FE-SS-GD	85 1/2 x 35 3/8 x 85 3/4	6050	1 1/2 [§]	860
HALF DOORS	1FENGDHD	1FENSAGDHD	1FENSSGDHD	28 1/2 x 35 3/8 x 82 1/4	2470	1/2	345
	1FX-GD-HD	1FX-SA-GD-HD	1FX-SS-GD-HD	36 1/4 x 35 3/8 x 82 1/4	2720	3/4 [§]	455
	2FE-GD-HD	2FE-SA-GD-HD	2FE-SS-GD-HD	57 x 35 3/8 x 85 3/4	4325	1 [§]	610
	3FE-GD-HD	3FE-SA-GD-HD	3FE-SS-GD-HD	85 1/2 x 35 3/8 x 85 3/4	6050	1 1/2 [§]	860
FULL DOORS SHALLOW DEPTH	1FESNGD	1FESNSAGD	1FESNSSGD	28 1/2 x 29 1/2 x 82 1/4	2470	1/2	345
	1FXS-GD	1FXS-SA-GD	1FXS-SS-GD	36 1/4 x 29 1/4 x 82 1/4	2720	3/4 [§]	455
HALF DOORS SHALLOW DEPTH	1FESNGDHD	1FESNSAGDHD	1FESNSSGDHD	28 1/2 x 29 1/4 x 82 1/4	2470	1/2	345
	1FXS-GD-HD	1FXS-SA-GD-HD	1FXS-SS-GD-HD	36 1/4 x 29 1/4 x 82 1/4	2720	3/4 [§]	455

Note: Consult factory for Pass-Thru models.

BTU/HR Rating @ -15°F, 90°F ambient

10 ft. cord and plug attached (115-60-1 volts)

§No cord and plug attached (115/208-230-60-1 volts)

**Ship weight for Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

- Chrome or stainless steel shelves
- Add'l epoxy-coated steel shelves
- Wine racks
- Heavy-duty pilaster strips (not available on all models)
- Pan slide assemblies (not available on all models)
- Adjustable legs
- Rehinging of doors (consult factory)
- Correctional facility package
- Expansion valve system (standard on some models)
- Custom laminates
- Stainless steel case back
- Glass door on Pass-Thru models (consult factory)

Correctional Facility Package




Coverless hinges



Security screws



Locking hasp
(lock not included)



Stainless steel mesh
security cover

Engineering, Manufacturing & Quality Control

Continental Refrigerator engineers and builds our Reach-Ins and Pass-Thrus to meet the most stringent specifications demanded by consultants and service operators. All cabinets are constructed of top quality materials and components, attributing to their genuine ruggedness and durability. Our Reach-Ins and Pass-Thrus are designed with enhancements to endure everyday use in typical commercial kitchen environments.

Prior to factory shipping, all models are performance-run tested for a minimum of 12 hours, providing a highly sophisticated temperature analysis recording, exclusive to each individual cabinet. This recording is then supplied, along with the unit's operation manual, for the customer. A final leak test, vibration check, noise level and visual examination is made by our quality control team, to assure a superior product is shipped from our factory.



Plug refrigeration air flow

Air Flow

Air is drawn into the evaporator so condensation is not sprayed onto the food inside the cabinet. The conditioned air circulates radially from the evaporator compartment to provide more uniform air flow distribution.



Plug refrigeration system



Modular refrigeration system



Modular refrigeration air flow

“Plug” Refrigeration

Pass-Thru Refrigerators and Freezers utilize a “plug” refrigeration system where the assembly is outside the food storage zone. The “plug” system can be removed for servicing, cleaning or converting from a refrigerator to freezer in the field.

Modular Refrigeration

Reach-In Refrigerators and Freezers utilize a modular refrigeration system where the assembly is dropped into the food storage zone and uses an electric condensate evaporator which runs down the back of the unit. The modular system can be removed for servicing, cleaning or converting from a refrigerator to freezer in the field.

How to Buy

Local Sale Representatives

Territory

Dave Swain Associates	Westford, MA	(978) 392-8401	ME, RI, NH, MA, VT, CT
Master Marketing Carolina	High Shoals, NC	(704) 860-0092	NC, SC
Pro-Quip Foodservice	Little Rock, AR	(501) 221-7120	AR, LA, MS, W. TN (W. of Tenn. River)
The Veitch Group	Ft. Lauderdale, FL	(954) 316-6162	FL (except Panhandle)
Merkolat	Wellington, FL	(561) 594-7153	Latin America, Caribbean
Carman-Girard Associates	Atlanta, GA	(770) 457-6548	AL, FL (Panhandle), GA, E. TN (E. of Tenn River)
Ignite Foodservice Solutions	Denver, CO	(303) 433-0124	CO, S. ID, MT, UT WY
Roller & Associates	Seattle, WA	(206) 547-3555	WA, OR, AK, N. ID
Foodservice Equipment Agents	Anaheim, CA	(714) 693-3329	AZ (Bull Head City), S. CA, S. NV
Inform Marketing Group	Walnut Creek, CA	(510) 337-0420	N. CA, N. NV
McGirr, Inc.	Aiea, HI	(808) 486-0053	HI
Ignite Foodservice Solutions	Denver, CO	(303) 433-0124	AZ (except Bull Head City), NM, TX (El Paso)
Forbes Hever & Wallace, Inc.	Coppell, TX	(972) 219-8898	OK, TX (except El Paso)
Collis Group	Richmond Hill, ONT	(905) 660-4600	Ontario, Canada
Link 2 Hospitality Solutions	Rochester, NY	(585) 254-1780	Upstate NY
Pecinka Ferri Associates	Fairfield, NJ	(973) 812-4277	N. NJ, New York City
Schmid Dewland & Associates	Gibbsboro, NJ	(856) 783-3400	E. PA, DE, S. & Central NJ
Link 2 Hospitality Solutions	Pittsburg, PA	(412) 341-2020	W. PA, W. VA (except Panhandle)
High Sabatino Associates, Inc.	Jessup, MD	(301) 470-7051	DC, MD, VA, W. VA (Panhandle)
Stiefel Associates, Inc.	Lansing, MI	(517) 393-3019	MI (except Upper Peninsula)
Dick Stanley & Associates	Pickerington, OH	(800) 833-0797	OH, KY
Acosta/Cornerstone	Fishers, IN	(800) 832-6442	IN
Jay Mark Group, LTD	Elk Grove Village, IL	(847) 545-1918	N. IL
North Star Agency	Edina, MN	(763) 545-1400	MN, ND, SD
Mirkovich & Associates	Waukesha, WI	(630) 792-0080	WI, MI (Upper Peninsula)
Select Marketing	St. Louis, MO	(314) 961-3332	MO, KS, IA, NE, S. IL



A Division of National Refrigeration & Air Conditioning Products

Continental Refrigerator | Local: (215) 244-1400
539 Dunksferry Road | Toll Free: (800) 523-7138
Bensalem, PA 19020 | Fax: (215) 244-9579

www.continentalrefrigerator.com

Continental[®]

Refrigerator

INNOVATIVE DESIGNS FOR YOUR FOODSERVICE NEEDS

