



**DISPENSED WATER
EQUIPMENT**





BUNN refresh® Tower
Pull & Hold

BUNN refresh®

Dispensed cold filtered water from tap, and long lasting sparkling water from the other

Sleek visual design language worthy of front-of-house settings

Purity achieved with water filtration certified to reduce cysts, lead, particulates, chloramines, chlorine taste and odor and 99.99% of water-borne bacteria

Recirculation loop ensures cold water is constantly circulating for consistently low casual drink temperature of 40°F water

In-line patent-pending water mistifier provides delicate balance of purified, cold water and "light" carbonation for longer lasting sparkling water and optimal absorption of flavors

Fast flow faucet accommodates large cups or carafes up to 12" Tall

At a rate of two 12oz drinks per minute, can dispense 120 drinks before exceeding 41°F



BUNN refresh® Tower
Portion Control

DESCRIPTION							ELECTRICAL	
Product #	Model	Finish	Temperature Setting		Dimensions Height x Width x Depth (Inches)			Volts
			°F	°C				
45900.0100	BUNN refresh Tower Pull & Hold	Chrome Plated	40	4.4	24.70	7.80	14.60	120
45900.0101	BUNN refresh Push Button	Chrome Plated	40	4.4	20.10	7.80	14.60	120

Plumbing: 30-100 PSI. Machine supplied with 3/8" male flare fitting

BUNN refresh®

Sparkling and still cold water dispenser with patent-pending mistifier delivers purified premium water elevating the customer beverage experience

Purity achieved with water filtration certified to reduce cysts, lead, particulates, chloramines, chlorine taste and odor and 99.99% of water-borne bacteria

Recirculation loop ensures cold water is constantly circulating for consistently low casual drink temperature of 40°F water

In-line patent-pending water mistifier provides delicate balance of purified, cold water and "light" carbonation for longer lasting sparkling water and optimal absorption of flavors

The perfect instrument to incorporate infusions and natural ingredients for crafted beverages

New visual design language worthy of front-of-house settings

At a rate of one 12oz drink per minute, can dispense 60 drinks before exceeding 41°F



BUNN® refresh®
Push Button



BUNN refresh®
Portion Control



BUNN refresh®
Push Button



BUNN refresh®
Portion Control

DESCRIPTION								ELECTRICAL
Product #	Model	Finish	Temperature Setting		Dimensions Height x Width x Depth (Inches)			Volts
			°F	°C				
45800.0000	BUNN refresh Countertop Push Button	Black/Stainless	40	4.4	27	10	26.5	120
45800.0001	BUNN refresh Countertop Portion Control	Black/Stainless	40	4.4	27	10	26.5	120
45800.0002	BUNN refresh Countertop Push Button	White/Stainless	40	4.4	27	10	26.5	120
45800.0003	BUNN refresh Countertop Portion Control	White/Stainless	40	4.4	27	10	26.5	120

Plumbing: 30-100 PSI. Machine supplied with 3/8" male flare fitting



H3X Element

Precise Temperature - Medium Volume

3gal (11.4L) tank

Digital thermostat provides consistent and accurate temperatures, programmable from 60°-212°F (15.6°-100°C)

Contemporary, low profile design for front-of-house and self-service

Thinsulate® tank insulation provides increased energy efficiency

LED display provides simple temperature adjustment

Drip tray included



DESCRIPTION								CAPACITY		ELECTRICAL
Product #	Model	Finish	Temperature Setting		Dimensions Height x Width x Depth (Inches)			WATER INPUT 60°F / 15.5°C		
			°F	°C				gal/hr	L/hr	Volts
45300.0006	H3X	Stainless	212	100	22.30	7.60	13.30	4.7	17.8	120
45300.0007	H3X	Stainless	212	100	22.30	7.60	13.30	8.4	31.8	208
45300.0008	H3X	Stainless	212	100	22.30	7.60	13.30	3.5	13.2	120

Precise Temperature - Medium Volume

5gal (18.9L) tank

Digital thermostat provides consistent and accurate temperatures, programmable from 60°-212°F (15.6°-100°C)

Thinsulate® tank insulation provides increased energy efficiency

LED display provides simple temperature adjustment



H5X Element
(Stainless)



H5X Element
(Black)

DESCRIPTION								CAPACITY		ELECTRICAL
								WATER INPUT 60°F / 15.5°C		
Product #	Model	Finish	Temperature Setting		Dimensions Height x Width x Depth (Inches)			gal/hr	L/hr	Volts
			°F	°C						
43600.0002	H5X	Stainless	212	100	28.50	7.40	17.60	10.5	39.7	208
43600.0003	H5X	Stainless	212	100	28.50	7.40	17.60	10.5	39.7	240
43600.0026	H5X	Stainless	212	100	28.50	7.40	17.60	4.7	17.8	120
43600.0010	H5X	Black	212	100	28.50	7.40	17.60	10.5	39.7	208



OHW

Constant Temperature - Pourover & Low Volume

High quality, easy-to-clean stainless steel exterior and tank for a long life

Includes drip tray

OHW

Compact styling to accommodate a variety of spaces

Pourover model. No plumbing needed

HW2

Hooked to water line so fresh, hot water is always available

2gal (7.57L) of hot water in a space-saving machine



HW2

DESCRIPTION					TANK SIZE		CAPACITY		ELECTRICAL		
Product #	Model	Dimensions Height x Width x Depth (Inches)			Temperature Setting		gal	L	gal/hr	L/hr	Volts
		Height	Width	Depth	°F	°C					
02550.0003	OHW	16.90	6.50	10.80	200	93.3	.625	2.4	Pourover		120
02500.0001	HW2	24.00	7.10	14.30	200	93.3	2	7.6	4.1	15.5	120

Constant Temperature - Large Volume

High quality, easy-to-clean stainless steel exterior and tank for a long life

H5E-DV PC

Constant temperature control between (65°F-200°F) (18.3°C-96.1°C) ensures consistent water temperature

Dual voltage model; can operate at 120V/15 amp or 120/208-240V/17 amp

Three programmable volume settings and one push and hold continuous dispense button

H5X-DV-PC

Dispenses at temperatures up to boiling (212°F) (100°C) for food prep and cleaning

Dual voltage model; can operate at 120V/15 amp or 120/208-240V/17 amp

Three programmable volume settings and one push and hold continuous dispense button

H10X

Dry-plug prevention for easy installation

Precise temperature (212°F / 100°C) ensures consistent, high quality results



H10X



H5E-DV PC

DESCRIPTION									CAPACITY		ELECTRICAL
									WATER INPUT 60°F / 15.5°C		
Product #	Model	Dimensions Height x Width x Depth (Inches)			Temperature Setting		Tank Size		gal/hr	L/hr	Volts
39100.0000	H5E-DV PC	28.40	7.00	15.50	200	93.3	5	18.9	5.1	19.3	120
									8.6	32.6	120/208
									11.4	43.2	120/240
39100.0001	H5E-DV PC	28.40	7.00	15.50	90	32.2	5	18.9	24	90	120
									40	151	120/208
									53	200.6	120/240
39100.0005	H5X-DV PC	28.40	7.00	15.50	212	100	5	18.9	4.7	17.8	120
									7.9	29.9	120/208
									10.5	39.7	120/240
26300.0001	H10X-80-208	34.40	10.20	24.50	212	100	10	37.9	10.5	39.7	208
26300.0000	H10X-80-240	34.40	10.20	24.50	212	100	10	37.9	10.5	39.7	240



Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Premium Filtered Water

Expand your beverage menu with profitable, custom-crafted still and carbonated filtered water infusions.

Hot Water on Demand

Hot water is a staple in every type of foodservice operation. From quality beverages to efficient food preparation to reduced labor costs, the value of readily available hot water is invaluable. BUNN offers a full line of plumbed and pourover Hot Water Dispensers to meet your on-demand hot water requirements.

USA • CANADA • MEXICO • UNITED KINGDOM • GERMANY • BRAZIL • CHINA • UAE



corporate headquarters

5020 Ash Grove Drive • Springfield, Illinois 62711 • USA
(+1) (217) 529-6601 • (800) 637-8606