

# NORLAKE<sup>®</sup>

*Quality Refrigeration  
Since 1947*



## **NOVA<sup>™</sup>** **Products**

*Reach-in, Roll-in &  
Pass-Thru Cabinets*

*Heated Cabinets*



*Blast Chillers*

*Blast Chillers/  
Freezers*



*Open Air  
Merchandisers*



*Refrigerated Prep  
Tables*



*Milk Coolers*

*Milk Cooler Storage*



*Specialty Freezers*



# NOVA™ Reach-ins

**NOVA™ Reach-in Refrigerators and Freezers are perfect for high-volume applications as the airflow design protects and maintains high temperature tolerances. They also boast the largest interior storage space in the industry.**

- Refrigerators and freezers
- Glass doors available (refrigerator models only)
- Available in 1, 2 or 3 full or half door models
- Top mount refrigeration system
- Microprocessor with digital display
- Stainless steel interior and exterior
- Standard models ship the same day!
- UL, C-UL, UL Sanitation



	Height	Width	Depth	CuFt	HP	Voltage
<b>Refrigerators</b>						
<b>NR241</b>	81-1/2"	27-1/2"	35-1/8"	24.1	1/4	115/60/1
<b>NR522</b>	81-1/2"	55"	35-1/8"	51.9	1/3	115/60/1
<b>NR803</b>	81-1/2"	82-1/2"	35-1/8"	79.9	1/2	115/60/1
<b>Freezers</b>						
<b>NF241</b>	81-1/2"	27-1/2"	35-1/8"	24.1	1/2	115/60/1
<b>NF522</b>	81-1/2"	55"	35-1/8"	51.9	3/4	115/60/1
<b>NF803</b>	81-1/2"	82-1/2"	35-1/8"	79.9	3/4	115/60/1

**Standard Three Year Parts and Labor, Five Year Compressor Warranties**

# NOVA™ Reach-ins

**NOVA™ Pass-Thru, Roll-Thru and Roll-In Refrigerators meet multiple demands for performance and provide many flexible configurations to meet your needs.**

- Stainless steel interior
- Stainless and galvanized steel exterior
- Pass-Thrus available in 1, 2 or 3 solid, glass or half doors
- Roll-Ins and Roll-Thrus available in 1 or 2 doors
- Heavy-duty pivot hinges
- Horizontal work flow pull handles
- Microprocessor with digital display
- UL, C-UL and UL Sanitation; NSF and UL Safety on Roll-In models



	Height	Width	Depth	CuFt	HP	Voltage
<b>Pass-Thrus</b>						
<b>PR242</b>	81-1/2"	27-1/2"	38-1/4"	25.6	1/3	115/60/1
<b>PR524</b>	81-1/2"	55"	38-1/4"	55.7	1/2	115/60/1
<b>PR806</b>	81-1/2"	82-1/2"	38-1/4"	85.8	3/4	115/60/1
<b>Roll-ins</b>						
<b>WR331</b>	84-3/4"	31-3/4"	36-3/8"	34.2	1/3	115/60/1
<b>WR722</b>	84-3/4"	63-1/2"	36-3/8"	72.5	1/2	115/60/1
<b>Roll-Thrus</b>						
<b>PWR332</b>	84-3/4"	31-3/4"	39-3/4"	33.0	1/3	115/60/1
<b>PWR724</b>	84-3/4"	63-1/2"	39-3/4"	72.0	3/4	115/60/1

**Standard Three Year Parts and Labor, Five Year Compressor Warranties**

# NOVA™ Reach-ins

**NOVA™ Heated Reach-ins, Pass-Thrus and Roll-Thrus provide exacting temperature maintenance to protect your products.**

- Stainless steel interior
- Stainless and galvanized steel exterior
- Horizontal work flow handles
- Maintains up to +200°F
- Ducted air distribution
- Digital LED thermometer
- UL, C-UL and UL Sanitation



	Height	Width	Depth	CuFt	Watts	Voltage
<b>Reach-ins</b>						
<b>NW211</b>	81-1/2"	27-1/2"	35-1/8"	22.5	1500	115/60/1
<b>NW482</b>	81-1/2"	55"	35-1/8"	48.8	3000	208-230/60/1
<b>Pass-Thrus</b>						
<b>PW252</b>	81-1/2"	27-1/2"	38-1/4"	25.6	1500	115/60/1
<b>PW554</b>	82-3/4"	55"	38-1/4"	55.7	3000	115/208-230/60/1
<b>Roll-Thrus</b>						
<b>PW332</b>	84-3/4"	31-3/4"	39-3/4"	36.4	1500	115/60/1
<b>PW724</b>	84-3/4"	63-1/2"	38-3/4"	78.1	3000	208-230/60/1

**Standard Three Year Parts and Labor, Five Year Compressor Warranties**



# NOVA™ Blast Chillers / Freezers

**NOVA™ Blast Chillers and Chillers/Freezers were designed for operational ease in the precision chilling / freezing process.**

- Stainless steel exterior and interior
- Stainless steel half racks
- Adjustable legs with plastic heat resistant pads
- Electronically controlled defrost
- Chilling process will take product from +194°F to +37°F in 90 minutes
- Freezing process will take product from +194°F to 0°F in 240 minutes
- ETL Safety and Sanitation



	Height	Width	Depth	# Shelves	HP	Voltage
<b>Chillers</b>						
<b>NBC40-4A</b>	38-1/4"	29-3/8"	28-15/16"	3	1/2	220/60/1
<b>NBC80-8A</b>	74-5/8"	31-1/2"	33-1/8"	3	2-1/2	220/60/3
<b>NBC113-16A</b>	78"	40-15/16"	40"	6	2-1/2	220/60/3
<b>Chillers/Freezers</b>						
<b>NBCF35/22-5A</b>	33-9/16"	36-9/16"	30-13/16"	5*	1	220/60/1
<b>NBCF48/28-4A</b>	38-1/4"	29-3/8"	28-15/16"	3	1	220/60/1
<b>NBCF99/59-8A</b>	74-5/8"	31-1/2"	33-1/8"	3	3	220/60/3
<b>NBCF115/55-16A</b>	78"	40-15/16"	40"	6	3	220/60/3
<b>NBCF220/110-16A</b>	78"	40-15/16"	40"	10	5-1/2	220/60/3

\* NLCF35/22-5A is standard with pan guides instead of shelves

**Standard One Year Parts and Labor, Five Year Compressor Warranties**

# NOVA™ Open Air Merchandisers

**NOVA™ Horizontal Open Air Merchandisers hold up to 120 lbs. of product per shelf and are the quietest running in the industry.**

- 24 gauge black painted textured galvanized steel interior and exterior front and top
- Adjustable shelf
- Automatic defrost
- LED lighting in canopy
- Electronically controlled monitoring system
- UL, C-UL Safety and UL Sanitation



	<i>Height</i>	<i>Width</i>	<i>Depth</i>	<i>CuFt</i>	<i>HP</i>	<i>Voltage</i>
<b>Merchandisers</b>						
<b>NLHOAM36</b>	46"	35-1/2"	34"	4.6	1/2	115/60/1
<b>NLHOAM48</b>	46"	47-1/2"	34"	6.3	1/2	115/60/1
<b>NLHOAM60</b>	46"	59-1/2"	34"	7.9	3/4	115/60/1
<b>NLHOAM72</b>	46"	71-1/2"	34"	9.6	3/4	115/60/1

**Standard Three Year Parts and Labor, Five Year Compressor Warranties**

# NOVA™ Open Air Merchandisers

**NOVA™ Vertical Open Air Merchandisers feature a demand evaporator system which adjusts in even the most humid temperatures.**

- 24 gauge black painted textured galvanized steel interior and exterior front and top
- Adjustable shelves
- Automatic defrost
- LED lighting in canopy
- Electronically controlled monitoring system
- Retractable vinyl night curtain (shown right with optional stainless finish)
- UL, C-UL Safety and UL Sanitation



	Height	Width	Depth	CuFt	HP	Voltage
<b>60" Height</b>						
NLVOAM36-60	60"	35-1/2"	34"	13.4	1/2	115/60/1
NLVOAM48-60	60"	47-1/2"	34"	18.2	3/4	115/60/1
NLVOAM60-60	60"	59-1/2"	34"	23.1	1	115/60/1
NLVOAM72-60	60"	71-1/2"	34"	28.0	1	115/60/1
<b>72" Height</b>						
NLVOAM36-72	72"	35-1/2"	34"	17.8	3/4	115/60/1
NLVOAM48-72	72"	47-1/2"	34"	24.2	1	115/60/1
NLVOAM60-72	72"	59-1/2"	34"	30.7	1	208-230/60/1
NLVOAM72-72	72"	71-1/2"	34"	37.1	1	208-230/60/1
<b>79" Height</b>						
NLVOAM36-79	79"	35-1/2"	34"	20.8	3/4	115/60/1
NLVOAM48-79	79"	47-1/2"	34"	28.3	1	115/60/1
NLVOAM60-79	79"	59-1/2"	34"	35.9	1	208-230/60/1
NLVOAM72-79	79"	71-1/2"	34"	43.4	1	208-230/60/1

**Standard Three Year Parts and Labor, Five Year Compressor Warranties**

# NOVA™ Refrigerated Prep Tables

**NOVA™ Refrigerated Prep Tables can maintain temperatures in even the hottest environment. Its rail and base have different temperature adjustments to best fit your product.**

- Stainless and galvanized steel exterior
- Smooth aluminum interior
- Operating temperatures: +33°F to +41°F in pan well area, +34°F to +38°F in storage area
- Available in 1, 2, 3 and 4 door models
- UL, C-UL and UL Sanitation listed to NSF Standard 7



	Height	Width	Depth	CuFt	HP	Voltage
<b>Prep Tables</b>						
<b>RR152</b>	43-1/2"	47-3/4"	35"	15.0	1/4	115/60/1
<b>RR192</b>	43-1/2"	59-3/4"	35"	19.0	1/4	115/60/1
<b>RR243</b>	43-1/2"	71-3/4"	35"	24.0	1/3	115/60/1
<b>RR283</b>	43-1/2"	83-3/4"	35"	28.0	1/3	115/60/1
<b>RR324</b>	43-1/2"	95-3/4"	35"	32.0	1/3	115/60/1

**Standard Three Year Parts and Labor, Five Year Compressor Warranties**



# NOVA™ Milk Coolers

**NOVA™ Cold Wall Milk Coolers are designed for the most demanding abuse with a reinforced floor and 5-year frame warranty.**

- Storage for 8, 12, or 16 cases of milk cartons
- Drop lid(s) that provide easy access to self-serve milk
- Exterior self-service door(s) are stainless steel
- Easy roll locking swivel casters
- Heavy-duty floor racks
- Key locking feature
- UL, C-UL, UL Sanitation



	Height	Width	Depth	Cases	HP	Voltage
<b>Open Front</b>						
<b>AR082</b>	43-5/8"	34-5/8"	32-3/4"	8	1/5	115/60/1
<b>AR122</b>	43-5/8"	48-5/8"	32-3/4"	12	1/5	115/60/1
<b>AR162</b>	43-5/8"	62-5/8"	32-3/4"	16	1/5	115/60/1
<b>Dual Access</b>						
<b>AR084</b>	43-5/8"	34-5/8"	33-1/2"	8	1/5	115/60/1
<b>AR124</b>	43-5/8"	48-5/8"	33-1/2"	12	1/5	115/60/1
<b>AR164</b>	43-5/8"	62-5/8"	33-1/2"	16	1/5	115/60/1
<b>Cooler Storage</b>						
<b>GR422</b>	64-7/8"	63-3/8"	34"	28	1/4	115/60/1

**Standard Three Year Parts and Labor, Five Year Compressor Warranties**

# NOVA™ Specialty Freezers

**NOVA™ Topping Cabinets with a Refrigerated Rail are designed to safely hold all the necessary toppings for sundaes in the NSF Standard 7 rail.**

- Stainless steel exterior
- Smooth aluminum cabinet and rail interior liners
- Syrup rail meets NSF Standard 7 requirements and has dedicated temperature controls for the base unit and syrup rail
- UL, C-UL and UL Sanitation



**NOVA™ Topping-Dipping and Storage-Dipping Cabinets really are the work-horse of the industry.**

- Stainless steel top
- 24 gauge white painted galvanized steel exterior
- Anti-condensate heaters under stainless top cap (Dipping models)
- Leveling legs
- Jars, ladles and pumps are optional (Topping-Dipping models)
- UL, C-UL and NSF

	Height	Width	Depth	CuFt	HP	Voltage
<b>Refrigerated Rail</b>						
ZF071	47-1/8"	27-1/2"	33-1/8"	7.0	3/8	115/60/1
ZR152	47-1/8"	54"	33-1/8"	15.0	1/4	115/60/1
ZF152	47-1/8"	54"	33-1/8"	15.0	1/2	115/60/1
<b>Topping Dipping</b>						
ZF124	38-1/4"	43"	30-1/8"	12.5	1/4	115/60/1
ZF174	38-1/4"	54"	30-1/8"	16.8	1/3	115/60/1
<b>Dipping</b>						
FF044	34-1/8"	31-7/8"	21-1/8"	5.2	1/4	115/60/1
FF074	34-1/8"	30-5/8"	30-1/8"	7.6	1/4	115/60/1
FF104	34-1/8"	54"	21-1/8"	11.0	1/4	115/60/1
FF114	34-1/8"	43"	30-1/8"	12.5	1/4	115/60/1
FF154	34-1/8"	54"	30-1/8"	17.3	1/3	115/60/1
FF204	34-1/8"	66-5/8"	30-1/8"	22.0	1/3	115/60/1
FF264	34-1/8"	84-5/8"	30-1/8"	29.1	1/3	115/60/1

**Standard Two Year Parts and Labor, Five Year Compressor Warranties**

# NOVA™ Specialty Freezers

**NOVA™ Dipping Display Freezers are available in three different configurations to best fit any need.**

- 24 gauge white painted galvanized steel interior and exterior
- Stainless steel top and attached super structure with tempered plate glass viewing window
- Stainless steel serving deck
- Standard profile, low profile glass and curved glass models available
- UL, C-UL and NSF



	Height	Width	Depth	Cans*	HP	Voltage
<b>Angled Glass</b>						
<b>HF040</b>	50"	26-1/2"	27-3/4"	4	1/3	115/60/1
<b>HF100</b>	50"	47-3/4"	27-3/4"	8	1/2	115/60/1
<b>HF160</b>	50"	69-1/4"	27-3/4"	12	1/2	115/60/1
<b>HF230</b>	50"	90-3/4"	27-3/4"	16	3/4	115/60/1
<b>Curved Glass</b>						
<b>HF040</b>	52"	26-1/2"	27-3/4"	4	1/3	115/60/1
<b>HF100</b>	52"	47-3/4"	27-3/4"	8	1/2	115/60/1
<b>HF160</b>	52"	69-1/4"	27-3/4"	12	1/2	115/60/1
<b>HF230</b>	52"	90-3/4"	27-3/4"	16	3/4	115/60/1

\* 9-1/2" diameter 3 gallon cans

**Standard Two Year Parts and Labor, Five Year Compressor Warranties**

# NOVA™ Specialty Freezers

**NOVA™ Angled Display Merchandisers are perfect for grab-and-go applications.**

- 24 gauge white polyester enamel painted steel interior and exterior
- Stainless steel top serving deck
- Adjustable, white epoxy-coated wire shelves
- Self-closing field reversible rear door
- UL, C-UL and UL Sanitation

*Standard Two Year Parts and Labor, Five Year Compressor Warranties*



**NOVA™ Ice Crushers provide crushed ice without requiring a specialty ice maker. Its unrelenting capacity is preferable for high-volume applications.**

- Crushes ice to sizes from cube to flake
- Stainless steel exterior
- UL, C-UL and UL Sanitation

	Height	Width	Depth	CuFt	HP	Voltage
<b>Merchandisers</b>						
<b>MF122</b>	50-3/16"	40"	31"	11.8	3/4	115/60/1
<b>MF182</b>	50"	60"	31"	18.1	3/4	115/60/1
<b>Ice Crusher</b>						
<b>N14CR</b>	44"	15-1/2"	20"	-	1/4	115/60/1

*Standard One Year Parts and Labor, Five Year Compressor Warranties*



**NORLAKE**

727 Second Street • Hudson, Wisconsin 54016  
800-955-5253 • 715-386-4291 FAX • www.norlake.com

**Standex**  
Food Service Equipment Group

04/17 132826