# NORLAKE

#### Quality Refrigeration Since 1947



## NOVA™ Products

Reach-in, Roll-in & Pass-Thru Cabinets Heated Cabinets



Blast Chillers Blast Chillers/

**Freezers** 



Open Air Merchandisers



Refrigerated Prep Tables



Milk Coolers Milk Cooler Storage



**Ice Cream Cabinets** 



#### NOVA<sup>™</sup> Reach-ins

NOVA<sup>™</sup> Reach-in Refrigerators and Freezers are perfect for high-volume applications as the airflow design protects and maintains high temperature tolerances. They also boast the largest interior storage space in the industry.

- · Refrigerators and freezers
- Glass doors available (refrigerator models only)
- Available in 1, 2 or 3 full or half door models
- Top mount refrigeration system
- · Microprocessor with digital display
- · Stainless steel interior and exterior
- Standard models ship the same day!
- UL, C-UL, UL Sanitation and ENERGY STAR<sup>®</sup> (ENERGY STAR<sup>®</sup> on solid door models only)





	Height	Width	Depth	CuFt	HP	Voltage
Refrigerators						
NR241	81-1/2"	27-1/2"	35-1/8"	24.1	1/4	115/60/1
NR522	81-1/2"	55"	35-1/8"	51.9	1/3	115/60/1
NR803	81-1/2"	82-1/2"	35-1/8"	79.9	1/2	115/60/1
Freezers						
NF241	81-1/2"	27-1/2"	35-1/8"	24.1	1/2	115/60/1
NF522	81-1/2"	55"	35-1/8"	51.9	3/4	115/60/1
NF803	81-1/2"	82-1/2"	35-1/8"	79.9	3/4	115/60/1

#### NOVA<sup>™</sup> Reach-ins

## NOVA<sup>™</sup> Pass-Thru, Roll-Thru and Roll-In Refrigerators meet multiple demands for performance and provide many flexible configurations to meet your needs.

- Stainless steel interior
- · Stainless and galvanized steel exterior
- Pass-Thrus available in 1, 2 or 3 solid, glass or half doors
- Roll-Ins and Roll-Thrus available in 1 or 2 doors
- Heavy-duty pivot hinges
- Horizontal work flow pull handles
- Microprocessor with digital display
- UL, C-UL and UL Sanitation; NSF and UL Safety on Roll-In models



	Height	Width	Depth	CuFt	HP	Voltage
Pass-Thrus						
PR242	81-1/2"	27-1/2"	38-1/4"	25.6	1/3	115/60/1
PR524	81-1/2"	55"	38-1/4"	55.7	1/2	115/60/1
PR806	81-1/2"	82-1/2"	38-1/4"	85.8	3/4	115/60/1
Roll-ins						
WR331	84-3/4"	31-3/4"	36-3/8"	34.2	1/3	115/60/1
WR722	84-3/4"	63-1/2"	36-3/8"	72.5	1/2	115/60/1
Roll-Thrus						
PWR332	84-3/4"	31-3/4"	39-3/4"	33.0	1/3	115/60/1
PWR724	84-3/4"	63-1/2"	39-3/4"	72.0	3/4	115/60/1

#### NOVA<sup>™</sup> Reach-ins

#### NOVA<sup>™</sup> Heated Reach-ins, Pass-Thrus and Roll-Thrus provide exacting temperature maintenance to protect your products.

- Stainless steel interior
- Stainless and galvanized steel exterior
- Horizontal work flow handles
- Maintains up to +200°F
- Ducted air distribution
- Digital LED thermometer
- UL, C-UL and UL Sanitation



	Height	Width	Depth	CuFt	Watts	Voltage
Reach-ins						
NW211	81-1/2"	27-1/2"	35-1/8"	22.5	1500	115/60/1
NW482	81-1/2"	55"	35-1/8"	48.8	3000	208-230/60/1
Pass-Thrus						
PW252	81-1/2"	27-1/2"	38-1/4"	25.6	1500	115/60/1
PW554	82-3/4"	55"	38-1/4"	55.7	3000	115/208-230/60/1
Roll-Thrus						
PW332	84-3/4"	31-3/4"	39-3/4"	36.4	1500	115/60/1
PW724	84-3/4"	63-1/2"	38-3/4"	78.1	3000	208-230/60/1

## **NOVA<sup>™</sup> Blast Chillers / Freezers**

#### NOVA<sup>™</sup> Blast Chillers and Chillers/Freezers were designed for operational ease in the precision chilling / freezing process.

- Stainless steel exterior and interior
- Stainless steel half racks
- · Adjustable legs with plastic heat resistant pads
- Electronically controlled defrost
- Chilling process will take product from +194°F to +37°F in 90 minutes
- Freezing process will take product from +194°F to 0°F in 240 minutes
- ETL Safety and Sanitation



	Height	Width	Depth	# Shelves	HP	Voltage
Chillers						
NBC40-4A	38-1/4"	29-3/8"	28-15/16"	3	1/2	220/60/1
NBC80-8A	74-5/8"	31-1/2"	33-1/8"	3	2-1/2	220/60/3
NBC113-16A	78"	40-15/16"	40"	6	2-1/2	220/60/3
Chillers/Freezers						
NBCF35/22-5A	33-9/16"	36-9/16"	30-13/16"	5*	1	220/60/1
NBCF48/28-4A	38-1/4"	29-3/8"	28-15/16"	3	1	220/60/1
NBCF99/59-8A	74-5/8"	31-1/2"	33-1/8"	3	3	220/60/3
NBCF115/55-16A	78"	40-15/16"	40"	6	3	220/60/3
NBCF220/110-16A	78"	40-15/16"	40"	10	5-1/2	220/60/3
* NLCF35/22-5A is standa	rd with pan guid	es instead of she	elves			

## **NOVA<sup>™</sup> Open Air Merchandisers**

#### NOVA<sup>™</sup> Horizontal Open Air Merchandisers hold up to 120 lbs. of product per shelf and are the quietest running in the industry.

- 24 gauge black painted textured galvanized steel interior and exterior front and top
- Adjustable shelf
- Automatic defrost
- LED lighting in canopy
- Electronically controlled monitoring system
- UL, C-UL Safety and UL Sanitation



	Height	Width	Depth	CuFt	HP	Voltage
Merchandisers						
NLHOAM36	46"	35-1/2"	34"	4.6	1/2	115/60/1
NLHOAM48	46"	47-1/2"	34"	6.3	1/2	115/60/1
NLHOAM60	46"	59-1/2"	34"	7.9	3/4	115/60/1
NLHOAM72	46"	71-1/2"	34"	9.6	3/4	115/60/1

#### **NOVA<sup>™</sup> Open Air Merchandisers**

#### NOVA<sup>™</sup> Vertical Open Air Merchandisers feature a demand evaporator system which adjusts in even the most humid temperatures.

- 24 gauge black painted textured galvanized steel interior and exterior front and top
- Adjustable shelves
- Automatic defrost
- LED lighting in canopy
- Electronically controlled monitoring system
- Retractable vinyl night curtain (shown right with optional stainless finish)
- UL, C-UL Safety and UL Sanitation



	Height	Width	Depth	CuFt	HP	Voltage
60" Height						
NLVOAM36-60	60"	35-1/2"	34"	13.4	1/2	115/60/1
NLVOAM48-60	60"	47-1/2"	34"	18.2	3/4	115/60/1
NLVOAM60-60	60"	59-1/2"	34"	23.1	1	115/60/1
NLVOAM72-60	60"	71-1/2"	34"	28.0	1	115/60/1
72" Height						
NLVOAM36-72	72"	35-1/2"	34"	17.8	3/4	115/60/1
NLVOAM48-72	72"	47-1/2"	34"	24.2	1	115/60/1
NLVOAM60-72	72"	59-1/2"	34"	30.7	1	208-230/60/1
NLVOAM72-72	72"	71-1/2"	34"	37.1	1	208-230/60/1
79" Height						
NLVOAM36-79	79"	35-1/2"	34"	20.8	3/4	115/60/1
NLVOAM48-79	79"	47-1/2"	34"	28.3	1	115/60/1
NLVOAM60-79	79"	59-1/2"	34"	35.9	1	208-230/60/1
NLVOAM72-79	79"	71-1/2"	34"	43.4	1	208-230/60/1

#### **NOVA<sup>™</sup> Refrigerated Prep Tables**

# NOVA<sup>™</sup> Refrigerated Prep Tables can maintain temperatures in even the hottest environment. Its rail and base have different temperature adjustments to best fit your product.

- · Stainless and galvanized steel exterior
- Smooth aluminum interior
- Operating temperatures: +33°F to +41°F in pan well area, +34°F to +38°F in storage area
- Available in 1, 2, 3 and 4 door models
- UL, C-UL and UL Sanitation listed to NSF Standard 7



	Height	Width	Depth	CuFt	HP	Voltage
Prep Tables						
RR152	43-1/2"	47-3/4"	35"	15.0	1/4	115/60/1
RR192	43-1/2"	59-3/4"	35"	19.0	1/4	115/60/1
RR243	43-1/2"	71-3/4"	35"	24.0	1/3	115/60/1
RR283	43-1/2"	83-3/4"	35"	28.0	1/3	115/60/1
RR324	43-1/2"	95-3/4"	35"	32.0	1/3	115/60/1

### **NOVA<sup>™</sup> Milk Coolers**

#### NOVA<sup>™</sup> Cold Wall Milk Coolers are designed for the most demanding abuse with a reinforced floor and 5-year frame warranty.

- Storage for 8, 12, or 16 cases of milk cartons
- Drop lid(s) that provide easy access to self-serve milk
- Exterior self-service door(s) are stainless steel
- Easy roll locking swivel casters
- Heavy-duty floor racks
- Key locking feature
- UL, C-UL, UL Sanitation and ENERGY STAR® rated





	Height	Width	Depth	Cases	HP	Voltage
Open Front						
AR082	43-5/8"	34-5/8"	32-3/4"	8	1/5	115/60/1
AR122	43-5/8"	48-5/8"	32-3/4"	12	1/5	115/60/1
AR162	43-5/8"	62-5/8"	32-3/4"	16	1/5	115/60/1
Dual Access						
AR084	43-5/8"	34-5/8"	33-1/2"	8	1/5	115/60/1
AR124	43-5/8"	48-5/8"	33-1/2"	12	1/5	115/60/1
AR164	43-5/8"	62-5/8"	33-1/2"	16	1/5	115/60/1
Cooler Storage						
GR422	64-7/8"	63-3/8"	34"	28	1/4	115/60/1

Standard Three Year Parts and Labor, Five Year Compressor Warranties

#### **NOVA<sup>™</sup> Ice Cream Cabinets**

#### NOVA<sup>™</sup> Ice Cream Topping Cabinets with a Refrigerated Rail are designed to safely hold all the necessary toppings for sundaes in the NSF Standard 7 rail.

- · Stainless steel exterior
- · Smooth aluminum cabinet and rail interior liners
- Syrup rail meets NSF Standard 7 requirements and has dedicated temperature controls for the base unit and syrup rail
- UL, C-UL and UL Sanitation



NOVA<sup>™</sup> Ice Cream Topping-Dipping and Storage-Dipping Cabinets really are the workhorse of the industry.

- Stainless steel top
- 24 gauge white painted galvanized steel exterior
- Anti-condensate heaters under stainless top cap (Storage-Dipping models)
- Leveling legs
- Jars, ladles and pumps are optional (Topping-Dipping models)
- UL, C-UL and NSF

	Height	Width	Depth	CuFt	HP	Voltage
Refrigerated Rail						<u>.</u>
ZF071	47-1/8"	27-1/2"	33-1/8"	7.0	3/8	115/60/1
ZR152	47-1/8"	54"	33-1/8"	15.0	1/4	115/60/1
ZF152	47-1/8"	54"	33-1/8"	15.0	1/2	115/60/1
Topping Dipping						
ZF124	38-1/4"	43"	30-1/8"	12.5	1/4	115/60/1
ZF174	38-1/4"	54"	30-1/8"	16.8	1/3	115/60/1
Storage Dipping						
FF044	34-1/8"	31-7/8"	21-1/8"	5.2	1/4	115/60/1
FF074	34-1/8"	30-5/8"	30-1/8"	7.6	1/4	115/60/1
FF104	34-1/8"	54"	21-1/8"	11.0	1/4	115/60/1
FF114	34-1/8"	43"	30-1/8"	12.5	1/4	115/60/1
FF154	34-1/8"	54"	30-1/8"	17.3	1/3	115/60/1
FF204	34-1/8"	66-5/8"	30-1/8"	22.0	1/3	115/60/1
FF264	34-1/8"	84-5/8"	30-1/8"	29.1	1/3	115/60/1

#### **NOVA<sup>™</sup> Ice Cream Cabinets**

#### NOVA<sup>™</sup> Ice Cream Dipping Display Freezers are available in three different configurations to best fit any need.

- 24 gauge white painted galvanized steel interior and exterior
- Stainless steel top and attached super structure with tempered plate glass viewing window
- Stainless steel serving deck
- Standard profile, low profile glass and curved glass models available
- UL, C-UL and NSF



	Height	Width	Depth	Cans*	HP	Voltage
Angled Glass						
HF040	50"	26-1/2"	27-3/4"	4	1/3	115/60/1
HF100	50"	47-3/4"	27-3/4"	8	1/2	115/60/1
HF160	50"	69-1/4"	27-3/4"	12	1/2	115/60/1
HF230	50"	90-3/4"	27-3/4"	16	3/4	115/60/1
Curved Glass						
HF040	52"	26-1/2"	27-3/4"	4	1/3	115/60/1
HF100	52"	47-3/4"	27-3/4"	8	1/2	115/60/1
HF160	52"	69-1/4"	27-3/4"	12	1/2	115/60/1
HF230	52"	90-3/4"	27-3/4"	16	3/4	115/60/1
* 9-1/2" diameter 3 gallor	n cans					

Standard Two Year Parts and Labor, Five Year Compressor Warranties

## **NOVA<sup>™</sup> Ice Cream Cabinets**

#### NOVA<sup>™</sup> Ice Cream Angled Display Merchandisers are perfect for grab-andgo applications.

- 24 gauge white polyester enamel painted steel interior and exterior
- Stainless steel top serving deck
- · Adjustable, white epoxy-coated wire shelves
- · Self-closing field reversible rear door
- UL, C-UL and UL Sanitation

#### Standard Two Year Parts and Labor, Five Year Compressor Warranties



#### NOVA<sup>™</sup> Ice Crushers provide crushed ice without requiring a specialty ice maker. Its unrelenting capacity is preferrable for high-volume applications.

- · Crushes ice to sizes from cube to flake
- Stainless steel exterior
- UL, C-UL and UL Sanitation

	Height	Width	Depth	CuFt	HP	Voltage
Merchandisers						
MF122	50-3/16"	40"	31"	11.8	3/4	115/60/1
MF182	50"	60"	31"	18.1	3/4	115/60/1
Ice Crusher						
N14CR	44"	15-1/2"	20"	-	1/4	115/60/1



