Sandscreen





Durable Sandscreen Discs

<u>Professional Quality Screen Discs</u> are longer lasting screens used primarily for resurfacing hardwood floors of all types. The discs sand down old finish so that new finish can be applied. This is known as the "scour method" of refinishing a floor and is most often used on gym floors. All our discs are manufactured with waterproof resins & silicon carbide abrasive, assuring you of the finest quality Professional discs you can buy.

<u>Commercial Quality Superscreen Discs</u> are also used primarily on hardwood floors and are a great value. These Commercial screen discs come in grits ranging from extremely coarse to super fine.

Item No.	Grit	Size	Pk.	Case/Wt.	Cu.	Pro	Com
60 Grit - Extremely Coa	rse						
32149	60	12	10	1.00	0.19	•	
32150	60	13	10	1.50	0.19	•	•
32151	60	14	10	2.00	0.19	•	•
32089	60	15	10	2.00	0.19	•	•
32090	60	16	10	2.00	0.19	•	•
32091	60	17	10	2.50	0.19	•	•
32092	60	18	10	2.50	0.19	•	•
32093	60	19	10	3.50	0.24	•	•
32094	60	20	10	4.25	0.24	•	•
32152	60	21	10	4.25	0.29	•	•
32153	60	22	10	4.25	0.29	•	
32155	60	24	10	4.25	0.34	•	
80 Grit - Coarse							
32156	80	12	10	1.00	0.19	•	
32157	80	13	10	1.50	0.19	•	•
32098	80	15	10	2.00	0.19	•	•
32099	80	16	10	2.00	0.19	•	•
32100	80	17	10	2.50	0.19	•	•
32143	80	18	10	2.50	0.19	•	•
32144	80	19	10	3.50	0.24	•	•
32145	80	20	10	4.25	0.24	•	•
32159	80	22	10	4.25	0.29		•
32161	80	24	10	4.25	0.34		•

Rev.0 January 2019

100 Grit - Medium							ANING PRODUC
32001	100	13	10	1.50	0.19	•	•
32163	100	14	10	2.00	0.19	•	•
32991	100	15	10	2.00	0.19	•	•
32003	100	16	10	2.00	0.19	•	•
32044	100	17	10	2.50	0.19	•	•
32006	100	18	10	2.50	0.19	•	•
32045	100	19	10	3.50	0.24	•	•
32012	100	20	10	4.25	0.24	•	•
32027	100	21	10	4.25	0.29	•	•
32033	100	22	10	4.25	0.29		•
120 Grit - Fine							
32164	120	10	10	0.90	0.19		•
32166	120	12	10	1.00	0.19	•	•
32167	120	13	10	1.50	0.19	•	•
32168	120	14	10	2.00	0.19	•	•
32992	120	15	10	2.00	0.19	•	•
32004	120	16	10	2.00	0.19	•	•
33179	120	17	10	2.50	0.19	•	•
32104	120	18	10	2.50	0.19	•	•
32010	120	19	10	3.50	0.24	•	•
32066	120	20	10	4.25	0.24	•	•
32169	120	21	10	4.25	0.29	•	•
32170	120	22	10	4.25	0.29	•	•
32172	120	24	10	4.25	0.34	•	•
150 Grit - Medium Fine	:						
32173	150	12	10	1.00	0.19		•
32174	150	13	10	1.50	0.19		•
32993	150	15	10	2.00	0.19	•	•
32005	150	16	10	2.00	0.19	•	•
32133	150	17	10	2.50	0.19	•	•
32023	150	18	10	2.50	0.19	•	•
32007	150	19	10	3.50	0.24	•	•
32199	150	20	10	4.25	0.24	•	•

-ACS is certified in ISO 9001:2015

Note: Due to the properties of the material and variable conditions of use, there may be variations in the specifications. Please contact ACS with any questions about the product.

⁻Plant is operating under PROFEPA environmental regulations.



180 Grit - Very Fin	e						
32181	180	13	10	1.50	0.19	•	•
32182	180	14	10	2.00	0.19	•	•
32994	180	15	10	2.00	0.19	•	•
32000	180	16	10	2.00	0.19	•	•
32134	180	17	10	2.50	0.19	•	•
32183	180	18	10	2.50	0.19	•	•
32184	180	19	10	3.50	0.24	•	•
32185	180	20	10	4.25	0.24	•	•
32186	180	21	10	4.25	0.29	•	•
32188	180	23	10	5.00	0.34		•
220 Grit - Extreme	ely Fine				'	,	1
32190	220	12	10	1.00	0.19	•	
32192	220	14	10	2.00	0.19	•	•
32995	220	15	10	2.00	0.19	•	•
32046	220	16	10	2.00	0.19	•	•
32043	220	17	10	2.50	0.19	•	•
32039	220	18	10	2.50	0.19	•	•
32193	220	19	10	3.50	0.24	•	•
32194	220	20	10	4.25	0.24	•	•
220 Grit - Super Fi	ne						
32203	400	15	10	2.00	0.19	•	•
32204	400	16	10	2.00	0.19	•	•
32205	400	17	10	2.50	0.19	•	•
32206	400	18	10	2.50	0.19	•	•
32207	400	19	10	3.50	0.24	•	•
32208	400	20	10	4.25	0.24	•	•

-ACS is certified in ISO 9001:2015

⁻Plant is operating under PROFEPA environmental regulations.