

Hands-Free Hand Sink with Pedestal Base

Assembly Instructions

TOOLS REQUIRED:

Tape Measure
Flat Head Screw Driver
Phillips Head Screw Driver
Adjustable Wrench
48" Level

PARTS:

Hand Sink with Pedestal
Foot Pedal Valve w/ Mounting Screws & Nuts
Faucet with 6" Gooseneck Spout
Basket Drain with Strainer
Wall Clip



Assembly Instructions

1. Mark a plumb line 44" up your wall in the location you want to install your sink. Center the wall clip on the plumb line at a point 41 1/2" up the wall. Ensure the wall clip is level and mount it to your wall (hardware sold separately).
2. Secure the foot pedal valve to the pedestal base using the four included mounting screws and nuts.
3. Install the faucet into the sink's backsplash.
4. Install the basket drain into the sink bowl.
5. Position the hand sink and pedestal in front of the wall clip. Lift the sink slightly and place the rear lip of the backsplash over the wall clip. The base of the pedestal should now be firmly resting flat on the floor and the sink should be secured to the wall via the clip.
6. Connect a hot and cold water supply to the foot pedal valve in accordance with local plumbing codes.
7. Connect a supply line from the foot pedal valve to the faucet.
8. Secure the pedestal to the wall via the rear brace (hardware sold separately).



9. Remove the aerator from the faucet by rotating counterclockwise, and flush the water system. Reinstall the aerator by rotating clockwise.
10. Use a flat head screw driver at the front of the foot pedal valve to adjust the water temperature as needed.
11. Be sure to check all water and drain connections for leaks.
12. Install the front panel by sliding it beneath the front of the sink and lowering it onto the pegs in the pedestal's base.

