

SECURITY CABLE FOR WASTE CONTAINERS

Contents List: 1 – 7' Cable
2 – 8-32 SS Screws
2 – 8-32 SS Locknuts

Tools required: Power Drill
Screwdriver
3/16" Drill bit
11/32" Wrench

INSTALLATION INSTRUCTIONS:

- Remove top cover of waste container.
- Waste Container Base: Select a panel without obstruction or the Grab Bag System panel. Measure 1 1/4" down from the lip of unit and 3/4" in from the corner panel. Mark the spot with a pencil or marker. Using the power drill with 3/16" diameter drill bit, drill a hole through the unit.
- Waste Container Lid: Place lid back on waste container correctly. Choose the lid panel that lines up to the panel you have already drilled a hole in on the base. Measure 1 1/4" from bottom of cover and 3/4" in from the corner panel. Mark the spot with a pencil or marker. Once you have marked the lid panel, remove the lid. Using the power drill with 3/16" diameter drill bit, drill a hole through the cover.
- Waste Container Base: Take one screw and push it through the hole from the inside. Attach one end of eye cable over the end of the screw. Place locknut on screw (nylon insert facing out) and tighten the screw on with your hand. Use 11/32" wrench to hold locknut in place while you tighten and screw in locknut with screwdriver or drill to lock cable in place.
- Waste Container Lid: Push in second screw through the hole from the outside. Attach other eye of cable to end of screw. Place locknut on screw (nylon insert facing out) and tighten the screw on with your hand. Use 11/32" wrench to hold locknut in place while you tighten and screw in locknut with screwdriver or drill to lock cable in place.

If you have any questions, please contact DCI Marketing at 1-800-782-7273.

DCI Marketing • 2727 West Good Hope Road • Milwaukee, WI 53209
Phone: 800-782-7273 or 414-228-7000
Fax: 800-443-7489 or 414-228-4366
www.commercialzone.com

