

Shower Valves











New Models! B-3400 and B-3500 Series Give You More Options

When you choose a T&S Brass product, you know you've chosen one with Reliability Built In^{TM} .

Our Pressure Balancing Shower Valve models include various combinations of shower products to meet your specific needs.

B-3200 and B-3400 Series with Sweat Connections

Our B-3200 and NEW B-3400 series shower valve packages are designed for installation with ½" sweat connections, allowing for easy sweating of copper pipe.

The B-3200 series includes a shower head with 2.5 GPM.

Our NEW B-3400 series gives you a choice of models with a water-saving 1.5 GPM shower head.

B-3300 and B-3500 Series with Threaded Connections

The B-3300 and NEW B-3500 series models have ½" NPT threaded connections for easy installation to traditional threaded pipe, especially designed for installation in facilities that prohibit open flames (i.e. health care facilities).

The B-3300 series includes a 2.5 GPM shower head, and the *NEW* B-3500 series offers a water-saving shower head with a flow rate of 1.5 GPM.

With many different component packages to choose from, these shower products all include a heavy-duty solid brass pressure balancing shower mixing valve.

And with T&S's Reliability Built InTM, you can be assured of owning an outstanding shower product with T&S established quality and durability.



	2.5 GPM	1.5 GPM
1/2" NPT Sweat Connections	B-3200 Series	B-3400 Series
1/2" NPT Threaded Connections	B-3300 Series	B-3500 Series



B-3200/B-3300 Pressure Balancing Shower Valve, 2.5 GPM Shower Head and Tub Spout

FEATURES:

B-3300

Shower

Head

- Temperature limit stop
- Integral supply stops
- Replaceable ceramic cartridge
- Shower valve with heavy-duty solid brass construction (ASSE 1016)
- Polished chrome trim with color coded index
- Choice of 1.5 GPM or 2.5 GPM shower head models
- Chrome plated tub spout

OPTIONS:

- Hand held spray assembly with throttle down feature saves water
- Flexible 5 ft. polished metal hose
- Slide bar with multi-positional bracket
- Optional wall-mount vacuum breaker on spray assembly
- A wide variety of different shower model packages to choose from




www.tsbrass.com

FEATURES and BENEFITS

- The pressure balancing valve (ASSE 1016 listed) prevents scalding and thermal shock and maintains the desired water temperature, even with fluctuations in water pressure
- Integral supply stops allow for easy maintenance of the cartridge without shutting off the water main or disrupting the water supply of other fixtures
- The ceramic cartridge is easy to maintain or replace, and the B-3200/ B-3300 models have a built-in feature that allows for back to back installations

 Its solid brass construction means this shower valve is robust and long lasting



A polished chrome plated metal trim with color

 Two choices of shower head: 1.5 GPM (B-3400 and B-3500 series) or 2.5 GPM (B-3200 and B-3300 series).
 Includes polished chrome shower head with ball joint, arm and flange assembly

- An optional hand held spray assembly (B-3200 and B-3300 series) has a throttle down feature to conserve water, and the hand spray maintains the desired water temperature when re-activated
- The 5 ft. flexible polished metal hose is corrosion-resistant, non-yellowing, easy to clean and long enough to provide the user with 360° rotation of the spray
- An optional slide bar with the variable position bracket allows the user to position the hand held spray at different heights and angles to accomodate personal preference
- An optional in-line vacuum breaker in the flexible hose assembly prevents back flow and water contamination
- The chrome plated tub spout with a diverter lift knob is built to last
- A wide variety of different shower model packages are available to customize your application

(See p. 4 for shower package accessories and parts)



B-3200 and B-3400 Series	B-3200	B-3201	B-3204	B-3204-PBV	B-3205	B-3206	B-3206-VB	
with 1/2" Sweat Connections	B-3400	B-3401	B-3404	B-3404-PBV	B-3405	B-3406	B-3406-VB	
B-3300 and B-3500 Series	B-3300	B-3301	B-3304	B-3304-PBV	B-3305	B-3306	B-3306-VB	
with 1/2" NPT Threaded Connections	B-3500	B-3501	B-3504	B-3504-PBV	B-3505	B-3506	B-3506-VB	B-3507-VB
Pressure balancing mixing valve	X	X	X	X	X	X	X	Х
Chrome plated metal face plate	X	X	Х		Х	X	Х	Х
Tub spout with diverter lift knob	Х							Х
NEW! 1.5 GPM shower head and arm	B-3400 B-3500	B-3401 B-3501				B-3406 B-3506	B-3406-VB B-3506-VB	
2.5 GPM shower head with variable spray pattern and arm	B-3200 B-3300	B-3201 B-3301				B-3206 B-3306	B-3206-VB B-3306-VB	
Diverter valve with trim						Х	Х	
NEW! 1.5 GPM Hand held shower spray assembly with slide bar					B-3405 B-3505	B-3406 B-3506	B-3406-VB B-3506-VB	Х
2.5 GPM Hand held shower spray assembly with slide bar					B-3205 B-3305	B-3206 B-3306	B-3206-VB B-3306-VB	
Vacuum breaker for hand held shower assembly					Optional		Х	Х



PARTS and ACCESSORIES

The following chart is a list of parts and accessories that are included or can be added to your shower packages.

Model	Description	
B-1091	Deluxe shower head 2.2 GPM @ 60 PSI / 2.5 GPM @ 80 PSI	
B-1092	Vandal-resistant shower head 2.2 GPM @ 60 PSI / 2.5 GPM @ 80 PSI	
B-1097*	Two-way diverter valve, 1/2" NPT female	
B-0970-01*	Inline vacuum breaker (not shown)	
SQ-0100*	Diverter valve, 1/2" NPT female	
018998-45	Slip-on spout (not shown)	

^{*} Compatible with the B-3200/B-3300 series only











Additional technical information and model specs for Pressure Balancing Shower Valve models are available online at www.tsbrass.com

Related Single Lever Faucet Models



B-2711 Single Lever Faucet



B-2701 Single Lever Faucet









T&S Brass and Bronze Works, Inc. www.tsbrass.com





