ACCORDING TO REGULATION: 1907/2006

1. Identification of the Substance/mixture and of the company/undertaking

Trade Name: Vegalene GMO- Free Pan Coating (#22050) Trade Names/ Synonyms: N/A **Product Use**: Food Release Aerosol Spray Creation Date: 05/14 Revision Date: N/A

This Safety Data Sheet has been updated in accordance with the Global Harmonized System and is compliant with Regulation 1907/2006

Manufacturer/ Supplier

Par-Way Tryson Company 107 Bolte Lane St. Clair, MO 63077 Tel. (800) 844-4554

Emergency Telephone #

Chemtrec 24 hour Emergency Response Telephone Number: 1-800-424-9300 Chemtrec 24 hour Emergency Response (Outside the U.S. and Canada) Telephone Number: (703) 527-3887

2. Hazards Identification

Classification of the substance or material Classification according to Regulation (EC) No 1272/2008

Extremely Flammable Aerosol

H204 Fire or projection hazard



H317 May cause an allergic skin reaction H335 May cause respiratory irritation

Signal word	Danger
Hazard Statement:	Extremely flammable aerosol
Prevention:	Keep away from heat/sparks/open flames/hot surfacesNo smoking. Do not spray on or
	near an open flame or other ignition source. Pressurized container. Do not puncture or
	burn, even after use.
Response:	Wash hands after handling
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C (122°F)
Disposal:	Dispose in accordance with local, state and federal regulatory requirements.
Hazard(s) not other-	
wise classified:	Not classified

HIMS RATING

FLAMMABILITY

P.P. EQUIPMENT

REACTIVITY

1

4

1

0

HEALTH

ACCORDING TO REGULATION: 1907/2006

2. Hazards Identification

Label elements

Labeling according to Regulation (EC) No 1272/2008 This product is classified and labeled according to the CLP regulation.



Store below 49°C (120°F) Do not spray into or near open flame Contents under pressure, do not puncture or incinerate Avoid spraying in eyes

3. Composition/Information on Ingredients

Chemical characterization: Mixtures-

Description: Mixture of the substances below with nonhazardous additions

Cas #	Description	ACGIH	OSHA	% Range
8001-21-6	SUNFLOWER OIL	NO LIMIT		
8002-43-5	SUNFLOWER LECITHIN	NO LIMIT		
N/A	FLAVORING (natural butter type flavor)	NO LIMIT		
107-92-6	Butyric Acid, Nat.			
	PROPELLANT:			
74-98-6	Propane	2500 ppm	1000 ppm	2.5-10
106-98-7	N-Butane	800 ppm	800 ppm	2.5-10

4. First Aid Measures

Description of First Aid Measures

- After inhalation: Remove to fresh air. If not breathing, give mouth to mouth resuscitation. If breathing is difficult, give oxygen. Call a physician as excessive exposure may cause irritation to the upper respiratory system.
- After Skin Contact: wash with soap and water. Consult a physician if irritation persists.
- After Eye Contact: irrigate with flowing water at least ten minutes. Hold lids open as it helps prevent scratching and minimize irritation. Seek medical attention as material may become embedded.
- After swallowing: Do not induce vomiting. Call a physician and/or poison control center immediately.

Information for doctor:

No further relevant information available

ACCORDING TO REGULATION: 1907/2006

5. Firefighting Measures

EXTINGUISHING MEDIA:

Suitable extinguishing agents: Water fog, standard foam, CO₂, Dry chemical, Halon.

Special Hazards arising from the substance

- Vapors are heavier than air and may travel along the ground to sources of ignition; reports have been made of ignition from pilot lights, heaters, etc. after vapors have been moved by ventilating fans.
- Contents under pressure. Exploding cans may travel great distances discharging burning materials.
- Exposure to temperatures over 49°C (120°F) may cause cans to burst.

Hazardous Decomposition Products

- Oxides of Carbon
- Nitrogen

Advice for Firefighters:

Protective Equipment: wear self- contained breathing apparatus with a full face piece operated in a positive pressure mode.

Water fog may be used to help cool containers to help minimize pressure build-up.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

- Wear PPE as necessary.
- Ensure adequate ventilation; excessive concentration of vapors are flammable
- Keep away from ignition sources

Environmental Precautions

- Do not allow to enter sewers/ surface or ground water.
- Do not puncture or incinerate empty or full cans.

Methods and material for containment and cleaning up

- Clean with soap and water
- Once spills or leaks are cleaned up, dispose of waste in accordance with governmental ordinances.

7. Handling and Storage

Handling:

Precautions for safe handling

- Pressurized container, do not pierce or burn, even after use.
- Do not use if spray button is missing or defective.
- Do not spray on or near open flame or other incandescent material.
- Do not smoke while using.
- Do not puncture, cut, weld, solder, drill, grind, or expose container to heat, flame, sparks, or other sources of ignition.
- Use chemical resistant gloves if the possibility of prolonged contact exists
- General ventilation should be adequate for normal use; if using in a confined area, use necessary means of ventilation to keep from exceeding the TLV.

ACCORDING TO REGULATION: 1907/2006

7. Handling and Storage (cont.)

Precautions for Safe Storage

- Store in cool dry place with temperatures below 49°C (120°F)
- Avoid direct sources of heat and ignition
- Do not use deformed or damaged cans
- Keep out of the reach of children
- Consult local fire and insurance representatives for specific storage requirements in your area

8. Exposure Controls/personal protection

Occupational exposure limits:

occupational exposure nin			
US. OSHA Table Z-	-1 Limits for Air Contaminants (29CF)	R 1910.1000)	
Components	Туре	Value	
Propane (CAS 74-98-6)	PEL	1800mg/m^3	
• • • • •		1000 ppm	
US. NIOSH: Pocket	Guide to Chemincal Hazards		
Components	Туре	Value	
Butane $(C \land S \land 106 \land 07 \land 8)$	TWA	$1000 m g/m^3$	

Butane (CAS 106-97-8)	TWA	1900mg/m^3
		800 ppm
Propane (CAS 74-98-6)	TWA	1800mg/m^3
		1000 ppm

Exposure Control

General protective and hygienic measures:

The usual precautionary measures for using aerosols should be followed.

- Use in a well ventilated area
- Do not spray in eyes or face
- Do not intentionally inhale
- Remove soiled and contaminated clothing
- Wash hands and exposed skin
- If used in an enclosed area without proper ventilation where the TLV is likely to be exceeded, use a NIOSH/MSA approved respirator

Personal Protective Equipment

If evidence of sensitivity to product is experienced:

- Skin: Wear gloves and cover exposed skin
- Eyes: Safety glasses w/ side shields if sensitivity to the eyes occurs.

Respiratory: If permissible levels are exceeded use NIOSH/MSA approved respirator

ACCORDING TO REGULATION: 1907/2006

9. Physical and Chemical Properties

Contents without propellant

- Appearance: golden translucent liquid
- Odor: Buttery
- Flavor: Buttery
- Specific Gravity: 0.92 @ 25°C (77°F)
- Viscosity: 60-80 cPs @ 25 °C (77°F)
- Evaporation Rate: Slower than B-Acetate
- Solubility in Water: negligible
- Vapor Density (air=1): N/A
- Smoke Point: 175°C (350°F) min.
- Flash Point: 205°C (400°F) min.

Contents with propellant

- Appearance: foamy white
- Odor: Buttery
- Flavor: Buttery
- Percent volatile: 10-20%
- Drum Test: Negative
- Flash Point: 68.89°C (-156°F) propellant
- Flammability Class: flammable
- Flame extension @ 21°C (70°F): > 45.72 cm (18 inches)
- Flame Back: none
- Vapor Pressure @ 21°C (70°F) : 70<u>+</u> 5psig
- Vapor Pressure @ 54.4°C (130°F): 100 <u>+</u> 10 psig
- Explosive Limits:
 - Lower: 1.8%
 - Upper: 9.5 %

10. Stability and reactivity

Reactivity

Chemical Stability: Normally stable

Possibility of hazardous reactions: no dangerous reactions known.

Conditions to avoid: keep away from flames and ignition sources; do not store above 48.89°C (120°F) Incompatible materials: strong oxidizers.

Hazardous Polymerization: will not occur.

ACCORDING TO REGULATION: 1907/2006

11. Toxicological information

Acute Effects:

Eyes: Can cause pain and slight corneal injury. Vapors irritate eyes.
Skin: Prolonged or repeated contact may cause irritation defatting. May be irritant to skin and mucous membranes
Breathing: Fumes from the propellant are mildly anesthetic, narcotic effects may be seen in the 5,000-10,000 ppm range. High concentrations can cause dizziness, headaches, narcosis and nausea.
Germ cell mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenic: This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Reproductive Toxicity: This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity repeated exposure: Not classified Specific target organ toxicity repeated exposure: Not classified

Chronic Effects:

Target Organs/Systematic Effects: Excessive exposure can cause respiratory irritation, liver or kidney damage.

12. Ecological information

Toxicity

Aquatic toxicity: Not expected to be harmful to aquatic organisms. Additional ecological information: Do not allow large quantities of product to reach ground water, water course or sewage system. Results of PBT and vPvB assessment PBT: Not applicable vPvB: Not applicable

13. Disposal information

Waste treatment methods

Do not dispose of in a trash compactor or incinerate. Disposal must be made according to local and federal official regulations.

14. Transport information

DOT

UN Number: 1950UN Proper Shipping Name:Aerosol, FlammableTransport Hazard Class:2.1Subsidiary Class(es):Not availableContainer Size :6-21 oz aerosol cansSpecial precautions for user :Read Safety Instructions, SDS and emergency procedures before
handlingLabels required :None

ACCORDING TO REGULATION: 1907/2006

DOT		
	Special Provisions :	N82
	Packaging exceptions :	306
	Packaging non bulk :	None
	Packaging bulk :	None
	Propellant:	Propane/N-Butane
ATA		
	UN Number: 1950	
	UN Proper Shipping Name:	Aerosol, Flammable
	Transport Hazard Class:	2.1
	Subsidiary Class(es):	Not available
	Container Size :	6-21 oz aerosol cans
	Environmental Hazards:	No
	Labels Required:	2.1
	ERG Code:	10L
	Special Precautions for user :	Read Safety Instructions, SDS and emergency procedures before handling
	Packaging Exceptions :	LTD QTY (Limited Quantity)
MDG	r	
	UN Number: 1950	
	UN Proper Shipping Name:	AEROSOLS
	Transport Hazard Class:	2.1
	Subsidiary Class(es):	Not available
	Container Size :	6-21 oz aerosol cans
	Environmental Hazards:	
	Marine pollutant:	No
	Labels Required:	None
	EmS:	F-D, S-U
	Special Precautions for user :	Read Safety Instructions, SDS and emergency procedures before handling
	Packaging Exceptions :	LTD QTY (Limited Quantity)

Transport in bulk according to Annex II Of MARPOL 73/78 and the IBC Code: Not applicable.





15. Regulatory information

US federal regulations

This product is a "Hazardous chemical" as defined by the OSHA hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances: Not applicable.

ACCORDING TO REGULATION: 1907/2006

15. Regulatory information	n (cont.)	
CERCLA Hazardous Su US. OSHA Specifically F	rt Notification (40 CFR 707, Subpt. D): Not Ibstance List (40 CFR 302.4): Not listed Regulated Substances (29 CFR 1910.1001-10 elease notification: Not regulated	-
Hazard categories:	nd Reauthorization Act of 1986 (SARA) Immediate Hazard-No Delayed Hazard-Yes Fire Hazard-Yes Pressure Hazard-Yes Reactivity Hazard-No	
SARA 302 Extremely ha SARA 311/312 Hazardou		
Clean Air Act (CAA) S Safe Drinking Water A	ection 112 Hazardous Air Pollutants (HAPS ection 112 (r) Accidental Release Prevention Butane (CAS 106-97-8) Propane (CAS 74-98-6) ct (SDWA): Not regulated istration (DEA). Lsit 2, Essential Chemicals	n (40 CFR 68.130):
	ical Code Number: Not listed	(21 CFR 1310.02(b) and
US State Regulations This product does n or other reproductiv	ot contain a chemical known to the State of Ca	alifornia to cause cancer, birth defects
Butane (CA Propane (C. US Pennsylvania F Butane (CA Propane (C. US. California Pro California S	orker and Community Right-to-Know ActAS 106-97-8)500 lbsAS 74-98-6)500 lbs RTK-Hazardous Substances AS 106-97-8)AS 74-98-6) oposition 65 Safe Drinking Water and Toxic Enforcement Avn to contain any chemicals currently listed as	
International Inventories		
Country(s) or Region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substa (AICS)	nces Yes
Canada	Domestic Substances List (DSL)	Yes

ACCORDING TO REGULATION: 1907/2006

15. Regulatory information (cont.)

International Inventories

Country(s) or Region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemical List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventor	y Yes
. A "Var" in director this was d		and here the community of commutations (

* A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)
 * A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory by the governing country(s)

16. Other information

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Par-Way Tryson extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. Recipients are advised to confirm in advance of the need that the data is correct, applicable and suitable to their circumstances. The data on this Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. The data on the safety data sheet are not meant to be used as specifications, only guideline information as to safe use of the product. User should also refer to OSHA, State and local safety laws before use. Hazard communication regulations require that employees must be trained on how to use a Safety Data Sheet as a source of hazard information. Standards change without notice; it is the responsibility of the recipient to assure that their personnel have been notified of any changes which may affect them. Prepared by: Gary Daniels, Quality Systems Auditor, Par-Way Tryson Co.

History of Changes:

Revised:	Replaces:	Nature of Change:	Approved/Verified by:
05/2014	NDA	• New	Long Daniels