



## Safety Data Sheet

Material Name: Elmer's No-Wrinkle Rubber Cement

SDS ID: SDS-34

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

**Material Name**

Elmer's No-Wrinkle Rubber Cement

**Synonyms**

E141; E904; 231, 232, 233, 234, 61518; E63231T; E425; E1539, 60818

**Chemical Family**

Adhesive

**Product Use**

Adhesive

**Restrictions on Use**

None known.

**Details of the supplier of the safety data sheet**

Elmer's Products, Inc  
460 Polaris Parkway, Suite 500  
Westerville, OH 43082  
USA  
Phone:1-888-435-6377  
Fax:1-800-741-6046  
Email:comments@elmers.com

Emergency Phone Number:  
Poison Control Center  
1-888-516-2502

For additional product information, access our website at [www.elmers.com](http://www.elmers.com). To place an order, call 1-800-848-9400.

### Section 2 - HAZARDS IDENTIFICATION

**Classification in accordance with paragraph (d) of 29 CFR 1910.1200.**

Flammable Liquids - Category 2

Aspiration Hazard - Category 1

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2A

Specific Target Organ Toxicity - Single Exposure - Category 3

Specific Target Organ Toxicity - Repeated Exposure - Category 2

Hazardous to the Aquatic Environment - Acute - Category 1

Hazardous to the Aquatic Environment - Chronic - Category 1



## Safety Data Sheet

Material Name: Elmer's No-Wrinkle Rubber Cement

SDS ID: SDS-34

### GHS Label Elements

#### Symbol(s)



### Signal Word

Danger

### Hazard Statement(s)

Highly flammable liquid and vapor.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life with long lasting effects.

### Precautionary Statement(s)

#### Prevention

Keep container tightly closed.

Keep away from heat/sparks/open flame/hot surfaces - No smoking.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Take precautionary measures against static discharge.

Use only non-sparking tools.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Avoid release to the environment.

#### Response

In case of fire: Use appropriate media to extinguish.

Collect spillage.

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash before reuse.

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do NOT induce vomiting.

Specific treatment (see label).



## Safety Data Sheet

Material Name: Elmer's No-Wrinkle Rubber Cement

SDS ID: SDS-34

### Storage

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
142-82-5	n-Heptane	> 85

## Section 4 - FIRST AID MEASURES

### Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

### Skin

Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

### Eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

### Ingestion

Immediately call a POISON CENTER or doctor/physician. DO NOT induce vomiting. Aspiration hazard. If vomiting occurs, keep head lower than hips to help prevent aspiration. Aspiration into the lungs may result in pulmonary edema and pneumonitis.

### Most Important Symptoms/Effects

#### Acute

May be fatal if swallowed and enters airways. May cause respiratory irritation, skin irritation, eye irritation.

#### Delayed

May cause damage to organs through prolonged or repeated exposure.

## Section 5 - FIRE FIGHTING MEASURES

### Extinguishing Media

#### Suitable Extinguishing Media

Dry chemical, foam or carbon dioxide, water.

#### Unsuitable Extinguishing Media

None known.

### Special Hazards Arising from the Chemical

Highly flammable liquid and vapor. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Vapor/air mixtures are explosive.

### Advice for firefighters

Wear self-contained breathing apparatus with a full facepiece and protective clothing.



## Safety Data Sheet

Material Name: Elmer's No-Wrinkle Rubber Cement

SDS ID: SDS-34

### Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Do not scatter spilled material with high-pressure water streams. In case of fire and/or explosion do not breathe fumes. Stay upwind and keep out of low areas.

## Section 6 - ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Keep unnecessary people away, isolate hazard area and deny entry. Do not breath gas/vapor/spray. Avoid contact with eyes and skin. Vapors may cause drowsiness and dizziness. Wear personal protective clothing and equipment, see Section 8.

### Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources if safe to do so. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. Ventilate closed spaces before entering. Stop leak if possible without personal risk. Reduce vapors with water spray. Ground any equipment used in handling. Do not touch or walk through spilled material. Absorb with earth, sand or other non-combustible material and transfer to container. Use only non-sparking tools. Large spills: Dike for later disposal.

### Environmental Precautions

Prevent entry into waterways, sewers, basements, or confined areas. Avoid release to the environment. Collect spillage.

## Section 7 - HANDLING AND STORAGE

### Precautions for Safe Handling

Avoid contact with eyes and skin. Do not breathe dust/fume/gas/mist/vapors/spray. Use only with adequate ventilation. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid heat, flames, sparks and other sources of ignition. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

### Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

### Incompatible Materials

acids, bases, amines, oxidizing materials.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### Component Exposure Limits

n-Heptane	142-82-5
ACGIH:	400 ppm TWA
	500 ppm STEL
NIOSH:	85 ppm TWA ; 350 mg/m <sup>3</sup> TWA



## Safety Data Sheet

**Material Name: Elmer's No-Wrinkle Rubber Cement**

**SDS ID: SDS-34**

	440 ppm Ceiling 15 min ; 1800 mg/m <sup>3</sup> Ceiling 15 min
	750 ppm IDLH
Europe:	500 ppm TWA ; 2085 mg/m <sup>3</sup> TWA
OSHA (US):	500 ppm TWA ; 2000 mg/m <sup>3</sup> TWA
Mexico:	400 ppm TWA VLE-PPT ; 1600 mg/m <sup>3</sup> TWA VLE-PPT
	500 ppm STEL [PPT-CT ] ; 2000 mg/m <sup>3</sup> STEL [PPT-CT ]
	Skin - potential for cutaneous absorption

**EU - Occupational Exposure (98/24/EC) - Binding Biological Limit Values and Health Surveillance Measures**

There are no biological limit values for any of this product's components.

**ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)**

There are no biological limit values for any of this product's components.

**Engineering Controls**

Use explosion-proof electrical/ventilating/lighting equipment. Ensure compliance with applicable exposure limits.

**Individual Protection Measures, such as Personal Protective Equipment**

**Eye/face protection**

Wear chemical safety goggles.

**Skin Protection**

Wear appropriate chemical resistant clothing.

**Respiratory Protection**

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

**Glove Recommendations**

Wear appropriate chemical resistant gloves.

**Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	opaque liquid	<b>Physical State</b>	liquid
<b>Odor</b>	mild odor, solvent odor	<b>Color</b>	Not available
<b>Odor Threshold</b>	Not available	<b>pH</b>	Not available
<b>Melting Point</b>	Not available	<b>Boiling Point</b>	90 °C
<b>Boiling Point Range</b>	Not available	<b>Freezing point</b>	Not available
<b>Evaporation Rate</b>	<1 (ether =1 )	<b>Flammability (solid, gas)</b>	Flammable
<b>Autoignition Temperature</b>	Not available	<b>Flash Point</b>	-4 °C (TCC )
<b>Lower Explosive Limit</b>	Not available	<b>Decomposition temperature</b>	Not available



## Safety Data Sheet

Material Name: Elmer's No-Wrinkle Rubber Cement

SDS ID: SDS-34

Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	>1	Specific Gravity (water=1)	0.71
Water Solubility	almost insoluble	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Solubility (Other)	Not available
Density	Not available	Volatility	90 %
Molecular Weight	Not available		

### Section 10 - STABILITY AND REACTIVITY

#### Reactivity

No hazard expected.

#### Chemical Stability

Stable under normal conditions of use.

#### Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

#### Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Containers may rupture or explode if exposed to heat.

#### Incompatible Materials

acids, bases, amines, oxidizing materials.

#### Hazardous decomposition products

oxides of carbon.

### Section 11 - TOXICOLOGICAL INFORMATION

#### Information on Likely Routes of Exposure

##### Inhalation

May cause respiratory irritation.

##### Skin Contact

Causes skin irritation.

##### Eye Contact

Causes serious eye irritation.

##### Ingestion

Aspiration hazard. May be fatal if swallowed.

#### Acute and Chronic Toxicity

##### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

##### n-Heptane (142-82-5)

Oral LD50 Mouse 5000 mg/kg

Dermal LD50 Rabbit 3000 mg/kg

Inhalation LC50 Rat 103 g/m<sup>3</sup> 4 h



## Safety Data Sheet

Material Name: Elmer's No-Wrinkle Rubber Cement

SDS ID: SDS-34

### Product Toxicity Data

#### Acute Toxicity Estimate

Dermal	> 2000 mg/kg
Inhalation - Vapor	> 20 mg/L
Oral	> 2000 mg/kg

#### Immediate Effects

May cause respiratory irritation, skin irritation, eye irritation. May be fatal if swallowed.

#### Delayed Effects

May cause damage to organs through prolonged or repeated exposure.

#### Irritation/Corrosivity Data

Causes skin irritation. May cause eye irritation. May cause respiratory irritation.

#### Respiratory Sensitization

No information available for the product.

#### Dermal Sensitization

No information available for the product.

#### Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

#### Germ Cell Mutagenicity

No information available for the product.

#### Tumorigenic Data

No data available

#### Reproductive Toxicity

No information available for the product.

#### Specific Target Organ Toxicity - Single Exposure

Respiratory system

#### Specific Target Organ Toxicity - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

May be fatal if swallowed.

#### Medical Conditions Aggravated by Exposure

No data available.

## Section 12 - ECOLOGICAL INFORMATION

### Component Analysis - Aquatic Toxicity

n-Heptane	142-82-5
Fish:	LC50 96 h Cichlid fish 375 mg/L

## Section 13 - DISPOSAL CONSIDERATIONS

#### Disposal Methods

Dispose in accordance with all applicable regulations.



## Safety Data Sheet

Material Name: Elmer's No-Wrinkle Rubber Cement

SDS ID: SDS-34

### Component Waste Numbers

n-Heptane	142-82-5
RCRA:	waste number D001
	waste number D001
	D001

### Section 14 - TRANSPORT INFORMATION

#### Component Marine Pollutants

This material contains one or more of the following chemicals required by US DOT to be identified as marine pollutants

Component	CAS #	Minimum Concentration
n-Heptane	142-82-5	DOT regulated marine pollutant (related to Heptane isomers)

#### US DOT Information:

Shipping Name: ADHESIVES

Hazard Class: 3

UN/NA #: UN1133

Packing Group: II

Required Label(s): 3

#### IATA Information:

Shipping Name: ADHESIVES

Hazard Class: 3

UN#: UN1133

Packing Group: II

Required Label(s): 3

#### IMDG Information:

Shipping Name: ADHESIVES

Hazard Class: 3

UN#: UN1133

Packing Group: II

Required Label(s): 3

#### TDG Information:

Shipping Name: ADHESIVES

Hazard Class: 3

UN#: UN1133

Packing Group: II

Required Label(s): 3





## Safety Data Sheet

Material Name: Elmer's No-Wrinkle Rubber Cement

SDS ID: SDS-34

**Section 15 - REGULATORY INFORMATION**

**U.S. Federal Regulations**

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

<b>n-Heptane</b>	<b>142-82-5</b>
TSCA 12b:	Section 4 , 1 % de minimus concentration (related to Hydrocarbons, C>4)

**SARA Section 311/312 (40 CFR 370 Subparts B and C)**

**Acute Health:** Yes **Chronic Health:** Yes **Fire:** Yes **Pressure:** No **Reactivity:** No

**U.S. State Regulations**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
<b>n-Heptane</b>	<b>142-82-5</b>	Yes	Yes	Yes	Yes	Yes

**Not listed under California Proposition 65**

**Canada Regulations**

**Canadian WHMIS Ingredient Disclosure List (IDL)**

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

<b>n-Heptane</b>	<b>142-82-5</b>
	1 %

**Component Analysis - Inventory**

**n-Heptane (142-82-5)**

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - Annex 1	KR - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes	Yes

**Section 16 - OTHER INFORMATION**

**HMIS Rating**

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

**Summary of Changes**

Updated SDS: 10/21/2016

**Key / Legend**

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania\*; CAS - Chemical Abstracts Service; CFR - Code of



## Safety Data Sheet

**Material Name: Elmer's No-Wrinkle Rubber Cement**

**SDS ID: SDS-34**

Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KECI - Korea Existing Chemicals Inventory; KECL - Korea Existing Chemicals List; KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; NDSL - Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH - Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); WHMIS - Workplace Hazardous Materials Information System (Canada).

### **Other Information**

#### **Disclaimer:**

Supplier gives no warranty whatsoever, including the warranties of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser shall determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental, consequential or any other damages arising out of the use or misuse of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights.