

Liquid Skin® Adhesive

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Liquid Skin® Adhesive

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Skin Protectant

1.3. Details of the supplier of the safety data sheet

Chemence Medical Products, Inc.
200 Technology Drive
Alpharetta, GA 30005-2222
T 770-664-6624

1.4. Emergency telephone number

Emergency number : Chemtrec 1 800 424 9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 4 H227
Skin Irrit. 2 H315
Eye Irrit. 2A H319
Skin Sens. 1 H317
STOT SE 3 H335

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H227 - Combustible liquid
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

Precautionary statements (GHS-US) :

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
P264 - Wash thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P272 - Contaminated work clothing should not be allowed out of the workplace
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER/doctor if you feel unwell
P321 - Specific treatment (see label)
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use carbon dioxide, dry chemical, or foam for extinction
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

Liquid Skin® Adhesive

Safety Data Sheet

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	GHS-US classification
2-Propenoic acid, 2-cyano-, butyl ester	(CAS No) 6606-65-1	> 99	Not classified

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Seek medical attention.
First-aid measures after skin contact	: If unintended bonding of skin tissue occurs, peel of the adhesive, but do not pull skin apart. Application of petroleum jelly or acetone may help loosen the bond. As the epidermal layer grows the adhesive will naturally slough off.
First-aid measures after eye contact	: Rinse immediately with copious amounts of water and seek medical attention. If residual adhesive remains, apply topical ophthalmic ointment to help loosen the bond. Do not pull eye lids apart.
First-aid measures after ingestion	: If taken orally the product will polymerize rapidly, adhering to the mouth. Ensure breathing passages are clear. Saliva will separate any solidified product within two days. Prevent accidental swallowing. Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Will bond skin. May cause burns if dropped on clothing in contact with the skin. May cause allergic reaction on skin of acrylate sensitive individuals.
Symptoms/injuries after eye contact	: Causes serious eye irritation. May cause eye lids to bond.
Symptoms/injuries after ingestion	: May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide, dry chemical, alcohol foam.
Unsuitable extinguishing media	: None.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid.
Explosion hazard	: None known.

5.3. Advice for firefighters

Protection during firefighting	: Firefighters should wear full protective gear.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: If possible, stop flow of product.
Methods for cleaning up	: Contain and/or absorb spill with inert material, then place in suitable container.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with eyes, skin and clothing.
-------------------------------	---

Liquid Skin® Adhesive

Safety Data Sheet

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry place.

7.3. Specific end use(s)

Skin adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls : General (mechanical) room ventilation is expected to be satisfactory for normal handling.
Hand protection : Use impervious gloves such as neoprene, nitrile, or rubber for hand protection.
Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable working clothes.
Respiratory protection : None required under normal product handling conditions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear.
Color : Colorless or Purple.
Odor : sharp.
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : ~ -30°C
Freezing point : No data available
Boiling point : 83 - 84 °C @ 3mm Hg
Flash point : > 85 °C
Self ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : ~0.4 mm Hg @ 25°C
Relative vapour density at 20 °C : No data available
Relative density : 1.01 @20°C
Solubility : Water: Insoluble (Polymerizes in the presence of water)
Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

None.

10.5. Incompatible materials

Amines, Bases.

Liquid Skin® Adhesive

Safety Data Sheet

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)	: Not classified
--	------------------

Aspiration hazard	: Not classified
-------------------	------------------

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Dispose of contents/container in accordance with local/regional/national/international regulations.
--------------------------------	---

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

DOT NA no.	NA1993
------------	--------

14.2. UN proper shipping name

DOT Proper Shipping Name	: Combustible liquid, n.o.s. (Cyanoacrylate ester)
Department of Transportation (DOT) Hazard Classes	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
DOT Symbols	: D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name
Packing group (DOT)	: III - Minor Danger
DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241

Liquid Skin® Adhesive

Safety Data Sheet

SECTION 15: Regulatory information

15.1. US Federal regulations

2-Propenoic acid, 2-cyano-, butyl ester (6606-65-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

No additional information available

SECTION 16: Other information

Full text of H-phrases:

Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 4	Flammable liquids, Category 4
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H227	Combustible liquid
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product