
SPEC. 91588 APPLICATION: PRODUCT NAME: 4" C/C BACKSPLASH FAUCET JOB NAME: SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS QUANTITY: ITEM NO. MODEL: ☐ 91588 W/6" SWING SPOUT WITH WRIST HANDLES ☐ 94544 W/8" SWING SPOUT WITH WRIST HANDLES ☐ 45330 W/10" SWING SPOUT WITH WRIST HANDLES ►| 4" |- [101.6mm] ☐ 45349 W/12" SWING SPOUT WITH WRIST HANDLES ☐ 45357 W/14" SWING SPOUT WITH WRIST HANDLES ☐ 45365 W/16" SWING SPOUT WITH WRIST HANDLES "A" **OPTIONS OR MODIFICATIONS:** ☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH ☐ DJ SUB-ASSY (7-1/4" OR 13") CIRCLE LENGTH ☐ ELBOWS □ VANDAL RESISTANT KIT

MODEL	DIM "A"	DIM "B"	DIM "C"
91588	2"	5-3/8"	6"
	[50.8mm]	[136.5mm]	[152.4mm]
94544	2-1/4"	6"	8"
	[57.2mm]	[152.4mm]	[203.2mm]
45330	2-7/8"	6-1/2"	10"
	[73.0mm]	[165.1mm]	[254.0mm]
45349	3-1/8"	6-3/4"	12"
	[79.4mm]	[171.5mm]	[304.8mm]
45357	4-1/8"	7-3/4"	14"
	[104.8mm]	[196.9mm]	[355.6mm]
45365	4-7/8"	8-3/4"	16"
	[123.8mm]	[222.3mm]	[406.4mm]

ROUGH-IN:



(I) ANSI/A112.18.1M

FEATURES:

□ OTHER _

- * 4" C/C BACKSPLASH
- * SWIVELLING SEAT DISKS
- * HOT SIDE STEM RIGHT HAND
- * COLD SIDE STEM LEFT HAND
- * STAINLESS STEEL SEATS
- * STAINLESS STEEL SEAT SCREWS
- * STAINLESS STEEL HANDLE SCREWS

☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE

* 1/2" SLIP JOINT

SYSTEM LIMITS

- * TEMP: 40°F MIN. TO 140°F MAX.
- * PRESSURE 200 PSI MAX. STATIC
- * 2.20 GPM AT 80 PSI

SHIPPING WEIGHT

* 4.25 LBS



