# 3M<sup>TM</sup> Sky Blue Hi-Performance Burnish Pad 3050

Technical Data —	
Technical Data	
March 2012	

# **Description**:

The 3M™ Sky Blue HiPerformance Burnish Pad 3050
is a high quality floor
maintenance pad, made of
synthetic fiber, having resins
throughout and bonded to the
web structure. The burnishing
floor pad has been optimized for
use on softer floor finishes where
frequent burnishing is required.

The burnishing pad has been designed to deliver:

- High pad durability
- Higher gloss
- Reduced burn marks and minimization of dust, point build-up, and swirl marks

## **Applications**:

The pad is for use with high speed equipment operating at 1500-3000 rpm. It is ideal for use on softer floor finishes such as those typically used in retail environments where frequent burnishing is required.

#### **General Use Directions:**

- Dust mop and clean floor surface. 3M<sup>™</sup> Easy Trap Duster may be effectively used for dusting floor. Note: Burnish only on a clean floor.
- Install 3M<sup>™</sup> Sky Blue Hi-Performance Burnish Pad 3050 on a high-speed burnisher. It may be a corded electric, battery, or propane burnisher.
- 3. Burnish to a high gloss using overlapping passes.
- Dust mop floor surface with 3M™ Easy Trap Duster.

## Maintenance:

- After burnishing, if next burnishing will be with same pad, leave pad on burnisher. Otherwise, remove pad and store.
- Examine pad. Remove excessive dust and debris with a brush or vacuum.
- 3. Flip pad periodically.
- 4. Discard pad if thickness decreases to point where pad holder hooks extend completely through pad.

# **Product Specifications:**

- Pad thickness: 1 inch nominal
- 2. Center hole diameter: 3.25 inches



### **3M Branch Sales Offices**

#### **ANCHORAGE**

11151 Calaska Circle Anchorage, AK 99515 Telephone: 907/522-5200 Facsimile: 907/522-1645

### **CONTINENTAL UNITED STATES**

Customer Service Department 3M Center Building 223-2N-21 St. Paul, MN 55144-1000 Order Entry: 1-800-852-9722 Facsimile: 1-800-447-0408

#### HONOLULU

4443 Malaai Street Honolulu, HI 96818 Mail to: P.O. Box 30048 Honolulu, HI 96820 Telephone: 808/422-2721 Facsimile: 808/422-9557

#### **CANADA**

1840 Oxford Street East London, Ontario, N5V 3G2 Canada

Telephone: 519/451-2500 Facsimile: 519/452-6262

# Important Notice to User:

**Technical Information:** The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

**Product Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty and Limited Remedy: 3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

