



Technical Data

3M™ Stainless Steel Cleaner & Polish

Description

3M™ Stainless Steel Cleaner and Polish is a ready-to-use cleaner and polish packaged in an aerosol container. The product is dispensed as a white, non-evaporating foam.

Special Features

- Cleans and polishes in one step
- Leaves no greasy build-up on surfaces
- Pleasant citrus fragrance
- Leaves a light protective film
- Masks blemishes
- Slows resoiling
- Reduces fingerprinting
- Resists streaking
- Empty containers may be disposed of in sanitary landfills in accordance with local regulations
- NSF® Certified for use in federally-inspected meat and poultry processing plants

Applications

- Suitable for use on stainless steel, chrome, architectural aluminum, and other interior metal surfaces
- Not intended as a glass cleaner

Packaging

- 21-ounce (600 g) aerosol can
- 10-ounce aerosol can
- 12 cans per case

General Use Directions

Light soil

1. Shake can well.
2. Turn spray tip so arrow points to dot on can rim.
3. Hold can upright 6-12 inches from surface.
4. Spray area lightly directly on surface or on a clean, dry cloth.
5. Wipe area and polish until dry.

Heavy soil

1. Spray 3M™ Stainless Steel Cleaner and Polish onto a Scotch-Brite™ Light Duty Scrubbing Pad 9030 or Scotch-Brite™ Light Duty Scrub Sponge 63.
2. Vigorously rub the surface to remove the heavy soil. Always rub stainless steel in the direction of the grain.
3. Wipe surface with a clean, dry cloth to remove any excess cleaner.
4. Using a clean dry cloth, buff in the direction of the grain to achieve maximum shine.

NOTE:

Refer to product Material Safety Data Sheet for specific physical properties, health hazard, first aid and precautionary information.

3M™ Stainless Steel Cleaner and Polish:

- 10-2819-0

3M Branch Sales Offices

ANCHORAGE

11151 Calaska Circle
Anchorage, AK 99515

Telephone: 907/522-5200
Facsimile 907/522-1645

HONOLULU

4443 Malaai Street
Honolulu, HI 96818
Mail to: P.O. Box 30048
Honolulu, HI 96820

Telephone: 808/422-2721
Facsimile 808/422-9557

CONTINENTAL UNITED STATES

Customer Service Department
3M Center Building 223-5S-07
St. Paul, MN 55144-1000

Order Entry 1-800-852-9722
Facsimile 1-800-447-0408

CANADA

1840 Oxford Street East
London, Ontario, Canada
N5V 3G2
Mail to: P.O. Box 5757
London, Ontario, Canada
N6A 4T1

Telephone: 800/364-3577
Facsimile: 800/479-4453

Important Notice to User

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty and Limited Remedy: 3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.



**Building and Commercial
Services Division**
St. Paul, MN 55144-1000
1-800-852-9722
www.3M.com/facility

NSF and the mark are registered trademarks of NSF International.
3M and Scotch-Brite are trademarks of 3M Company.
Used under license in Canada.
© 3M 2013. All rights reserved.
60140