January 2013

3M[™] Liquid Stainless Steel Cleaner and Polish

Description

3M™ Liquid Stainless Steel Cleaner and Polish is designed to clean and polish metal surfaces in one step.

Special Features

- Thick, creamy formula provides smooth application and clings to vertical surfaces
- Cleans and polishes in one step with a pleasant citrus fragrance
- Leaves no greasy build-up on surfaces
- Leaves a light protective film after cleaning
 - Masks blemishes
 - Slows resoiling
 - Helps reduce fingerprints
 - Resists streaking
- Non-flammable formula

Applications

- Suitable for use on stainless steel, chrome, architectural aluminum, and other interior metal surfaces
- Not intended as a glass cleaner

Packaging

- 32-ounce bottle (quart)
 - 6 bottles per case with one trigger sprayer

Quarts contain ready-to-use product.

General Use Directions

Light soiling

- 1. Shake thoroughly.
- 2. Apply a small amount of cleaner to the surface using a trigger sprayer or clean cloth.
- 3. Clean entire area and polish to desired shine using clean dry cloth.

Heavy soiling

- Apply a liberal amount of 3M[™] Stainless Steel Cleaner and Polish onto a Scotch-Brite[™] Light Duty Cleansing Pad No. 98 or Scotch-Brite[™] Light Duty Scrub Sponge No. 63.
- 4. Vigorously rub the surface to remove the heavy soil. Always rub stainless steel in the direction of the grain.
- Wipe surface with a terry cloth towel to remove the excess cleaner from the surface.
- Using a clean dry cloth, buff in the direction of the grain to achieve maximum shine.

NOTE:

Refer to product Material Safety Data Sheet for specific physical properties, health hazard, first aid and precautionary information.

3M™ Liquid Stainless Steel Cleaner and Polish MSDS:

31-0596-2



3M Branch Sales Offices

ANCHORAGE

11151 Calaska Circle Anchorage, AK 99515

Telephone: 907/522-5200 Facsimile 907/522-1645

HONOLULU

4443 Malaai Street Honolulu, HI 96818 Mail to: P.O. Box 30048 Honolulu, HI 96820

Telephone: 808/422-2721 Facsimile 808/422-9557

CONTINENTAL UNITED STATES

Customer Service Department 3M Center Building 223-5S-07 St. Paul, MN 55144-1000

Order Entry 1-800-852-9722 Facsimile 1-800-447-0408

CANADA

1840 Oxford Street East London, Ontario, Canada N5V 3G2

Mail to: P.O. Box 5757 London, Ontario, Canada

N6A 4T1

Telephone: 800/364-3577 Facsimile: 800/479-4453

Important Notice to User

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty and Limited Remedy: 3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

