



KM-1301S_J(3)

STACKABLE ICE CUBER



KM-1301S_J(3)
07/20/17
Item # 13056

W x D x H
48" x 27^{3/8}" x 27^{3/8}"

KM Edge DESIGN

KM-1301SAJ
Air-Cooled 1 Phase

KM-1301SWJ
Water-Cooled 1 Phase
Shown on optional bin B-900

KM-1301SRJ ★
Remote Air-Cooled 1 Phase

KM-1301SAJ3 ★
Air-Cooled 3 Phase

KM-1301SWJ3
Water-Cooled 3 Phase

KM-1301SRJ3 ★
Remote Air-Cooled 3 Phase



Item #: _____
Project: _____
Qty: _____
AIA#: _____

Features

- ▶ Individual crescent cube
- ▶ Stainless steel evaporator
- ▶ CycleSaver™ design 

- Up to 1433 lbs. of ice production per 24 hours
- Stackable for 2866 lbs. per 24 hours ice production in the same floor space
- Durable stainless steel exterior
- Protected by H-Guard Plus  Antimicrobial Agent
- EverCheck™ alert system 
- Removable air filters (Air-cooled model only)
- R-404A Refrigerant

Available on Bins:


B-800 B-1150SS B-1500SS Top kit may be required.
B-900 B-1300SS B-1650SS See Bin Spec Sheets.

Warranty:

3 Year Parts & Labor on entire machine. 5 Year Parts & Labor on Evaporator. 5 Year Parts on Compressor; air-cooled condenser coil. Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

		ICE PRODUCTION				WATER USAGE			ELECTRICAL			Heat Rejection BTU/hr.	Shipping Weight	ENERGY STAR®
Condenser	Model	Air / Water Temp Lbs. per 24 hours		Per Cycle		Potable Gal. per 100 lbs.	Condenser Gal. per 100 lbs.	kWh Used per 100 lbs.	Max. Fuse Size or HACR Circuit Breaker	Amperage	Voltage			
		70°/ 50°F	90°/ 70°F	Lbs.	Cubes	90°/ 70°F	90°/ 70°F	90°/ 70°F						
1 Phase	Air-Cooled	KM-1301SAJ	1365	1301	28.6	1440	21.0	N/A	4.27	20A	12.4A	208-230V/60/1	19,400	338 lbs.
	Water-Cooled	KM-1301SWJ	1247	1230	28.5	1440	21.0	89	3.76	20A	8.2A	208-230V/60/1	20,900	335 lbs.
	Remote Air-Cooled	KM-1301SRJ	1400	1260	29.4	1440	14.0	N/A	4.28	20A	13.5A	208-230V/60/1	18,900	339 lbs. ★
3 Phase	Air-Cooled	KM-1301SAJ3	1427	1350	29.9	1440	15.6	N/A	3.95	20A	9.5A	208-230V/60/3	18,400	338 lbs. ★
	Water-Cooled	KM-1301SWJ3	1360	1355	29.3	1440	16.0	95	3.25	20A	6.1A	208-230V/60/3	20,100	335 lbs.
	Remote Air-Cooled	KM-1301SRJ3	1433	1330	28.9	1440	14.0	N/A	3.83	20A	10.7A	208-230V/60/3	18,800	339 lbs. ★

KM Edge Cube Dimensions*



* approximate size in inches, image not to scale

Operating Limits

- Ambient Temp Range 45 - 100°F
- Water Temp Range 45 - 90°F
- Water Pressure 10 - 113 PSIG
- Voltage Range 187 - 253V

Service

- Panels easily removed and all components accessible for service.
- Allow 6" (15cm) clearance at rear, sides, and top for proper air circulation and ease of maintenance/service.

Plumbing

- Icemaker Water Supply Line: Minimum 3/8" Nominal ID Copper Water Tubing or Equivalent
- Icemaker Drain Line: Minimum 3/4" Nominal ID Hard Pipe or Equivalent
- Water-Cooled Model (Lines Must Be Independent of Icemaker)
- Condenser Water Supply Line: Minimum 3/8" Nominal ID Copper Water Tubing or Equivalent
- Condenser Drain/Return Line: Minimum 3/8" Nominal ID Hard Pipe (open drain system) or Copper Water Tubing (closed loop system) or Equivalent




KM-1301S_J(3)

STACKABLE ICE CUBER




KM-3101S_J(3)
07/20/17
Item # 1356


FRONT VIEW



AIR-COOLED




WATER-COOLED




REMOTE AIR-COOLED


SIDE VIEW



AIR-COOLED




WATER-COOLED




REMOTE AIR-COOLED


BACK VIEW



AIR-COOLED




WATER-COOLED




REMOTE AIR-COOLED


BOTTOM VIEW



AIR-COOLED




WATER-COOLED



REMOTE AIR-COOLED

URC-14F Remote Condenser (Sold Separately)
For Use with KM-1301SRJ(3)



Pre-Charged Tubing Kits
(Sold Separately)
20' R404-2068-2
35' R404-3568-2
55' R404-5568-2



Voltage supply for the URC Remote Condenser is supplied from the Ice Maker. No additional circuit is required.