



MetroMax i[®] Drying Rack

- Promotes Air Flow ... "My Health Inspector won't need to write me up!"
- Built in Microban[®] keeps the unit "Cleaner Between Cleanings"
- Mobile or Stationary - Built to take on the toughest environments!



Preconfigured MetroMax i® Drying Racks with One Tray Drying Rack Level and Two Drop-Ins

- Includes two drop-ins (Cat. No. DR48S) and one cutting board/tray drying rack (Cat. No. MTR2448XE).

Stationary Unit

Width		Length		Height		Pkd. Wt.		i
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	
24	610	48	1219	75 ¹ / ₂	1917	130	59	PR48X3

Mobile Unit

Width		Length		Height		Pkd. Wt.		i
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	
24	610	48	1219	69	1752	124	56	PR48VX3

*Note: Includes two 5PCX swivel casters and two 5PCBX swivel casters with brakes.



Preconfigured MetroMax i® Drying Racks with Four Levels of Tray Drying Racks

- Includes four cutting board/tray drying racks

(Two Cat. No. MTR2448XE and two Cat. No. MTR2448XEA)

Stationary Unit

Width		Length		Height		Pkd. Wt.		i
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	
24	610	48	1219	75 ¹ / ₂	1917	142	64	PR48X4

Mobile Unit

Width		Length		Height		Pkd. Wt.		i
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	
24	610	48	1219	69	1752	148	67	PR48VX4

*Note: Includes two 5PCX swivel casters and two 5PCBX swivel casters with brakes.

Cutting Board and Tray Drying Rack

- Rack is mounted to standard MetroMax i® or MetroMax Q® shelf.
- Promotes safe air drying of cutting boards and trays.
- 1¹/₈" (28mm) and 3" (76mm) slide spacing available.

Fits Shelf		Spacing		Height		Tray Capacity	Approx. Pkd. Wt.		i and Q
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)		(lbs.)	(kg)	
24x36	610x914	1 ¹ / ₈	28	6	150	24	13.5	6.1	MTR2436XE
24x48	610x1219	1 ¹ / ₈	28	6	150	34	18.0	8.2	MTR2448XE
24x60	610x1524	1 ¹ / ₈	28	6	150	42	22.5	10.2	MTR2460XE
24x36	610x914	3	76	6	150	10	9.8	4.4	MTR2436XEA
24x48	610x1219	3	76	6	150	14	13	5.9	MTR2448XEA
24x60	610x1524	3	76	6	150	17	16.3	7.4	MTR2460XEA

*Note: Can be retrofitted to original MetroMax and MetroMax Q.

Stainless Steel Drop-in Racks

- Open wire design provides air flow to safely dry pots, pans, and containers
- To create a storage level with a stainless drop-in order the following:
 - Qty. 1 Drop-in rack
 - Qty. 1 Four-sided MetroMax i® frame
 - Qty. 1 MetroMax i® center beam
- Can be retrofitted to existing MetroMax i® shelves. Simply remove the mats and drop in the stainless drying rack.
- Center beams: RPMX36-CBEAM, RPMX48-CBEAM, RPMX60-CBEAM.

Width		Length		Height		Wire Spacing		Approx. Pkd. Wt.		Cat. No.
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	
24	610	33 ⁷ / ₈	854	5 ¹ / ₄	133	3 ³ / ₄	19	9	4.1	DR36S
24	610	45 ⁷ / ₈	1156	5 ¹ / ₄	133	3 ³ / ₄	19	12	5.4	DR48S
24	610	57 ⁷ / ₈	1458	5 ¹ / ₄	133	3 ³ / ₄	19	15	6.8	DR60S

*Note: Can be retrofitted to original MetroMax and MetroMax Q.

Storage Level Frames

- Open four sided frames accommodate stainless drop-in racks.
- Includes corrosion proof MetroMax i® frame and a bag of wedges.

Width		Length		Width/Length		Approx. Pkd. Wt.		i and Q
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	
24	610	36	914	24x32	610x810	11 ¹ / ₄	5.1	M4F2436
24	610	48	1220	24x44	610x1120	15	6.8	M4F2448
24	610	60	1524	24x56	610x1370	18 ³ / ₄	8.5	M4F2460



Inhibits the growth of stain and odor causing bacteria. Microban® does not protect users from food borne illness. Normal cleaning practices should be maintained. Microban is a registered trademark of Microban Products Company.

WWW.METRO.COM

1.800.992.1776

