



# QuietQube® RN-1078C Remote Nugget Ice Machine

## Models

RN-1078C



RN-1078C Remote Nugget Ice Machine - 115V



RCU Condensing Unit - 208-230V



RN-1078C Remote Nugget Ice Machine on B-570 Bin



RN-1078C Remote Nugget Ice Machine on Servend SV-250 Dispenser

### Standard Features

QuietQube® Series Remote System consists of a remote condensing unit, interconnecting refrigerant lines, ice machine head section, ice deflector, and ice storage unit- whether storage bin, countertop or floor-standing dispenser. All ordered separately. QuietQube ice machine with RCU condensing unit is designed as a Manitowoc system and not for use with any other ice machine or remote condenser brand.

- Up to 880 lbs. (399 kgs) daily ice production.
- Only 22" (55.88 cm) wide.
- Perfect for beverage applications, dispensing and cold therapy.
- Evaporator is designed for maximum quality and operating life.
- 90% ice to water ratio and longer pieces makes tubular nugget ideal for dispensing without congealing.
- Quiet operation eliminates most noise from the refrigeration system. Promotes a relaxing atmosphere.
- Ice machine is lighter in weight and 115 volt simplifies installation.
- Stainless steel exterior has a clean and modern look to enhance the display in any self-serve environment.



# Ice Shape

- Tubular Nugget Ice provides a softer, chewable texture while still providing maximum cooling effect.
- 5/8" (1.59 cm) diameter cylindricalshaped nugget with average length of approximately 1" (2.54 cm).














#### RN-1078C Ice Machine



Shipping Weight: 185 lbs. / 84 kgs.

- (A) 3/8" F.P.T. Ice Making Water Inlet
- **B** Refrigerant Lines
- © Electrical Entrance
- (D) 3/4" M.P.T. Drain Fitting

Dispenser Note - Verify with the dispenser manufacturer that the correct agitator and deflector kit for nugget ice dispensing is included with your dispenser purchase.

# Ice Machine Electric

115/60/1 ice machines are factory pre-wired with a 7' (2m) power cord and NEMA 5-15 right angle plug configuration.

Total Amps: 6.0

Max. fuse size: 15 amps
The ice machine and
condensing unit are powered
independently of each other.


# Specifications

Refrigerant: R404A

#### **Operating Limits:**

- Ambient Temperature Range: 50°-100°F (14.4°-37.8°C)
- Water Temperature Range: 45°-90°F (7.2°-32.2°C)
- Water Pressure Ice Maker Water In:
   Min. 20 psi (137.9 kPA)
   Max. 70 psi (483 kPA)

#### RCU-1075 Condensing Unit



# Condensing Unit Electric

**208-230/60/1 standard.** 208-230/60/3 also available. **Note:** QuietQube ice machine is wired independent of condensing unit.

 Min. circuit ampacity:
 15 1ph
 15 3ph

 Max. fuse size:
 15 1ph
 15 3ph

BTU Per Hour: 7,680 (average)
Compressor: Nominal rating: 1-1/2 HP

#### **Operating Limits:**

**Ambient Temperature Range:** 

-20° to 120°F (-29° to 49°C)

#### **Installation Information and Dimensions:**

Maximum Line Length—100' (30.5 m)\*
Maximum Vertical Rise\*—35' (10.7 m) above ice machine.

Maximum Vertical Drop—15' (4.5 m) below ice machine.

\*A rise over 20' (6 m) requires S-Trap Kit K-00172 - ordered separately



# Standard Interconnecting Tubing

	Line Length		Weight	
Model	ft.	m.	lbs.	kgs
RC-21	20	6	12	5
RC-31	30	9	20	9
RC-51	50	15	28	13

### Remote Air-cooled Ice Machine

		Ice Production 24 Hours		Power Usage	Potable Water
Model	Ice Shape	70°Air/ 50°F Water 21°Air/10°C Water	90°Air/ 70°F Water 32°Air/21°C Water	90°Air/ 70°F Water 32°Air/21°C Water	Usage/ 100 lbs. 45.4 kgs. of Ice
RN-1078C	Nugget	880 lbs.	713 lbs.	5.44	13.6 Gal.
		399 kgs	323 kgs		52 L

Order ice storage bin separately. Will not accept AuCS accessory.

2110 South 26th Street
PO Box 1720
Manitowoc, WI 54221-1720 USA

Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com

