

S9736

14T8/LED/48-840/DR 14 watt T8 LED; Medium bi-pin base; 4000K; 50000 average rated hours; 1800 lumens

Features

- Direct Replacement for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Ballast required
- Solid State LED lighting
- High efficacy

- Long lifeDLC Qualified5 year Limited warranty
- Dimmable*
- Compatible with emergency ballasts*
- All glass tube

*May not be compatible with all rapid start, dimmable, and emergency ballasts.

View: Ballast Compatibility Chart



S9736

| Item Number | | UPC Watts | | Fluorescent Equivalent | | Power Fa | ctor Lamp Shape | Base | ANSI Base |
|--------------------|-----------------------------------|-----------|-----------------|------------------------|----------------|------------------------|------------------------|---------------------------------|------------|
| S9736 0459 | | 9230973 | 62 14 | 25W-32W | | 0.90 T8 | | Medium BiPin | G13 |
| Lamp Code | | Finis | h MOL In Inches | MOD In Inches | Initial Lumens | | Average Rated Hours | Kelvin Temp | Color |
| 14T8/LED/48-840/DR | | Whit | e 48" | 1.00" | 1800 | | 50000 | 4000 | Cool White |
| CRI | Beam Spread Pack Package Type Deg | | DLC ID: | RoHS Compliant | | nt UL or ETL Listed | UL Classification | | |
| 82 | 230 | 10 | Вох | PNN6T7FB DLC Search | Yes | | Yes | cETLus - Damp Location Rated | |
| Warranty | | | | | | | | | |





Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051