

NOR-LAKE, INCORPORATED
727 Second Street
Hudson, Wisconsin 54016

800-955-5253
715-386-2323
866-961-5253 Parts
800-388-5253 Service
715-386-4291 FAX
www.norlake.com



ADVANTEDGE™ SLIDE GLASS DOOR REFRIGERATOR MERCHANDISERS



NLGRP48-SL

NLGRP74-SL

PROJECT:

ITEM NUMBER:

MODEL NUMBER:

SLIDE GLASS DOOR MERCHANDISERS

SPECIFICATIONS FOR: NLGRP48-SL, NLGRP74-SL

- **Finish:** 24 gauge painted textured galvanized steel interior and exterior. Black or white exterior finish. Standard white interior finish with stainless steel floor
- **Insulation:** 1-3/4" thick state-of-the-art, foamed-in-place "zero ODP" polyurethane insulation
- **Hardware:** Interior LED lighting with switch, interior hanging thermometer, top backlit graphic panel (standard panel is blank without graphics), adjustable legs for leveling, four adjustable heavy-duty epoxy coated shelves per door - adjustable in 1/2" increments on pilasters
- **Doors:** Auto-close, triple pane, safety glass doors, contemporary style black door frame with anti-microbial handles. On NLGRP74 models, left door slides to middle, middle and right door slide to left.
- **Electrical:** 115 volt, 60 Hz, 1 phase with cord and plug
- **Refrigeration** Self-contained bottom mount refrigeration system designed for optimum energy efficiency and low noise. Top mounted, low profile interior evaporator housing for increased storage space, energy-free condensate removal. Refrigeration system is accessible for ease of service and regular preventative maintenance. Refrigerant: R-134a. Temperature range: +34° to +41°F. Electronic temperature control.
- **Approvals:** UL/C-UL Safety, UL Sanitation, and NRCan listed **

STANDARD FEATURES

- 24 gauge painted textured galvanized steel interior and exterior
- 2-1/2" adjustable legs for leveling
- Anti-microbial finish on door handles
- Auto-close, triple pane, safety glass doors
- Contemporary style black door frame
- Energy-free condensate removal
- Four adjustable heavy-duty epoxy coated shelves per door
- Interior hanging thermometer
- Interior LED lighting with light switch
- Refrigerant: R-134a
- Self-contained bottom mount refrigeration system
- Top backlit graphic panel (standard panel is blank without graphics)
- Temperature range: +34° to +41°F
- Top mounted, low profile interior evaporator housing for increased storage space
- White interior finish with stainless steel floor
- Warranties: 3 year parts and labor, 5 year compressor
- Approvals: UL/C-UL Safety, UL Sanitation, and NRCan

OPTIONAL FEATURES*

- Additional shelving
- Black or white exterior finish
- Casters
- Graphic sign panels
- Price tag molding for shelving



Nor-Lake, Inc.
Registered to ISO 9001:2008
File No. 10001816

* Most options are available two weeks from receipt of order. Please contact us for specific questions.

** C-UL is Underwriters Laboratories Safety Certification Mark which indicates that UL has tested the equipment to applicable CSA Standards.

** UL Sanitation is Underwriters Laboratories Sanitation Mark which indicates that UL has tested the equipment to applicable NSF Standards.

