

Sammic



FOOD PRESERVATION AND SOUS-

VACUUM PACKING MACHINES - S RANGE



Vacuum Sealer SV-410S TABLE TOP UNIT. 350 CF/H. 16" SEALING BAR. • 16" sealing bar • Sensor-controlled vacuum.		TECHNICAL SPECIFICATIONS Pump capacity: 350 cf/h Useful length of the sealing bar: 16 " Total loading: 0.50 Hp Vacuum pressure (maximum): 2 mbar Internal dimensions -Width: 17 " ·Depth: 16 " ·Height: 6 "			
			Deep-drawn chamber.		External dimensions (WxDxH)
			 Improves the durability of cooked or raw food, with no loss of weight. All functions are controlled by a microprocessor, which allows control of the exact desired vacuum percentage in the chamber. Vacuum PLUS: allows to program an extra vacuum time once 99% vacuum has been reached. Easy to program. 10-program-memory. Stainless steel body. Stainless steel deep-drawn chamber. Cordless sealing bar. Softair as standard. Digital keyboard. LED's indicate each cycle stage whilst performing. STOP key allows the interruption of the cycle at any stage, moving on to the next step. Pump drying program: improves the durability of the machine. 		·Width: 20 " ·Depth: 20 " ·Height: 16 " Net weight: 141 lbs.
DEFAULT EQUIPMENT Filling plate.	OPTIONAL EQUIPMENT · Vac-Norm external vacuum kit. · Bag cutting kit. · Liquid insert plate set. · Vacuum sealing bags.				
		_			