

WATER FILTRATION SYSTEM

FEATURES

- Includes wall mounting bracket
- Locking assembly allows for quick changing of cartridges
- Phosphate for preventing scale build-up
- Activated carbon filtration makes water taste great and protects equipment from corrosive chlorine
- Gradient density depth filtration reduces dirt, rust, and other debris as small as 1 micron

TECHNICAL DATA

Capacity	18,000 Gal (68,137 Ltr)
Maximum Flow Rate	1.67 GPM (6.32 LPM)
Micron Rating	1
Inlet/Outlet Connection	3/8"
Replacement Cartridge	#790OCLOCARTL
Maximum Pressure	125 PSI (8.6 bar)
Maximum Temperature	100°F (38°C)

INSTALLATION & OPERATION TIPS

- Choose a mounting location suitable to support the full weight of the system
- Install vertically so cartridge hangs down
- Connect inlet side of the system to a cold water line. Do not connect to a hot water line
- Flush the filter cartridge at the time of installation and every cartridge change
- Cartridge should be replaced every 6 months
- Allow 3" clearance below system for cartridge replacement

APPLICATIONS

- Large ice machines with production capacity greater than 500 lb./day
- Large beverage and coffee equipment
- Floor steam equipment



WARNING

Cancer and reproductive harm
www.P65Warnings.ca.gov

These systems are for food service applications only, NOT for use in residential applications. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

