

WATER FILTRATION SYSTEM

FEATURES

- Includes wall mounting bracket
- Locking assembly allows for quick changing of cartridges
- Phosphate for preventing scale build-up
- Activated carbon filtration makes water taste great and protects equipment from corrosive chlorine
- Gradient density depth filtration reduces dirt, rust, and other debris as small as 1 micron

TECHNICAL DATA

| | |
|-------------------------|------------------------|
| Capacity | 6,000 Gal (22,712 Ltr) |
| Maximum Flow Rate | 0.75 GPM (2.84 LPM) |
| Micron Rating | 1 |
| Inlet/Outlet Connection | 3/8" |
| Replacement Cartridge | #790OCLOCARTS |
| Maximum Pressure | 125 PSI (6.8 bar) |
| Maximum Temperature | 100°F (38°C) |

INSTALLATION & OPERATION TIPS

- Choose a mounting location suitable to support the full weight of the system
- Install vertically so cartridge hangs down
- Connect inlet side of the system to a cold water line. Do not connect to a hot water line
- Flush the filter cartridge at the time of installation and every cartridge change
- Filter cartridge must be replaced every 3-6 months, or at the rated capacity, or if a noticeable reduction in flow rate occurs
- Allow 3" clearance below system for cartridge replacement

APPLICATIONS

- Small ice machines with production capacity up to 125 lb./day



WARNING

Cancer and reproductive harm
www.P65Warnings.ca.gov

These systems are for food service applications only, NOT for use in residential applications. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.