Spec.

AΙΑ


Roll-in Cooler Rack

Extreme Duty®



Rugged Design For Heavy-Duty Applications

- All welded stainless steel construction.
- Resists corrosion in high moisture refrigerated environments.
- High strength heliarc welded ledges.
- Rolls easily across all surfaces on 5" plate casters.
- · No pry points.
- Convenient 1-1/4" wide angle ledges. Spacing between ledges is 3".
- Easy to clean and sanitize, simply wipe down or steam clean.




High strength heliarc welded ledges.





Roll-in Cooler Rack

Extreme Duty®









AutoCAD drawings available through KCL CADalog

Specifications

Unit shall be of welded stainless steel construction, and shall have a total carrying capacity of 1000 pounds, evenly distributed. Unit shall accept 20 each 18" x 26" (one per ledge) or 40 each 14" x 18" (two per ledge) trays. Upright legs shall be of .120 x 1" x 1" angle material. Tray ledges shall be 1-1/4" (32) wide of 16-gauge angle material. Ledges shall be spaced at 3", and shall be continuously arc welded to upright legs at all points. Side panels shall have a center mounted vertical reinforcement of .104 angle stainless steel material, continuously arc welded to each tray ledge. Bottom cross member channels shall be 4" wide 18-gauge stainless steel with an additional 18-gauge stainless steel reinforcement. Casters shall be heavy-duty all swivel plate type, and shall be bolted to cross member channels with security hardware. Casters shall have 5" wheel with non-marking polyurethane tread.

Dimensions

	Model	Fits Coolers	Pan Capacity Full Half		Ledge Description Type Spacing Wid		tion Width	Overall Size W D H		Case Weight Lbs. (Kg)		
•	8900	Foster, Traulsen, Tyler (high Type)	20 ea.	40 ea.	Angle	3" (76)	1-1/4" (32)	20-13/16" (529)	26-1/2" (673)	67-7/8" (1724)	119	(53.9)

 $\label{lem:measurements} \mbox{Measurements in () denote metric millimeters, unless otherwise specified.}$



Lakeside Manufacturing, Inc.

4900 West Electric Avenue • West Milwaukee, WI 53219 U.S.A. 800-558-8565 • 414-902-6400 • Fax 414-902-6446 • www.eLakeside.com

Lit# 0607 EDRCR