HEATED HOLDING



VHU SERIES INSULATED HUMIDIFIED CABINETS



Model VHU18 Shown





UL Listed. UL Listed to Canadian safety standards. Classified by UL to NSF Standard #4.

SPECIFICATIONS

Vulcan Model No. VHU insulated heated cabinets automatically set the humidity when you set the temperature. Blower motor for even temperature distribution. Simple knob actuated electronic control with top mounted digital display for holding at temperatures up to 200°F. Field reversible glass door standard. Adjustable racking (universal tray slides) will hold 18" x 26" or 12" x 20" pans or a combination of both on 1½" centers. Cabinet interior and exterior are constructed out of 20 gauge stainless steel. Recessed side-mounted handles, magnetic action door latch, and full insulation; 2" in side walls, bottom and top. 1500 watts, 120 volt, 12.5 amps element with rear mounted cord and NEMA 5-15 plug. Complete with 5" heavy duty casters (2 swivel with brakes and 2 rigid). One year limited parts and labor warranty. After the first year, lifetime parts warranty on the heating elements.

□ VHU7	(see reverse for capacities)
□ VHU18	(see reverse for capacities)
□ VHU77	(see reverse for capacities)

STANDARD FEATURES

- Holding Capability:
 - 18" x 26" sheet pans.
 - 12" x 20" pans.
 - · Other pans and containers on shelves.
- Set the temperature and the humidity level automatically adjusts for you.
- Simple knob actuated electronic control with top mounted digital display for holding at temperatures of up to 200°F.
- Blower motor for even temperature distribution.
- Full sized glass door.
- 5" heavy duty casters (2 swivel with brakes and 2 rigid).
- Recessed side mounted handles.
- Universal tray slides adjustable on 1½" centers.
- Interior and the exterior are both constructed out of 20 gauge stainless steel.
- Fully insulated with 2" in side walls, bottom and top.
- Integrated steel frame for maximum strength.
- Magnetic action door latch.
- Field reversible doors.
- Rear mounted cord.
- 1500 watt, 120 volts element with NEMA 5-15 cord and plug.
- One year limited parts and labor warranty. After the first year, lifetime parts warranty on the heating elements.


$\hat{}$	D	_	^		\sim
	_		C D	N	•

2000 watts, 120 volts, 16.7 amps element with NEMA 5-20 plug
Solid door
Additional tray slides
Travel latch
3" high casters
Stacking kit





VHU SERIES INSULATED HUMIDIFIED CABINETS



	DIMENSIONS	CAPACITY***		ELECTRICAL			SHIPPING WEIGHTS	
MODEL	EXTERIOR	12" x 20" x 2½" PANS	18" x 26" SHEET PANS	VOLTS	WATTS	AMPS	LBS	KG
VHU7	26¾" W x 31¼" D x 39¾" H	14	7	120	1,500	12.5	200	90
VHU18	26¾" W x 31¼" D x 74½" H	36	18	120	1,500	12.5	300	136
VHU77**	26¾" W x 31¼" D x 73½" H	14 x 2	7 x 2	120	1,500	12.5	300	136
Different capacities, heights, and heating element powers available upon request.								

^{**}For stacked units, each compartment will have its own cord and plug. Electrical rating is for each compartment.



a division of ITW Food Equipment Group LLC

P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602



^{***} Capacity based on 3" spacing between each pan.