#### STAINLESS STEEL

# HAND SINKS SPACE SAVER UNITS







7-PS-23

#### WITH SOAP & TOWEL DISPENSERS







7-PS-73

| Item #:\_\_\_\_\_ Qty #: \_\_\_\_\_ | Model #: \_\_\_\_\_ | Project #: \_\_\_\_\_



Keyhole Bracket for easier installation and greater stability.

#### **FEATURES:**

One piece Deep Drawn sink bowl design.

Sink bowl is 9" x 9" x 5".

All sink bowls have a large liberal radii with a minimum dimension of 1" and are square in design.

Keyhole wall mount bracket.

2" stainless steel drain with strainer plate.

#### **Specific Features:**

**7-PS-22** and **7-PS-83** 4" O.C. centerset faucet furnished with aerator.

**7-PS-83** and **7-PS-84** 4" O.C. splash mounted gooseneck faucet furnished with aerator. liquid soap & towel dispenser with hinged towel box. Unit uses standard C-fold towels.

**7-PS-73** " O.C. splash mounted gooseneck faucet furnished with aerator. liquid soap & towel dispenser with hinged towel box. Unit uses standard C-fold towels. 7 3/4" high Side Splashes (from top of deck).

#### **CONSTRUCTION:**

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.

Die formed Countertop Edge with a No-Drip offset.

One sheet of stainless steel - No Seams.

#### **MATERIAL:**

Heavy gauge type 304 series stainless steel.

Wall mounting bracket is stainless steel and of offset design.

All fittings are brass / chrome plated unless otherwise indicated.

#### **MECHANICAL:**

Faucet supply is 1/2" IPS male thread hot and cold. Drains are 1-1/2" IPS.

### Standard Faucet conforms to NSF 61 Standard 9. Faucets Are AB1953 Lead Free Compliant.

For Replacement Faucets & Upgrades, Drains & Accessories visit our website at www.advancetabco.com



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:
Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

## **DIMENSIONS and SPECIFICATIONS**

TOL Overall: ± .500" Interior: ± .250"

FITTINGS SUPPLIED AS SHOWN

**ALL DIMENSIONS ARE TYPICAL** 



