

## Camshelving® Elements Series

### Single Shelf Kits for Mobile Units Shelf Plates with Camguard® antimicrobial

#### 3 Shelf Widths

18" (460 mm), 21" (540 mm), 24" (610 mm)



#### 5 Shelf Lengths

36" (910 mm), 42" (1070 mm), 48" (1220 mm),  
54" (1380 mm), 60" (1530 mm)



#### • Mobile Shelf Kit includes:

Two Mobile Traverses, 8 Mobile Dovetails (4 ea. A & B),  
Vented or Solid Shelf Plates to complete one shelf.

### Features & Benefits

#### Strong Technology

Mobile Traverses are built using advanced manufacturing technology and the use of a non-corrosive composite material. The robust design along with unique composite material gives Elements an unprecedented longevity, durability and weight-bearing capacity in the industry. Shelves up to 60" (1530 mm) long hold up to 900 lbs. per unit of evenly distributed static weight. Mobile traverse features a 45° gusset for maximum cross stabilization.

#### Hygienic Design

Camshelving Shelf Plates contain Camguard® antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing.

#### Shelving for Life

Non-corrosive design will endure all areas of operation, dry-storage, coolers, warewashing, freezer and heavy condensation and humidity settings without risk of rusting, peeling, denting, cracking or warping. Functions in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C).

#### Requires minimal assembly

Can be put together with the use of a rubber mallet. Two-piece Mobile Dovetails secure Mobile Traverses so they can be set easily into place.

#### Flexible Design

Shelves can be easily adjusted at 4" (102 mm) increments. Add a shelf to an existing unit by simply ordering the appropriate Mobile Shelf Kit.

#### Optional Accessories

Identification Tags clip easily onto traverses.  
Divider bars to create a custom storage unit.

Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_



Mobile Four Shelf Unit with Vented Shelf Plates.



Vented Shelf Kit includes two Traverses and Vented Shelf Set for one shelf.



Solid Shelf Kit includes two Traverses and Solid Shelf Set for one shelf.

### Approvals



Components

# Camshelving® Elements Series

## Single Shelf Kits for Mobile Units Shelf Plates with Camguard® antimicrobial

### 3 Shelf Widths

18" (460 mm), 21" (540 mm), 24" (610 mm)



### 5 Shelf Lengths

36" (910 mm), 42" (1070 mm), 48" (1220 mm),  
54" (1380 mm), 60" (1530 mm)



### • Mobile Shelf Kit includes:

Two Mobile Traverses, 8 Mobile Dovetails (4 ea. A & B),  
Vented or Solid Shelf Plates to complete one shelf.

### Mobile – Shelf Kits with Solid Shelf Plates

CODE	WIDTH IN. MM	LENGTH IN. MM	CASE LBS. (CUBE)	CASE KG. (CUBE M)
<b>36" (910 mm) Traverses</b>				
EMSK1836S	18" 460 mm	36" 910 mm	9.69 (1.51)	4,40 (0,04)
EMSK2136S	21" 540 mm	36" 910 mm	11.11 (1.51)	5,04 (0,04)
EMSK2436S	24" 610 mm	36" 910 mm	11.87 (1.51)	5,38 (0,04)
<b>42" (1070 mm) Traverses</b>				
EMSK1842S	18" 460 mm	42" 1070 mm	11.55 (2.03)	5,24 (0,06)
EMSK2142S	21" 540 mm	42" 1070 mm	13.08 (2.03)	5,93 (0,06)
EMSK2442S	24" 610 mm	42" 1070 mm	13.96 (2.03)	6,33 (0,06)
<b>48" (1220 mm) Traverses</b>				
EMSK1848S	18" 460 mm	48" 1220 mm	12.25 (1.54)	5,55 (0,04)
EMSK2148S	21" 540 mm	48" 1220 mm	14.16 (1.54)	6,42 (0,04)
EMSK2448S	24" 610 mm	48" 1220 mm	15.36 (1.54)	6,97 (0,04)
<b>54" (1380 mm) Traverses</b>				
EMSK1854S	18" 460 mm	54" 1380 mm	13.99 (2.63)	6,35 (0,07)
EMSK2154S	21" 540 mm	54" 1380 mm	16.01 (2.63)	7,26 (0,07)
EMSK2454S	24" 610 mm	54" 1380 mm	17.34 (2.63)	7,86 (0,07)
<b>60" (1530 mm) Traverses</b>				
EMSK1860S	18" 460 mm	60" 1530 mm	15.85 (2.91)	7,12 (0,08)
EMSK2160S	21" 540 mm	60" 1530 mm	17.98 (2.91)	8,16 (0,08)
EMSK2460S	24" 610 mm	60" 1530 mm	19.43 (2.91)	8,81 (0,08)

Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_

### Mobile – Shelf Kits with Vented Shelf Plates

CODE	WIDTH IN. MM	LENGTH IN. MM	CASE LBS. (CUBE)	CASE KG. (CUBE M)
<b>36" (910 mm) Traverses</b>				
EMSK1836V	18" 460 mm	36" 910 mm	9.22 (1.51)	4,18 (0,04)
EMSK2136V	21" 540 mm	36" 910 mm	10.20 (1.51)	4,63 (0,04)
EMSK2436V	24" 610 mm	36" 910 mm	11.02 (1.51)	4,99 (0,04)
<b>42" (1070 mm) Traverses</b>				
EMSK1842V	18" 460 mm	42" 1070 mm	10.93 (2.03)	4,96 (0,06)
EMSK2142V	21" 540 mm	42" 1070 mm	12.10 (2.03)	5,49 (0,06)
EMSK2442V	24" 610 mm	42" 1070 mm	13.05 (2.03)	5,92 (0,06)
<b>48" (1220 mm) Traverses</b>				
EMSK1848V	18" 460 mm	48" 1220 mm	11.59 (1.54)	5,26 (0,04)
EMSK2148V	21" 540 mm	48" 1220 mm	12.93 (1.54)	5,86 (0,04)
EMSK2448V	24" 610 mm	48" 1220 mm	14.21 (1.54)	6,45 (0,04)
<b>54" (1380 mm) Traverses</b>				
EMSK1854V	18" 460 mm	54" 1380 mm	13.18 (2.63)	5,97 (0,07)
EMSK2154V	21" 540 mm	54" 1380 mm	14.71 (2.63)	6,67 (0,07)
EMSK2454V	24" 610 mm	54" 1380 mm	16.12 (2.63)	7,31 (0,07)
<b>60" (1530 mm) Traverses</b>				
EMSK1860V	18" 460 mm	60" 1530 mm	14.89 (2.91)	6,75 (0,08)
EMSK2160V	21" 540 mm	60" 1530 mm	16.61 (2.91)	7,53 (0,08)
EMSK2460V	24" 610 mm	60" 1530 mm	18.15 (2.91)	8,23 (0,08)

### Architect Specs

<b>Posts:</b>	Proprietary non-corrosive composite material.
<b>Post Connectors:</b>	Glass Filled Polypropylene.
<b>Mobile Traverses:</b>	Proprietary non-corrosive composite material.
<b>Vented/Solid Shelf Plates:</b>	Reinforced polypropylene with Camguard® antimicrobial.
<b>Divider Bars:</b>	Glass Filled Nylon.
<b>Mobile Dovetails:</b>	Resin Nylon
<b>Wedges:</b>	Resin Polypropylene

### Optional Accessories

<b>Identification Tag 6"</b>	<input type="checkbox"/> CSID	<b>Color:</b> White/Clear	<b>Case pack:</b> 12 each
<b>Identification Tag 3"</b>	<input type="checkbox"/> CSID3	<b>Color:</b> White/Clear	<b>Case pack:</b> 12 each
<b>Divider Bar Angled</b>	<input type="checkbox"/> EDDBA	<b>Color:</b> Speckled Gray	<b>Case pack:</b> 4 each
<b>Divider Bar Straight</b>	<input type="checkbox"/> EDDBS	<b>Color:</b> Speckled Gray	<b>Case pack:</b> 4 each

### Standard Color

Brushed Graphite (580)

### Approvals



Components



© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, CA 92647-2056, U.S.A.  
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003