

Item No. _____

Quantity _____

Job Name _____

Spec No. _____



401A
Front Load



411A
Side Load



401S
Front Load

BUN PAN RACKS

FULL SIZE ALL WELDED
ALUMINUM OR STAINLESS CONSTRUCTION

Custom Sizes Available

| ALUMINUM | | STAINLESS | | Spacing/Capacity | H | W | D |
|----------|-----|-----------|-----|------------------|------|------|-----|
| Model | Wt. | Model | Wt. | | | | |
| 400A | 45 | 400S | 75 | FL 2" / 30 Pans | 70¼" | 20½" | 26" |
| 401A | 36 | 401S | 57 | FL 3" / 20 Pans | 70¼" | 20½" | 26" |
| 402A | 32 | 402S | 47 | FL 4" / 15 Pans | 70¼" | 20½" | 26" |
| 403A | 30 | 403S | 41 | FL 5" / 12 Pans | 70¼" | 20½" | 26" |
| 404A | 28 | 404S | 35 | FL 6" / 10 Pans | 70¼" | 20½" | 26" |
| 405A | 43 | 405S | 70 | FL 2" / 27 Pans | 64" | 20½" | 26" |
| 406A | 35 | 406S | 53 | FL 3" / 18 Pans | 64" | 20½" | 26" |
| 410A | 43 | 410S | 70 | SL 2" / 30 Pans | 70¼" | 28½" | 18" |
| 411A | 33 | 411S | 55 | SL 3" / 20 Pans | 70¼" | 28½" | 18" |
| 412A | 30 | 412S | 44 | SL 4" / 15 Pans | 70¼" | 28½" | 18" |
| 413A | 28 | 413S | 38 | SL 5" / 12 Pans | 70¼" | 28½" | 18" |
| 414A | 26 | 414S | 33 | SL 6" / 10 Pans | 70¼" | 28½" | 18" |
| 415A | 40 | 415S | 65 | SL 2" / 27 Pans | 64" | 28½" | 18" |
| 416A | 35 | 416S | 50 | SL 3" / 18 Pans | 64" | 28½" | 18" |

Options:

- /011 Caster Brakes
- /052 5" X 2" Caster Upgrade
- /5B HD Caster Brakes
- /CC Card Clip Aluminum
- /022 Corner Bumpers (2)
- /024 Corner Bumpers (4)
- /PB Perimeter Bumper
- /VB Vertical Bumper
- /009 Pan Stop Aluminum
- /010 Pan Stop Stainless
- /PG Pan Stop Gravity
- /015 Pan Stop Web-Strap
- /BA Solid Bottom Aluminum
- /A Solid Top Aluminum

APPLICATIONS: Mobile multi-purpose racks for holding, storing and transporting both plastic and aluminum. 18" X 26" Bun Pans, 18" X 13" Pans, and 17" X 25" Fryer Screens.

CONSTRUCTION: Aluminum: Heavy duty, high tensile extruded aluminum. Type 6063-T5 alloy. Lifetime guarantee against rust and corrosion. **Stainless:** 18 Gauge, 304 Series stainless steel.

TRAY SLIDES: Slides are 1" X 1-1/2" extruded aluminum angle heli-arc welded to frame. Bottom load ledge design.

FRAME AND CROSS SUPPORTS: Vertical and horizontal frame sections are 1" extruded aluminum tubing and 1" solid flat bar extruded aluminum or stainless.

CASTERS: Standard 5" full swivel non-marking casters. Casters are securely bolted to frame to facilitate replacements.



Notes

55 Channel Drive • Port Washington, NY 11050-2216
 8891 NW 102nd Street • Medley, FL 33178
 Tel: 516-944-6271 • Fax: 516-944-0625
 Toll Free: 866-712-7283
 www.channelmfg.com • Email: sales@channelmfg.com