Continental Refrigerator

EXTRA WIDE DISPLAY REFRIGERATORS

Operating with Environmentally Safe, CFC-free R-134a Refrigerant

1RE-GD

2RE-GD

3RE-GD

Standard Features

- Modern, State-of-the-Art Styling
- Performance Rated Refrigeration System Utilizing Environmentally Safe R-134a Refrigerant
- 3" Non-CFC Polyurethane Foam Insulation
- Cam-Action Lift-Off Hinges
- Self-Closing Doors
- Magnetic Snap-In Door Gasket
- Cylinder Lock in Each Door
- Automatic Electric Condensate Evaporator
- 5" Casters
- Heavy-Duty, Epoxy-Coated Steel Shelves
- External Dial Thermometer
- Double-Pane, Tempered Hinged Glass Doors
- Fluorescent Interior lighting

Standard (S/S Front, Aluminum End Panels & Interior)
Suffix SA (S/S Exterior, Aluminum Interior)
Suffix SS (S/S Exterior & Interior)

Optional Features & Accessories

- Legs
- Stainless Steel Case Back
- Pan Slide Assemblies
- Increased Refrigeration Systems
- Stainless Steel Shelves
- Digital Thermometer
- Rehinging of Doors
- Half Door
- Remote
- Pass-Thru
- Shallow Depth

SPECIFICATIONS	MODEL 1RE-GD Reach-In Pass-Thru		MODEL 1RX-GD Reach-In Pass-Thru		MODEL 2RE-GD Reach-In Pass-Thru		MODEL 3RE-GD Reach-In Pass-Thru	
DIMENSIONAL DATA								
Net Capacity (cu. ft.)	21	21	30	30	50	50	73	73
Width, Overall (in.)	28 1/2	28 1/2	36 1/4	36 1/4	57	57	85 1/2	85 1/2
Depth, Overall (Incl. Hdls.) (in.)	35 1/2	39	35 1/2	39	35 1/2	39	35 1/2	39
Depth (Less Door(s) (in.)	32	32	32	32	32	32	32	32
Depth (Doors(s) Open 90°) (in.)	58	84	66	100	58	84	58	84
Clear Door Width (in.)	21 7/8	21 7/8	29 5/8	29 5/8	21 7/8	21 7/8	21 7/8	21 7/8
Clear Full-Door Height (in.)	58 5/8	58 5/8	58 5/8	58 5/8	58 5/8	58 5/8	58 5/8	58 5/8
Clear Half-Door Height (in.)	27 1/2	27 1/2	27 1/2	27 1/2	27 1/2	27 1/2	27 1/2	27 1/2
Height, Overall (Inc. 5" Casters)(in.)	82 1/4	82 1/4	82 1/4	82 1/4	82 1/4	82 1/4	85 3/4	85 3/4
No. of Full Door(s)	1	2	1	2	2	4	3	6
No. of Half Door(s)	2	4	2	4	4	8	6	12
Shelves	4	4	4	4	8	8	12	12
Shelf Area (sq. ft.)	20.4	20.4	24.4	24.4	40.8	40.8	61.2	61.2
Tray Slide Capacity (Half)	12 ea.	12 ea.	12 ea.	12 ea.	12 ea.	12 ea.	12 ea.	12 ea.
Tray Slide Capacity (Full)	24 ea.	24 ea.	24 ea.	24 ea.	24 ea.	24 ea.	24 ea.	24 ea.
REFRIGERATION DATA								
Condensing Unit Size (H.P.)	1/3	1/3	1/3	1/3	1/2	1/2	3/4	3/4
Capacity (BTU/Hr)*	2560	2560	2810	2810	4010	4010	5930	5930
ELECTRICAL DATA								
Cabinet Specifications	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115/208-230/60/1	115/208-230/60/1
Feed Wires (Incl. Ground)	3	3	3	3	3	3	4	4
Condensing Unit Specs.	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	208-230/60/1	208-230/60/1
Total Amperes	10.7	11.0	11.0	11.3	13.6	16.0	12.4	15.9
Cabinet Amperes	3.5	3.8	3.8	4.1	4.1	6.5	5.4	8.9
Defrost Amperes	-	-	-	-	-	-	-	-
Power Supply Cord	yes	yes	yes	yes	yes	yes	no	no
SHIPPING DATA								
Height – crated (in.)	83	83	83	83	83	83	85 1/2	85 1/2
Width – crated (in.)	31 5/8	31 5/8	42	42	64	64	90	90
Depth – crated (in.)	42	42	42	42	42	42	42	42
Volume – crated (cu.ft.)	63	63	84	84	129	129	187	187
Weight Std – crated (lbs.)	315	360	430	435	530	610	740	855
Weight SS – crated (lbs.)	375	420	490	495	610	680	855	970
Weight Std – uncrated (lbs.)	215	250	330	335	360	430	530	635
Weight SS – uncrated (lbs.)	275	310	390	395	440	510	645	750

* Rating @ +25°F Evaporator, 90° Ambient

Note: All specifications subject to change without notice.
Note: If the cabinet is located directly against wall and/or under low ceiling, a minimum clearance of 12" is required.



SIDE VIEW



1RE-GD FRONT VIEW



1RX-GD FRONT VIEW



2RE-GD FRONT VIEW



3RE-GD FRONT VIEW

Continental Refrigerator

A Division of National Refrigeration & A/C Products, Inc.
539 Dunksferry Road Bensalem, PA 19020
(800) 523-7138 Fax: (215) 244-9579
www.continentalrefrigerator.com