SANDWICH UNIT REFRIGERATOR

Model: SW48-8C-FB

48" Cutting Top Sandwich Unit Refrigerator with Solid Doors - 8 Pans Front Breathing

Stainless steel front and top, aluminum end panels, case back and interior. Certified under NSF-7 to maintain temperatures in 86°F ambient and designed to maintain NSF-7 temperatures in 100°F ambient.



Options and Accessories

(upcharge and lead times may apply)

Stainless steel exterior and interior - SS models	Drawers in lieu of doors
Stainless steel end panels - SA models	Stainless steel shelves
Glass doors in lieu of solid doors - GD models	Expansion valve system
Stainless steel finished back in lieu of aluminum	Rear-mounted cutting board
Overshelves (single or double)	Flat insulated night cover
Additional epoxy-coated steel shelves	Remote models
Automatic, electric condensate evaporator	Door locks

Consult factory for other model configurations, options and accessories

Project Name:

Model Specified:

Location:

AIA #: SIS #:

Quantity:

Standard Model Features

REFRIGERATION SYSTEM

Item No:

Performance-rated refrigeration system

Environmentally-safe R-134a refrigerant

Unique air flow distribution allows pan product to maintain 33° - 41°F

Automatic, energy saving, non-electric condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, back mounted compressor

CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation

Spring loaded, self closing doors

Magnetic snap-in door gaskets

Heavy-duty, epoxy-coated steel shelves

19" deep, full length nylon cutting board

Insulated lid

3 5/8" casters

Completely enclosed, vented and removable case back

MODEL FEATURES

(8) 1/6 size non-recessed pans, 4" deep

Interior hanging thermometer

Field rehingeable doors

Front breathers are a unique, field assembled, bottom mounted ventilation system designed to allow cabinets to be flush against a wall or built into a counter to conserve space.



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

APPROVAL:

Mode	- I O	:4:		
WITHT	or South	•14141	11	mis
	7	77111	va u	סוניו

DIMENSIONAL DATA	
Net Capacity (cu. ft.)	13.4 (379 cu I)
1/6 Size Pans (4" deep)	8
Width, Overall (in.)	48 (1219 mm)

Depth, Overall (in.) 38 1/4 (972 mm) (incl. cutting board & bumpers) Depth, Body Only (less doors) (in.) 27 1/2 (699 mm)

Depth, Cutting Board (in.) 19 (483 mm)

Height, Overall (in.) 40 7/8 (1038 mm) (incl. 3 5/8" casters)

Shelf Area (sq. ft.) 6.8 (.6 sq m) No. of Shelves 2 No. of Doors 2

Interior Depth (in.) 19 3/8 (492 mm) 26 1/4 (667 mm) Interior Height (in.)

Interior Width (in.) 44 (1118 mm)

REFRIGERANT DATA

Condensing Unit Size (H.P.) 1/5 1620 Capacity (BTU/Hr)*

ELECTRICAL DATA

Voltage (int'l)	115/60/1 (220/50/1)
Fans	3
Total Amps (int'l)	7.3 (3.6)
10 ft. Cord/Plug [attached] (int'l)	Yes (No)

SHIPPING DATA

Weight (lbs.)	270 (122 kg)
Height - Crated (in.)	43 1/4 (1099 mm)
Width - Crated (in.)	64 (1626 mm)
Depth - Crated (in.)	46 (1168 mm)

^{*} Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.

Refrigerator



Equipped with one NEMA-5-15P Plug (varies by country)

Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.







 $\@$ Copyright 2014. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

Model Plan Views





