REFRIGERATOR MANUFACTURER
Turbo air
more durable, efficient, beautiful

4184 E. Conant St.
Long Beach, CA 90808
Tel. 310-900-1000
Fax. 310-900-1077
www.turboairinc.com

Project :	
Model # :	
Item # :	Qty :
Available W/H :	
Approval :	

Solid Door Freezer

Reach-In Top Mount
E-line

Model : EF19-1-N-V

FEATURES & BENEFITS

- ***Digital temperature control & monitor system***
  - Keep food products safe by maintaining constant temperatures.
  - Alarms that sound when doors are not sealed shut; protect against food spoilage that originates from cold air leaks.
  - Early warning alarm program detects issues before malfunction occurs.
  - Digital display allows for easy monitoring.
  - Programs interpret the condition of refrigeration systems by self-diagnosis.
  - Rapid cool-down function (Turbo Freeze).
  - Automatic evaporator fan motor delays.
- ***Hydrocarbon refrigerants (R-290)***
  With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).
- ***Cabinet construction***
  E-Line series model boasts a stainless steel exterior (door and top grille) with AL exterior (galvanized steel top, bottom, and back). Interior has a stainless steel bottom with AL interior (walls, door liners, and top duct).
- ***High-density polyurethane insulation***
  The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- ***LED interior lighting***
- ***Adjustable, heavy duty, PE (polyethylene) coated wire shelves***
- ***Self-contained system***
- ***Standard 4" dia. swivel casters with locks on the front set***
- ***Door locks standard***
- ***Solid and sturdy grille design***
- ***Top mount compressor***
- ***Anti-corrosion coated evaporator standard feature***
- ***Freezer holds -10°F ~ 0°F for the best in frozen food preservation***

NATURAL Refrigerant

Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D* x H † (inches)
EF19-1-N-V	1	18.47	3	1/2	4.9	176	25 1/4 x 31 1/2 x 72

Ver.20200605

* Depth does not include 2" for rear condensate enclosure. † Height does not include 5" for caster height.

Solid Door Freezer

Reach-In Top Mount
E-line

Model : EF19-1-N-V

ELECTRICAL DATA	
Voltage	115/60/1
Plug Type	NEMA 5-15P
Full Load Amperes	4.9
Compressor HP	1/2
Feed Wires with Ground	3
Cord Length (ft.)	9
Refrigerant	R-290
DIMENSIONAL DATA	
# of Doors	1
# of Racks Accepted	-
Net Capacity (cu. ft.)	18.47
Ext. Length Overall (in.)	25 1/4 (640mm)
Ext. Depth Overall (in.)*	31 1/2 (800mm)
Ext. Height Overall (in.)†	72 (1830mm)
Int. Length Overall (in.)	21 5/8 (550mm)
Int. Depth Overall (in.)	25 5/8 (650mm)
Int. Height Overall (in.)	57 1/4 (1456mm)
# of Shelves	3
Shelf Size (L x D) (in.)	20 3/8 x 23 1/2
Gross Weight (lbs.)	176

Design and specifications subject to change without notice.
Actual shipping weight may differ due to extra packing materials for product protection.
* Depth does not include 2" for rear condensate enclosure.
† Height does not include 5" for caster height.

PLAN VIEW

(unit : inch)



TOP VIEW



SIDE VIEW

WARRANTY : 2 Year Parts and Labor Warranty
Additional 3 Year Warranty on Compressor

STANDARD FEATURES

- *Self-contained system*
- *Standard 4" dia. swivel casters with locks on the front set*
- *Door locks standard*
- *Magnetic door gaskets*
- *Solid and sturdy grille design*

OPTIONAL ACCESSORIES

- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- 6" stainless steel leg: 30221M0600
- Additional PE coated wire shelf: K1F9000103

Ver.20200605

NATURAL Refrigerant

- Turbo Air : 800-627-0032
- GK : 800-500-3519
- Warranty : 800-381-7770
- AC : 888-900-1002

Turbo air REFRIGERATOR MANUFACTURER · GERMAN KNIFE · RADIANCE · Turbo air REFRIGERATION SYSTEM · Texaking