



**ICE CHESTS**  
EXTRA CAPACITY WITH COLD PLATE



*Covers sold separately*

JOB	
AREA	
ITEM NO.	
MODEL NO.	

MODELS	
TS Series	TSD Series
TS24IC-EC10	TSD24IC-EC10
TS30IC-EC10	TSD30IC-EC10
TS36IC-EC10	TSD36IC-EC10



**Features**

- Dent-resistant ABS top ledge
- Stainless steel legs install without tools and have rust-free thermoplastic feet



## ICE CHESTS

### EXTRA CAPACITY WITH COLD PLATE

MODEL NOS.	TS(D)24IC-EC10	TS(D)30IC-EC10	TS(D)36IC-EC10
LENGTH, INCHES (mm)	24 (610)	30 (762)	36 (914)
ICE CAPACITY, LBS. (kg)	75 (34)	95 (43.1)	115 (52.2)
SHIP WEIGHT, LBS. (kg)	100 (45.4)	110 (49.9)	120 (54.4)
FRONT & SIDES	Stainless steel, top rim ABS		
BACKSPLASH	Stainless steel, 6" high with 1" return at top, mechanically fastened and sealed to ice chest top with steel support brackets		
BACK & BOTTOM	Galvanized steel		
INTERIOR	Stainless steel with 1/4" radius corners, welded and sealed with non-exposed cold plate. Interiors can be divided with freestanding ice dividers.		
INSULATION	Foamed-in-place polyurethane		
LEGS (optional)	1-5/8" tubular, stainless steel with 1" adjustable thermoplastic foot.		
PLUMBING	Drain connection – 1/2" NPS male		
COLD PLATE	Cast aluminum plate concealed under ice chest liner. Cold plate has two full-length circuits and 8 half-length circuits. Connections 5/16" O.D. stainless steel tubing with swaged end to accept standard 1/4" I.D. beverage tubing		
OPERATING SPECIFICATIONS	Each full circuit will deliver four 6 oz. drinks per minute at 40° continuously, or 40 oz. every three minutes in a single draw (flow rate 2 oz./sec, 75° ambient, 75° degree product)		
ACCESSORIES	Covers, bottle well and cover kits, condiment trays, soda chases		

*Note: Covers not included.*

