




### **PASS-THRU WORKSTATIONS** NSE

# with Double Deep Drawn Bowls







Recessed 15A - 120V **Duplex Receptacle Located Beneath Blender Shelf** 



## **FEATURES:**

Double Deep Drawn sink bowls.

PR-44X42SP-10-L Shown

K-51 Deck mounted swing spout faucet

Insulated ice bin with 10-Circuit cold plate sealed into the bottom of Ice Bin.

Tubing chase for soda gun

Blender shelf with recessed duplex outlet located underneath shelf.

Double tier speed rail

Stainless steel legs with adjustable stainless steel bullet feet and adjustable side cross-bracing.

## SIDE PANEL MODELS (SP Series)

Side Panels with perforated drainboard shelf.

Front Apron.

Supported by side panels (legs not provided).

Sink Bowl, Sides, Ice Bin & Blender Shelf:

20 gauge, 300 stainless steel

Front Apron: 22 gauge, 300 stainless steel

Speed Rail: 22 gauge rail, 16 gauge sides, 300 stainless steel Cold Plate: Cast aluminum with 10 circuits sealed into the bottom

Legs: 1 5/8" O.D. 18 gauge, stainless steel with adjustable

stainless steel bullet feet and side cross-bracing

Insulation: 2 lb. density foam-in-place SIDE PANEL MODELS (SP Series)

Side Panels & Overshelf: 18 gauge, 300 stainless steel

**PLUMBING:** 

Faucet: 4" O.C. K-51 deck mount swing spout faucet

Faucet meet federal lead free standards Sink Bowl: 1-1/2" IPS . 3-1/2" basket drain

Ice Bin: 1/2" IPS drain

Model #	O.A. L x W	A	Sink Bowl Size	lce Capacity	Approx. Weight	Approx. Cu. Ft.		
PR-42x30-10-L or R	42" x 40"	30"	9" x 9" x 4 1/2"	70 lbs.	250 lbs.	38		
PR-42x42-10-L or R	42" x 52"	42"	9" x 9" x 4 1/2"	174 lbs.	400 lbs.	58		
SIDE PANELS WITH PERFORATED DRAINBOARD SHELF								
PR-44x30SP-10-L or R	44" x 40"	30"	9" x 9" x 4 1/2"	70 lbs.	350 lbs.	59		
PR-44x42SP-10-L or R	44" x 52"	42"	9" x 9" x 4 1/2"	174 lbs.	575 lbs.	59		

NOTE: To determine left or right hand model, Ice Bin is either Left (L) or Right (R) of the sink from the bartender side.

## **Dual Soda Gun Holder**

- Openings for a single soda gun on each end
- Fits Prestige<sup>®</sup> Pass-Thru Workstations Only

MODEL # SU-43

Factory Installed Only

# **OPTIONAL OVERSHELF FOR PASS-THRU WORKSTATIONS**

(For SP Models Only)

Removable perforated pan.

20 gauge, 300 stainless steel.

Stainless steel tubular legs.

Units with Glass Rack: 18 gauge, 302 stainless steel.

Model #	0.A. L x W	Description		Approx. Cu. Ft.
PRSO-44	44" x 16 3/4"	Single Overshelf	65 lbs.	5
PRSO-44-G	44" x 16 3/4"	Single Overshelf w/ Stemware Glass Rack	85 lbs.	5
PRDO-44	44" x 16 3/4"	Double Overshelf	125 lbs.	17
PRDO-44-G	44" x 16 3/4"	Double Overshelf w/ Stemware Glass Rack	145 lbs.	17





Single Shelf

**Double Shelf** 



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

# **DIMENSIONS and SPECIFICATIONS**

TOL Overall: ± .500" Interior: ± .250"

ALL DIMENSIONS ARE TYPICAL

