

R 301 Ultra B



D	Number of meals per service	10 to 30
	Quantity per batch in cutter function	Up to 3.3 lbs

A SALES FEATURES

The R 301 Ultra B Bowl Cutter Mixer is ideal for grinding, mincing and kneading, as well as for making mousses, emulsions and smooth stuffings. It effortlessly performs even the lengthiest task in just a few minutes, consistently producing a flawless end product.

B TECHNICAL FEATURES

R 301 Ultra B Bowl Cutter Mixer. Single phase 120/60/1. Power 1.5 HP. Speed: 1725 rpm. 3.7 L cutter bowl in stainless steel and smooth bowl-base blade assembly. 10 to 30 meals.

Select your options at the back page, **F** part.

C TECHNICAL DATA

Output power	1.5 HP
Electrical data	120V/60/1 - 12 Amp
Speed	1725 rpm
Dimensions (WxDxH)	8 1/2"x11 15/16"x15 11/16"
Rate of recyclability	95%
Net weight	23 lbs
Nema #	5-15P
Reference	R 301 U B120V/60/1

E PRODUCT FEATURES / BENEFITS

MOTOR BASE

- Direct drive induction motor (no belt) for intensive use.
- Power 1.5 HP
- Stainless steel motor shaft.
- Motor base made from heavy-duty composite material.
- Magnetic safety system, thermal failsafe and motor brake.
- **Speed:** 1725 rpm.
- **Pulse** button for better cut precision.

CUTTER FUNCTION

- 3.7 L stainless-steel cutter bowl with handle for better grip
- Bowl-base high resistance smooth blade assembly for homogeneous processing even for small amounts
- Central lid opening for adding liquid or solid ingredients during processing
- High heat- and shock-resistant see-through lid to monitor processing from start to finish
- All parts are dishwasher-safe and can easily be removed for cleaning

ACCESSORIES INCLUDED

- Cutter attachment: lid, bowl, and high resistance stainless steel smooth blade assembly with removable cap.

STANDARDS

ETL electrical and sanitation Listed/ cETL (Canada)



R 301 Ultra B

F OPTIONAL ACCESSORIES

- Coarse serrated blade assembly for kneading and grinding, ref 27288
- Fine serrated blade assembly for chopping herbs and spices, ref 27287
- Cuisine Kit ref 27396



Coarse-serrated



Fine-serrated

G ELECTRICAL DATA

120V/60/1 - delivered with cord and plug

