

Enclosed Utility Cabinets

Stainless Steel Sheet Pan and Universal Angle Models



Model 6540



All Purpose Transport and Storage

- Durable welded stainless steel construction.
- Single door and double dutch door versions are available.
- Built tough to withstand the demands of heavy utility transport operations.
- Lift-off door.
- Recessed hand grips.
- Adjustable tray slides on universal models.
- NSF listed.



Adjustable Tray Ledges



Sheet Pan Tray Ledges

General Specifications

Shall be of stainless steel construction. Universal models hold 20" x 22" (510 x 560 mm), 18" x 26" (457 x 660 mm) and 14" x 18" (356 x 457 mm) pans and trays. Sheet Pans models hold 18" x 26" (457 x 660 mm) pans and trays. Welded tubular base frame shall be 1" square, heavy gauge stainless steel tubing, with 10-gauge stainless steel reinforcing plates at corners. High density fiberglass insulated door. Door shall be attached to cabinet with heavy-duty lift-off hinges, which provide for 270° swing and be held open by magnetic door latch. Each door has paddle latch. Cabinet has recessed handles. Bottom corner bumpers shall be standard. Polyurethane tire casters in a configuration of two (2) rigid, and two (2) swivel with brake. Casters shall have a reinforced yoke welded to 10-gauge caster mounting plate. The caster mounting plate shall be secured to a 10-gauge stainless steel reinforcing stress plate via welded in place stainless steel studs. The reinforcing stress plates shall be welded to the heavy gauge tubular frame of the unit.




Lakeside Manufacturing, Inc.

4900 West Electric Avenue • West Milwaukee, WI 53219 U.S.A.

800-558-8565 • 414-902-6400 • Fax 414-902-6446 • www.eLakeside.com

Enclosed Utility Cabinets

Stainless Steel Sheet Pan and Universal Angle Models



Spec.#

Dimensions

Sheet Pan (18" x 26") Models

Models	Pan Capacity		Ledge Spacing	Door Type	Overall Size			Case Weight	
	Full Size	Half Size			W	D	H (A)	Lbs.	(kg)
6532	7	14	3" (76)	Single	25.5" (648)	34" (864)	32" (813)	125	(57)
6533	11	22	3" (76)	Single	25.5" (648)	34" (864)	45" (1143)	165	(75)
6534	16	32	3" (76)	Single	25.5" (648)	34" (864)	60" (1524)	205	(93)
6536	19	38	3" (76)	Single	25.5" (648)	34" (864)	69" (1753)	230	(104)

Options

- Full Perimeter Bumper
- All Swivel Lake-Glide Casters
- Floor Lock Centered (6" Casters)
- Additional Tray Slides
- Transport Door Latch
- Magnetic Door Latch
- Clear Polycarbonate Door Panel
- Vented Door
- Left-Hand Door Hinging
- Transport Package

Universal Angle Models

Models	Pan Capacity		Ledge Spacing	Door Type	Overall Size			Case Weight	
	Full Size	Half Size			W	D	H (A)	Lbs.	(kg)
6537	5	10	4.5" (114)	Single	28" (711)	34" (864)	33" (838)	140	(59)
6538	7	14	4.5" (114)	Single	28" (711)	34" (864)	42" (1067)	150	(77)
6539	11	22	4.5" (114)	Single	28" (711)	34" (864)	60" (1524)	215	(104)
6540	13	26	4.5" (114)	Single	28" (711)	34" (864)	69" (1753)	255	(114)

Universal Ledges Accommodate The Following Per Slide:

- 1 ea. 18" x 26" Pan
- 1 ea. 15" x 20" Tray
- 1 ea. 16" x 22" Tray
- 1 ea. 20" x 22" Pan
- 2 ea. 14" x 18" Pan
- 2 ea. 13" x 18" Pan
- 2 ea. 12" x 20" Pan (3" Deep)

Measurements in () denote metric millimeters, unless otherwise specified.

AIA#



Lakeside Manufacturing, Inc.

4900 West Electric Avenue • West Milwaukee, WI 53219 U.S.A.
800-558-8565 • 414-902-6400 • Fax 414-902-6446 • www.eLakeside.com