

Project

Item #

Model Specified:

CSI Section 114000

Freezer Equipment Stands/ Self-Contained

Two & Four Drawer Models, 34" Deep



Stainless Exterior
& Interior

2-Drawer Models TE048LT & TE060LT
4-Drawer Models TE072LT & TE084LT



Model TE084LT
(shown as supplied standard)

Traulsen's TE Series freezer equipment stands are designed for use along the cook line where cabinet strength and system performance really matter. Their rear mounted evaporators keep food cold in very warm kitchen environments despite frequent drawer openings. They also offer greater capacity, as each drawer accommodates 6" (15 cm) deep pans, and a variety of other features making them ideal for the equipment stand application. Drawers include a stay open and self closing feature, as well as a guard to protect the gasket from damage. Grease accumulation on the condenser is prevented by an easy to remove and clean filter. Even installation is facilitated through use of factory installed casters mounted on an adjustable rail, making it easy to position these around such common floor obstructions as drains, junction boxes, and gas connections.

Standard Product Features

- Stainless Steel Exterior & Interior
- Stainless Steel Top w/Drip Guard (marine) Edge
- INTELA-TRAUL® Microprocessor Control System
- Balanced, Self-Contained Refrigeration System Using R-404A
- Front-Breathing Design For "Zero-Clearance" Installation
- Non-Electric Automatic Condensate Evaporator
- Condenser Filter
- Hot Gas Defrost
- Controllable Anti-Condensate Drawer Perimeter Heaters
- Full Length Drawer Handle With Gasket Guard
- Magnetic Snap-In EZ-Clean Door Gasket(s)
- Drawers Accommodate 12" x 20" x 6" (30 x 51 x 15 cm) Pans (pans supplied by others)
- Self-Closing Drawers With Stay Open Feature
- Stainless Steel Drawer Slide
- Side, Front & Rear Access Panel For Ease of Service & Maintenance
- NEMA 5-15P Plug With 9' (2.7 m) Cord & Cord Retainer
- 4" (10 cm) Casters On Adjustable Channel Moving System
- Three Year Parts And Labor Warranty
- Five Year Compressor Warranty

Options & Accessories

- Set Of 6" (15 cm) High Stainless Steel Legs in Lieu Of Casters
- 6" (15 cm) Cabinet Length Extension
- Stainless Steel Exterior Finished Back



Intertek
4004142
Conforms to ANSI/NSF-7



CERTIFIED TO
ANSI/NSF 7



This unit is listed to the applicable UL, CSA and NSF Standards by an approved NRTL. Consult the factory or units data plate for approval information.

Approval: _____



TRAULSEN
4401 BLUE MOUND RD.
PHONE 1 (800) 825-8220
Website: www.traulsen.com

FT. WORTH, TX 76106
FAX-MKTG. 1 (817) 624-4302

Project	Quantity	Item #
Model Specified:		CSI Section 114000

Specifications

Construction, Hardware and Insulation

Cabinet exterior front, sides, louver assembly and drawers are constructed of 430 stainless steel, exterior back and bottom are constructed of heavy gauge galvanized steel. Cabinet interior sides are constructed of a 400 series stainless steel, top and bottom are constructed of a 300 series stainless steel. A set of 4" (10 cm) high casters are included standard. Gasket profile and Santoprene® material simplify cleaning and increase overall gasket life. Both the cabinet and drawers are insulated with an average of 2" (5 cm) thick high density, non-CFC, foamed in place polyurethane.

Controller

The easy to use water resistant INTELA-TRAUL® microprocessor control system is supplied standard. It includes a 3-Digit LED Display with °F or °C Temperature Scale Display Capability, and an RS485 data port. In addition it includes audio/visual alarms for: Hi/Lo Cabinet Temperature, Clean Condenser, Evaporator Coil and Discharge Line Sensor Failures, and Power Supply Interruption.

Refrigeration System

The left side mounted, self-contained, balanced refrigeration system using R-404A refrigerant features a hot gas defrost, TXV, air-cooled hermetic compressor, automatic condensate evaporator, and a dedicated rear-mounted evaporator design which distributes cold air through each drawer section. A 9' (2.7 m) NEMA cord and retainer is provided. Standard operating temperature is -5 to 0°F (-20 to -17°C).

Drawers

Each heavy-duty drawer is designed to accommodate 12" x 20" x 6" (30 x 51 x 15 cm) deep pans constructed with stainless steel drawer slides and 2" (5 cm) diameter stainless steel rollers. Drawers include both a self-closing and stay-open feature.

Warranties

Both a three year parts and labor warranty and a five year compressor warranty (self-contained models only) are provided standard.

FREEZER	TE048LT	TE060LT	TE072LT	TE084LT
Length Overall in.	48 (121.9 cm)	60 (152.5 cm)	72 (182.9 cm)	84 (213.4 cm)
Depth - Cabinet Only in.	32 (81.3 cm)	32 (81.3 cm)	32 (81.3 cm)	32 (81.3 cm)
Depth - with Drawer Open	54 ^{5/8} (138.75 cm)	54 ^{5/8} (138.75 cm)	54 ^{5/8} (138.75 cm)	54 ^{5/8} (138.75 cm)
Depth - Over Handle in.	34 ^{1/16} (88.1 cm)	34 ^{1/16} (88.1 cm)	34 ^{1/16} (88.1 cm)	34 ^{1/16} (88.1 cm)
Height - in. ¹	26 ^{1/16} (66.2 cm)	26 ^{1/16} (66.2 cm)	26 ^{1/16} (66.2 cm)	26 ^{1/16} (66.2 cm)
Max Top Load Capacity lbs.	625 (283 kg)	1200 (544 kg)	1200 (544 kg)	1500 (680 kg)
Pan Capacity 12" x 20" x 6" ²	4	6	6 ²	8
Pan Orientation	Side by Side	Side by Side	Side by Side	Side by Side
Drawers Per Cabinet	2	2	4	4
Gross Weight-crated lbs. ³	435 (197 kg)	558 (253 kg)	606 (275 kg)	675 (306 kg)
ELECTRICAL DATA				
Voltage	115/60/1	115/60/1	115/60/1	115/60/1
Full Load Amperes	8.2	8.7	11.2	11.2
NEMA Plug Type	5-15P	5-15P	5-15P	5-15P
REFRIGERATION DATA				
Refrigerant	R-404A	R-404A	R-404A	R-404A
BTU/HR - HP ⁴	1929 (¹ / ₂ HP)	1920 (¹ / ₂ HP)	2570 (³ / ₄ HP)	2570 (³ / ₄ HP)










NOTE: Figures in parentheses reflect metric equivalents.

1= Height overall on 4" (10 cm) casters in.

2= TE072LT shown with pan capacity of (6) 12"x20"x6" & an additional (6) 1/6 size pans.

3= For shipping weights and dimensions please refer to form TR35875.

4= Based on a 90 degree F ambient and 20 degree F evaporator.



Equipped With One NEMA 5-15 P Plug

NOTE: When ordering please specify: Voltage and any Options.

Continued product development may necessitate specification changes without notice.

TR36065 (REV. 10-31-17)

TRAULSEN
4401 BLUE MOUND RD.
PHONE 1 (800) 825-8220
Website: www.traulsen.com

FT. WORTH, TX 76106
FAX-MKTG. 1 (817) 624-4302

